Assignment -4

Student Name	Haripriya U
Student Roll no	720319106012

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events. Upload document with wokwi share link and images of IBM cloud

Link: https://wokwi.com/projects/348548872665039443

```
#include <WiFi.h>
#include <PubSubClient.h>
WiFiClient wifiClient;
#define trigpin
                   18
#define echopin
                   5
String data3;
#define ORG "kabw0z"//IBM ORGANITION ID
#define DEVICE_TYPE"smartfarming"//Device type mentioned in ibm watson IOT
Platform
#define DEVICE_ID "sf1234sf"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "haripriya23"
#define speed 0.034
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char topic[] = "iot-2/cmd/home/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883, wifiClient);
void publishData();
String command;
String data="";
long duration;
float dist;
void setup()
```

```
{
  Serial.begin(115200);
 wifiConnect();
  pinMode(trigpin, OUTPUT);
  pinMode(echopin, INPUT);
mqttConnect();
}
void wifiConnect() {
  Serial.print("Connecting to "); Serial.print("Wifi");
 WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
}
void loop()
{
    int pulseWidth = 0;
    digitalWrite(trigpin, HIGH);
    delayMicroseconds(100);
    digitalWrite(trigpin, LOW);
    pulseWidth = pulseIn(echopin, HIGH);
    Serial.print("AlertDistance: ");
    Serial.println(pulseWidth/58);
  publishData();
  if (!client.loop()) {
    mqttConnect();
  }
}
void mqttConnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting MQTT client to "); Serial.println(server);
    while (!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }
    initManagedDevice();
    Serial.println();
```

```
}
}
void initManagedDevice() {
  if (client.subscribe(topic)) {
    // Serial.println(client.subscribe(topic));
    Serial.println("IBM subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void publishData()
  digitalWrite(trigpin, LOW);
  digitalWrite(trigpin,HIGH);
  delayMicroseconds(10);
  digitalWrite(trigpin,LOW);
  duration=pulseIn(echopin,HIGH);
  dist=duration*speed/2;
  if(dist<100){</pre>
    String payload = "{\"Normal Distance\":";
    payload += dist;
    payload += "}";
    Serial.print("\n");
    Serial.print("Sending payload: ");
    Serial.println(payload);
    if (client.publish(publishTopic, (char*) payload.c_str())) {
      Serial.println("Publish OK");
    }
  }
    if(dist>101 && dist<111){</pre>
    String payload = "{\"Alert distance\":";
    payload += dist;
    payload += "}";
    Serial.print("\n");
    Serial.print("Sending payload: ");
    Serial.println(payload);
     if(client.publish(publishTopic, (char*) payload.c_str())) {
      Serial.println("Warning crosses 110cm -- it automaticaly of the loop");
    }else {
      Serial.println("Publish FAILED");
```

```
}
  }
  }
  void callback(char* subscribeTopic, byte* payload, unsigned int payloadLength){
  Serial.print("callback invoked for topic:");
  Serial.println(subscribeTopic);
  for(int i=0; i<payloadLength; i++){</pre>
      dist += (char)payload[i];
  }
  Serial.println("data:"+ data3);
  if(data3=="lighton"){
      Serial.println(data3);
  }
  data3="";
M Fwd: Sign in to V: X W sketchino - Wok: X W New ESP32 Proje: X SAKSHAYA COLLE: X W Your Projects on X New Tab
                                                                                                                                     e ☆ • :
← → C  wokwi.com/projects/348548872665039443
₩OKWî 🕞 SAVE 🔻 🥕 SHARE 💛 sketch.ino 🖍
                                                                                                                                          Docs <u></u>
 sketch.ino diagram.json libraries.txt Library Manager *
                                                                              Simulation
       #include <WiFi.h>
#include <PubSubC</pre>
                                                                                                                                       Ō00:03.899 (€)44%
                                                                             5 • •
        #include <PubSubClient.h>

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength
       #define DEVICE_ID "sf1234sf"
#define TOKEN "haripriya23"
       char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
       PubSubClient client(server, 1883, callback ,wifiClient);
       const int trigPin = 5;
const int echoPin = 18;
        #define SOUND_SPEED 0.034
       long duration;
float distance;
       void setup() {
    serial.begin(115200);
    pinMode(trigPin, OUTPUT);
    pinMode(echoPin, INPUT);
    wificonnect();
                                                                            Connecting to ...
                                                                            WiFi connected
                                                                            IP address:
                                                                            Reconnecting client to kabw0z.messaging.internetofthings.ibmcloud.com
       {
digitalWrite(trigPin, LOW);
islawWicroseconds(2);
```

Output

Link: https://v9y7gx.internetofthings.ibmcloud.com/dashboard/devices/browse

