SPRINT-4

CODE IMPLEMENTATION

```
import serial
import time
import csv
import numpy as np
import matplotlib.pyplot as plt
ser = serial.Serial('/COM6',9600)
ser_bytes = ser.readline(10)
print (ser_bytes)
ser.flushInput()
while True:
try:
ser_bytes = ser.readline()
decoded_bytes = float(ser_bytes[0:len(ser_bytes)-2].decode("utf-8"))
print(decoded_bytes)
```

```
temp = float(decoded_bytes(1:3))
turb = float(decoded_bytes(4:6))
pH = float(decoded_bytes(6:8))
with open("test_data.csv","a") as f:
writer = csv.writer(f,delimiter=",")
writer.writerow([time.time(),decoded_bytes])
except:
print("Keyboard Interrupt")
ser.close()
break()
t = np.arange(0.0, 2.0, 0.01)
s = 1 + np.sin(2*np.pi*t)
plt.plot(t, s)
plt.xlabel('time (s)')
plt.ylabel('Celsisus (C)')
plt.title('Temperature')
plt.grid(True)
plt.savefig("Temperature.png")
plt.show()
Serial.begin(9600);
sensors.begin();
int sensorValue = analogRead(A1);
voltage = sensorValue * (5.0 / 1024.0);
}
void loop(void)
```

```
{
sensors.requestTemperatures();
Celcius=sensors.getTempCByIndex(0);
Fahrenheit=sensors.toFahrenheit(Celcius);
for(int i=0;i<10;i++)
buf[i]=analogRead(analogInPin);
delay(10);
}
for(int i=0;i<9;i++)
for(int j=i+1;j<10;j++)
{
if(buf[i]>buf[j])
{
temp=buf[i];
buf[i]=buf[j];
buf[j]=temp;
}
n = 256
X = np.linspace(-np.pi, np.pi, 256, endpoint=True)
C,S = np.cos(X), np.sin(X)
plt.plot(X, C)
plt.plot(X,S)
plt.show()
```

```
print ("Visualization of real time sensor
Data.")print("/n")
while True:
try:
ser_bytes = ser.readline()
decoded_bytes = float(ser_bytes[0:len(ser_bytes)-
2].decode("utf-8"))print(decoded_bytes)
temp =
float(decoded_bytes(1:3))
turb =
float(decoded_bytes(4:6))
pH =
float(decoded_bytes(6:8))
with
open("test_data.csv","a")
as f:writer =
csv.writer(f,delimiter=",")
writer.writerow([time.time(),decoded_byt
es])except:
print("Keyboard
Interrupt")
ser.close()
break()
t = np.arange(0.0,
2.0, 0.01)s = 1 +
np.sin(2*np.pi*t)
plt.plot(t, s)
```