IBM ASSIGNMENT - 4

TEAM ID: PNT2022TMID26570

NAME: LOUIS AKASH J

ROLL NO: 212919104027

1.Write Code and connections in wokwi for ultrasonic sensor. whatever distance is less than 100 cms send "Alert" to ibm cloud aand display in device recent events.


```
Solution:
//Pins
const int TRIG PIN = 7;
const int ECHO_PIN = 8;
//Anything over 400 cm (23200 us pulse) is "out of range"
const unsigned int MAX_DIST = 23200;
void setup() {
// The Trigger pin will tell the sensor to range find
Pin Mode(TRIG_PIN, OUTPUT);
digital Write(TRIG PIN, LOW);
//Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensor
pinMode(ECHO PIN, INPUT);
// We'll use the serial monitor to view the sensor output
```

```
Serial.begin(9600);
}
void loop() {
unsigned long t1;
unsigned long t2;
unsigned long pulse_width;
float cm;
float inches;
// Hold the trigger pin high for at least 10 us
digitalWrite(TRIG PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
// Wait for pulse on echo pin
while (digitalRead( ECHO_PIN )==0 );
// Measure how long the echo pin was held high (pulse width)
// Note: the micros() counter will overflow after-70 min
t1= micros ();
 while (digitalRead(ECHO_PIN) == 1);
 t2= micros ();
 pulse_width = t2-t1;
// Calculate distance in centimeters and inches. The constants
//are found in the datasheet, and calculated from the assumed speed
// of sound in air at sea level (- 340m/s)
cm=pulse_Width / 58;
inches = pulse_width/148.0;
```

```
// Print out results
if (pulse width >MAX DIST){
Serial.println("Out of range");
} else {
Serial.println("*******************************);
Serial.print("The Measured Distance in cm: ");
Serial.println(cm);
if( cm < 100 ){
   //while(true){
   Serial.println("Alert!!");
   //}
}
Serial.print("******************************);
}
//wait at least 1000ms before next measurement
Delay(1000);
}
```

Output:

1. If the distance is less than 100 cms, it alerts.



2. If the distance is more than 100 cms, it won't alert

```
WOKWI B SAVE
                                                                                                                                                                                        Docs
              diagram json • Library Manager •
                                                                                                      Simulation
 hc-sr04.ino
                                                                                                                                                                                 Ō00:00.599 (?)62%
          const int TRIG_PIN = 7;
          const int ECHO_PIN = 8;
         // Anything over 400 cm (23200 us pulse) is "out of range" const unsigned int MAX_DIST = 23200;
          void setup() {
            // The Trigger pin will tell the sensor to range find
pinMode(TRIG_PIN, OUTPUT);
    11
            digitalWrite(TRIG_PIN, LOW);
                                                                                                                                  OO UNO
   14
15
           //Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensor
pinMode(ECHO_PIN, INPUT);
    17
18
            // We'll use the serial monitor to view the sensor output
    19
            Serial.begin(9600);
                                                                                                                                  POWER ANALOG I
    22
          void loop() {
    24
25
            unsigned long t1;
            unsigned long t2;
                                                                                                   The Measured Distance in cm : 227.10
             unsigned long pulse_width;
            float cm;
float inches;
                                                                                                   *******************
                                                                                                                                                            Activate Windows
                                                                                                                                                            Go to Settings to activate Windows
```

3. Simulation and code execution

