Assignment -4

SMS SPAM Classification

signment Date 08 October 2022	
Student Name	Ashwini K
Student Roll Number	612919103008

- Download the Dataset: Dataset
- Import the necessary libraries

Import the necessary libraries

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import Adam
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

Read dataset and do pre-processing

```
messages = pd.read_csv('../content/spam.csv',encoding = 'latin-1')
messages.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro	NaN	NaN	NaN

Preprocessing the Data

Pre-processing the dataset

Preprocessing the Data

```
messages.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
from wordcloud import WordCloud, STOPWORDS, ImageColorGenerator
X = messages.v2
Y = messages.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.25)
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

Create Model

Creating the Model

```
inputs = Input(shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
```

• Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
layer = LSTM(128)(layer)
layer = Dense(128)(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1.5)(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #
input_1 (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 128)	91648
dense (Dense)	(None, 128)	16512
activation (Activation)	(None, 128)	0
dropout (Dropout)	(None, 128)	0
dense_1 (Dense)	(None, 1)	129
activation_1 (Activation)	(None, 1)	0

Total params: 158,289 Trainable params: 158,289 Non-trainable params: 0

Compile the Model


Compile the Model

```
model.compile(loss='binary_crossentropy',optimizer=Adam(),metrics=['accuracy'])
```

Fit the Model

Fit the Model

```
history = model.fit(sequences_matrix,Y_train,batch_size=20,epochs=10,validation_split=0.2)
Epoch 1/10
168/168 [==
            ==========] - 51s 283ms/step - loss: 0.2100 - accuracy: 0.9324 - val_loss: 0.0622 - val_accuracy: 0.9821
Epoch 2/10
=========] - 39s 231ms/step - loss: 0.0250 - accuracy: 0.9940 - val_loss: 0.0645 - val_accuracy: 0.9844
168/168 [==:
Epoch 4/10
Epoch 5/10
             Epoch 6/10
168/168 [===
            ========== ] - 33s 196ms/step - loss: 0.0088 - accuracy: 0.9979 - val loss: 0.0763 - val accuracy: 0.9773
Epoch 7/10
168/168 [====
            Epoch 8/10
168/168 [===
            Epoch 9/10
      metrics = pd.DataFrame(history.history)
metrics.rename(columns = {'loss': 'Tra
def plot_graphs1(var1, var2, string):
                    'Training_Loss', 'accuracy': 'Training_Accuracy', 'val_loss': 'Validation_Loss', 'val_accuracy': 'Validation_Accurac
 metrics[[var1, var2]].plot()
plt.title('Training and Validation ' + string)
plt.xlabel ('Number of epochs')
 plt.ylabel(string)
 plt.legend([var1, var2])
plot_graphs1('Training_Accuracy', 'Validation_Accuracy', 'accuracy')
```



Save The Model

Save the Model

```
model.save('Spam_sms_classifier.h5')
```

Test The Model

Test the Model

Accuracy: 0.09085