PROJECT-BASED EXPERIENTIAL LEARNING PROGRAM (NALAIYA THIRAN) SIGNS WITH SMART CONNECTIVITY FOR BETTER ROAD SAFETY

A PROJECT REPORT

Submitted by

PRADEEPKUMAR S

ARUN PANDIYAN R

SUDHAN KARTHICK K

KARTHIC BABU KG

TEAM ID: PNT2022TMID17542

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

TAGORE ENGINEERING COLLEGE

(Approved by AICTE, Affiliated to ANNA University)





NOVEMBER 2022

CONTENT

1. INTRODUCTION

- 1.1 Project Overview
- 1.2 Purpose

2. LITERATURE SURVEY

- 2.1 Existing problem
- 2.2 References
- 2.3 Problem Statement Definition

3. IDEATION & PROPOSED SOLUTION

- 3.1 Empathy Map Canvas
- 3.2 Ideation & Brainstorming
- 3.3 Proposed Solution
- 3.4 Problem Solution fit

4. REQUIREMENT ANALYSIS

- 4.1 Functional requirement
- 4.2 Non-Functional requirements

5. PROJECT DESIGN

- 5.1 Data Flow Diagrams
- 5.2 Solution & Technical Architecture
- 5.3 User Stories

6. PROJECT PLANNING & SCHEDULING

- 6.1 Sprint Planning & Estimation
- 6.2 Sprint Delivery Schedule
- 6.3 Reports from JIRA

7. CODING & SOLUTIONING (Explain the features added in the project along with code)

- 7.1 Feature 1
- 7.2 Feature 2
- 7.3 Database Schema (if Applicable)

8. TESTING

- 8.1 Test Cases
- 8.2 User Acceptance Testing

9. RESULTS

9.1 Performance Metrics

10. ADVANTAGES & DISADVANTAGES

11. CONCLUSION

GitHub & Project Demo Link

1.INTRODUCTION:

Based on current research and development efforts, we can all be fairly certain that smart road signs will be broadly utilized in the years to come. They serve as one of the major components of an emerging system designed to enhance the current infrastructure. These indicators are useful tools, and they can have a positive impact on all who share the roads. Most importantly, this type of signage has the potential to improve our way of life.

When vehicles approach such a sign on the roadway, vital information is imparted to their drivers via their dashboard or their head-up display. Along with the visual data, voice narration may also be used to indicate changing roadway conditions. Instead of trying to read passing road indicators, drivers are thus better able to pay attention to the road.

The road signage of the future might also be used to transmit crucial data to driverless cars. These signs may appear to humans to be conventional road indicators.

However, the information transmitted from a given sign is "visible" to the vehicle's infrared light. The sign alerts oncoming cars to slow down due to a change in the roadway. This sort of transmission can even help autonomous vehicles to stay in their lanes.

Smart signs provide:

- Preventing wrong-way crashes
- Better traffic management and safety
- Increased cost efficiency
- Combating poor visibility

1.1 PROJECT OVERVIEW:

The primary aim for developing these route placards is to make the roads safer for all of us. The enhanced signage creates a more efficient experience for drivers. It can also complement the system designs of driverless cars and to help people automate the roads by providing them with a Web App through which they can monitor the parameters of the road like temperature, speed limit, and visibility of the road. They also show guides for schools and provide services of displaying hospitals, and restaurant signs accordingly.

1.2 PURPOSE:

Clearly, intelligent roadway smart signs can be a vital part of our driving experience. They enable a better way for drivers to access the information they need in real time on the roads. These signs can increase awareness of upcoming issues, which people might otherwise discover too late.

They may also augment the functionality of driverless vehicles. The value of implementing this technology should not be underestimated. Smart roadway indicators have the potential to increase cost-efficiency, which eases the burden on governments and taxpayers. They facilitate a smoother driving process for both human drivers and autonomous vehicles.

The smart signs can be more user-friendly than the analog route signs we currently employ. Above all, they may ultimately lead to a safer network of roads for everyone.

These smart connected sign boards get the speed limitations from a web app using weather API and update automatically, based on the weather changes the speed may increase or decrease.

Based on the traffic and fatal situations the diversion signs are displayed. Different modes of operation can be selected with the help of buttons.

<u> 2. LITERATURE SURVEY :</u>

2.1 EXISTING PROBLEM:

Road traffic safety refers to the methods and measures used to prevent road users from being killed or seriously injured. Growth in population has led to growth in technology. People use cars in large numbers and the number of accidents taking place is increasing daily. Road accidents are undoubtedly the most frequent happening cases and overall, the cause of the most damage. There are many dangerous roads in the world like mountain roads, narrow curve roads, and T roads. Some mountain roads are very narrow and they have many curves. The problem with these curve roads is that the drivers are not able to see the vehicle or obstacles coming from another end of the curve. If the vehicles inatreat speed then it is difficult to control and there are chances of falling off a cliff. Hence there is a fored of many road safety systems. By us advanced technology to create smart connectivity for better road safety.

2.2 REFERENCES:

ZiZ TELLET (CES.					
BOOK/	TOPIC	AUTHOR	YEAR	INFERENCE	
JOURNAL		NAME			
	Advances in smart roads for	Chai K.Toh, Julio		In the paper,they discussed therecent 10	
THE	future smart	A. Sanguesa,		technological advances	
ROYA	cities	Juna C. Cano		and	
L SOCIETY		and Francisco			
PUBLISHING		J.			

		Martinez	developments in the area of smart roads. They include: (i) energy-harvesting road, (ii) musical road, (iii) automatic- weighing road, (iv) electrifiedroad, (v) roadswith wireless digital traffic signs, (vi) roads with automatic traffic violation detection and notification, (vii) roads that talk (V2X), (viii) roads with smart intersections, (ix) roads with fast emergency rescue, and (x) roads with smart street lights. These advances will aid in the progress, development and realization of smart transport for future smart cities.
ICT INNOVATIONS	Things Based	Arnav Thakur, Reza Malekian,	Vehicle to vehicle communication and vehicle to infrastructure based channels are studied. Wireless the

2017	Intelligent Transportation Systems	Dijana Capeska Bogatinoska	2017	suitable for
				communication channels are technologies

		studied. Additional benefits and
		services that can be


				added to a system with the IoT approach are also studied. The effectiveness of such a system is studied with the use of validation framework. Multiple case studie of current and futur IoT based ITS along with the challenges in th application i discussed.
JOURNAL	Development	Eric M Masatu,	2022	In this study a
O F ADVANCED TRANSPORTATIO N	and Testing of Road Signs Aler t System Using a Smart Mobile Phone	Ramadhani Sinde, Anael Sam	2022	system for alerting drivers about road signs has been developed and tested using a smart mobile phone.
SAGE JOURNALS	Reading	Enes Karaaslan,	2021	The objective of
	Vehicular	Burak Sen, Tolga		this paper is to
	Messages from	Ercan, Haluk		investigate the
	Smart Road	Laman,James pol		operational
	Signs: A Novel			challenges of the
	Method to			proposed low-cost
	Support Vehicle-			solution in
	to-Infrastructure			different V2I

in Rural Settings	applications, including a Map Data message in an unsignalized traffic intersection, traveler information message in a work zone, and a redlight violation
-------------------	---

	1		
		warning	with th
		help of a s	mart
		sign.	Th
		proposed	
		sy	stem
		showed	
		SC	me
		important	
		advantage	es,
		su	ch as
		invulneral	oility to
		th	ird-
		party alte	rations
			an
		robust	
		(peratio
		under	
		ha	ırsh
		environme	enta
		I condition	ıs.

2.3 PROBLEM STATEMENT DEFNITION:


In present Systems the road signs and the speed limits are Static. But the road signs can be changed in some cases. We can consider some cases when there are road diversions due to heavy traffic or due to accidents then we can change the road signs accordingly if they are digitalized.




Problem	I am	I'm trying	But	Because	Which makes me
Statement (PS)	(Customer)	to			feel
PS-1	Traveller	Reach the	The routes	Any mislead	Perplex and
		correct	are	in road sign	frustrated
		place in	confusing	instructions	
		correct	as	can cause	
		time	constructio	traffic and	
			n works are	congestion	
			on process		
PS-2	Traveller	Travel in a	It takes	Of weather	Enraged and
		safer	long time	conditions	uncomforta
		and a		and	ble
		faster		environment	
		way		al changes	

3.IDEATION & PROPOSED SOLUTION:

3.1 EMPATHY MAP CANVAS:



3.2 IDEATION AND BRAINSTORMING:




3.3 PROPOSED SOLUTION:

S.No	Parameter	Description
1.	Problem Statement (Problem to be solved)	Road safety management refers to the process of identifying safety problems, devising potential strategies to combat those safety problems, and selecting and implementing the strategies. Effective safety management is also proactive and looks for ways to prevent safety problems before they arise. High-quality safety data should be used to determine the nature of road safety problems and how best to solve them.
		These data can be used to identify large-scale or small safety problems. Other data, such as roadway characteristics, traffic volume, citations, and driver history, can be integrated with crash data to assist in identifying safety trends and highpriority locations.

2.	Idea / Colution description	Connectivity also allows
۷.	Idea / Solution description	Connectivity also allows
		monitoring the flow velocity in
		real-time so you can warn drivers
		on the screen of their cars that
		they are exceeding the speed
		limit . They also warn the pilot to
		park in prohibited areas or other
		behaviors that do not comply with
		the law, thus avoiding penalties for
		drivers.
3.	Novelty / Uniqueness	It proposes a system that has digital
		signboards on which the signs can be
		changed dynamically. If there is
		rainfall then the roads will be slippery
		and the speed limit would be
		decreased. There is a web app through
		which you can enter the data of road
		diversions, and accident-prone areas,
		and the information sign boards can
		be entered through the web app. This
		data is
		retrieved and displayed on the
		signboards accordingly.
4.	Social Impact / Customer	From speed limits to directions on
	Satisfaction	where and when to turn, traffic signs
		provide a wealth of information.
		Following traffic signs helps to keep
		everyone on the road safe by
		reducing the chances of drivers
		colliding with other vehicles,
		pedestrians, or cyclists.
5.	Business Model (Revenue	IoT is already working to ensure road
	Model)	safety in areas such as vehicle
		maintenance, improved circulation,
		navigation, and monitoring of
		environmental conditions or the state
		of the roads. IoT obtains the majority
		of its data with the help of connected
		cars. These incorporate a large number
		of sensors that establish
<u> </u>		

		communication with the cloud, other vehicles, and devices.
6.	Scalability of the Solution	Traffic management networks for improving safety and reducing congestion. The network uses speed cameras to provide warning signs for hazardous conditions and sends automated traffic diversion signals that control traffic.

<u>**3.**</u> 4.PROBLEM SOLUTION FIT:



4. REQUIREMENT ANALYSIS:

4.1 FUNCTIONAL REQUIREMENT:

Following are the functional requirements of the proposed solution.

FR	Functional	Sub Requirement (Story / Sub-Task)
No.	Requirement (Epic)	
FR-1	User Registration	Web App
		Installation
		Register with
		Gmail
FR-2	User Confirmation	Confirmation
		via Email
		Confirmation
		via OTP

FR-3	Proof of Identity	Customers can register one mail account on their respective mobile.
FR-4	Credit Score and History	Purchaser has to get the premium package to access the information. Customers can check the history of the road signals.

4.2.NON–FUNCTIONAL REQUIREMENTS:

Following are the non-functional requirements of the proposed solution.

FR	Non-Functional	Description
No.	Requirement	
NFR-1	Usability	Customers can use the application in almost all web browsers. It will indicate the people through audio or notifications about road safety, and weather conditions.
NFR-2	Security	Customers are asked to create an account for themselves using their email which is protected with an 8character-long password, making it more
NFR-3	Reliability	Customers can raise their queries and will be replied with a valid reply, as soon as possible, making the application even more reliable and trustworthy.


NFR-	Performance	Customers will have a smooth experience while using the application, as it is simple and well- optimized.
NFR- 5	Availability	Application is available 24/7 as it is hosted on IBM Cloud
NFR-	Scalability	In the future, maybe crossplatform mobile applications can be developed as the user base grows.

secure.

5.PROJECT DESIGN

5.1. DATA FLOW DIAGRAMS

A Data Flow Diagram (DFD) is a traditional visual representation of the information flows within a system. A neat and clear DFD can depict the right amount of the system requirement graphically. It shows how data enters and leaves the system, what changes the information, and where data is stored.




5.2 SOLUTION AND TECHNICAL ARCHITECTURE

SOLUTION ARCHITECTURE:


Solution architecture is a complex process – with many sub-processes – that bridges the gap between business problems and technology solutions.

Its goals are to:

- Find the best tech solution to solve existing business problems.
- Describe the structure, characteristics, behavior, and other aspects of the software to project stakeholders.
- Define features, development phases, and solution requirements.
- Provide specifications according to which the solution is defined, managed, and delivered.



TECHNICAL ARCHITECTURE:



COMPONENTS AND TECHNOLOGIES:

5	S.No	Component	Description	Technology

1.	User Interface	How user interacts with application e.g. Web UI, Mobile App, Chatbot etc.	HTML, CSS, JavaScript / Angular Js / React Js etc.
2.	Application Logic-2	Logic for a process in the application	IBM Watson STT service
3.	Application Logic-3	Logic for a process in the application	IBM Watson Assistant
4.	Cloud Database	Database Service on Cloud	IBM DB2, IBM Cloudant etc.
5.	External API-1	Purpose of External API used in the application	IBM Weather API, etc

APPLICATION CHARACTERISTICS:

S.No Characteristics Description Technology

1.	Security Implementations	Strong security	Firewall,
		system that	Firebase, cyber
		anyone without	resiliency
		login credentials	strategy
		and hackers are	
		not allowed to	
		enter the network.	
2.	Scalable Architecture	Easy to expand the	IoT, internet.
		operating range by	
		increasing the	
		bandwidth of the	
		network.	
3.	Availability	Available anytime	IBM Cloud
		and everywhere	
		24/7 as long as the	
		user is signed into	
		the network.	
4.	Performance	Supports a large	IBM Cloud
		number of users to	
		access the	
		technology	
		simultaneously.	


5.3 USER STORIES:

User Type	Functiona l Requirem ent (Epic)	User story No.	User Story	Acceptance criteria	Priority	Release
Custome r (Mobile user)	Registration	USN-1	I can get my speed limitation using weather application	I can receive speed limitations	High	Sprint-1
		USN-2	As a user, I can register for the application by entering my email, password, and confirming my password. As a user	I can access my account / dashboard	Medium	Sprint-2
		USN-3	As a user, I can increase or decrease my speed according to the weather change	I can increase or decrease my speed	High	Sprint-1
		USN-4	As a user, I can I get my traffic diversion signs depending on the traffic and fatal stn.	I can access my traffic status ahead in my travel	Medium	Sprint-1

Login	USN-5	As a user, I can log into the open weather map by entering email & password	I can access the application through my Gmail login	High	Sprint-2
Interface	USN-6	As a user the interface should be simple and	I can access the interface easily	High	Sprint-1

			easily accessible			
Custome r(Webus er)	Data generation	USN-7	As a user I use open weather application to access the data regarding the weather changes	I can access the data regarding the weather through the application	High	Sprint-1
Administ ration (officials)	Problem solving/ Fault clearance	USN-8	As an official who is in charge for the proper functioning of the sign boards have to maintain it through periodic monitoring.	Officials can monitor the sign boards for proper functioning.	Medium	Sprint-2

CUSTOMER JOURNEY:



6. PROJECT PLANNING AND SCHEDULING:

6.1 SPRINT PLANNING & ESTIMATION:

Sprint	Functional Requirement (Epic)	User Story Number	User Story / Task	Story Points	Priority	Team Member s
Sprint-2	Login	USN-1	As a weather data controller, I log into my profile and start monitoring the weather	3	High	JANANI
Sprint	Functional Requirement (Epic)	User Story Number	User Story / Task	Story Points	Priority	Team Members
Sprint-1	Registration	USN-1	As a user, I can register for the application by entering my email, and password, and confirmingmy password.	2	High	SOWMIYAA
Sprint-1		USN-2	As a user, I will receive a confirmation email onceI have registered for the application	1	High	JANANI
Sprint-1		USN-3	As a user, I can register for the application through Facebook	2	Low	ANANDHI
Sprint-1		USN-4	As a user, I can register for the application through Gmail	2	Medium	JENIFER
Sprint-1	Login	USN-5	As a user, I can log into the application by entering my email & password	1	High	PAVITHRA
Sprint-1	Dashboard	USN-6	As a user, I can log into the application by entering my email & password and access all the resources and services available	2	High	SOWMIYAA

			updates			
Sprint-2	Dashboard	USN-2	I receive all the information about weather from web from weather API. Whenever there is change in weather, corresponding updates are made on sign boards.	2	Medium	ANANDHI
Sprint-3	Login	USN-1	As a image controller, I keep note of all the images received from various areas and detect traffic in that particular area.	3	High	JANANI
Sprint-3	Dashboard	USN-2	With the traffic, updates I change the status of sign board as "take diversion".	2	Medium	JENIFER
Sprint-4	Login	USN-1	As a zonal officer, I ensure that boards near school display "slow down" and near hospitals display "no horn".	3	High	PAVITHRA
Sprint-4	Login	USN-1	As an administrator, I ensure that all departments work coordinated and ensure the accuracy and efficiency.		Medium	ANANDHI

6.2 SPRINT DELIVERY SCHEDULE:


TITLE	DESCRIPTION	COMPLETED DATE
Literature Survey & Information Gathering	Prepare a Literature survey forthe selected project & gathering information	29 SEPTEMBER 2022
Prepare Empathy Map	Prepare Empathy Map Canvas to capture the user Pains & Gains, Prepare list of problem statements	25 SEPTEMBER 2022
Ideation	List the by organizing the brainstorming session and prioritize the top 3 ideas based on the feasibility & importance.	26 SEPTEMBER 2022

Proposed Solution	Prepare the proposed solution	24 SEPTEMBER 2022
	document, which includes the	
	novelty, feasibility of idea,	
	business model, social impact,	
	scalability of solution, etc.	

Problem Solution Fit	Prepare problem - solution fit document.	30 SEPTEMBER 2022
Solution Architecture	Prepare solution architecture document.	29 SEPTEMBER 2022
Customer Journey	Prepare the customer journey maps to understand the user interactions & experiences with the application (entry to exit).	17 OCTOBER 2022
Data Flow Diagrams	Draw the data flow diagrams and submit for review.	15 OCTOBER 2022

Technology Architecture	Prepare the	14 OCTOBER 2022
reciniology Arcintecture	technology architecture diagram.	14 OCTOBER 2022
Prepare Milestone & Activity List	Prepare the milestones & activity list of the project.	22 OCTOBER 2022
Sprint delivery plan	Prepare the sprint delivery plan of the project	22 OCTOBER 2022
Project Development - Delivery of Sprint-1	Develop & submit the developed code by testing it.	IN PROGRESS
Project Development - Delivery of Sprint2	Develop & submit the developed code by testing it.	IN PROGRESS
Project Development - Delivery of Sprint3	Develop & submit the developed code by testing it.	IN PROGRESS
Project Development - Delivery of Sprint4	Develop & submit the developed code by testing it.	IN PROGRESS

6.3 REPORTS FROM JIRA:



Velocity:

Imagine we have 10 day sprint duration, and the velocity of the team is 20 (points per sprint). Let's calculate the team's average velocity (AV) per iteration unit (story points per day)

$$AV = \frac{sprint\ duration}{velocity} = \frac{20}{10} = 2$$

Burndown chart:

A burn-down chart is graphical representation of work left to do versus time. It is often used in agile software development methodologies such as scrum. However, burn-down charts can be applied to any project containing measurable progress over time.

7. CODING AND SOLUTIONING:

7.1 FEATURE 1:

```
import wiotp.sdk.device
import time import
random import
ibmiotf.application
import ibmiotf.device
import requests, json

myConfig = { #Configuration
    "identity": {
"orgId": "fvh76j",
"typeId": "Connectivity123", "deviceId":"ESP32"},
```

```
#API Key
"auth": {
"token": "12345678"
#Receiving callbacks from IBM IOT platform def
myCommandCallback(cmd): print("Message
received from IBM IoT Platform: %s" %
cmd.data['command']) m=cmd.data['command']
client =
wiotp.sdk.device.DeviceClient(config=myConfig,logHandlers=None)
client.commandCallback= myCommandCallback client.connect()
#OpenWeatherMap Credentials
BASE_URL ="https://api.openweathermap.org/data/2.5/weather?"
CITY = "Chennai"
URL = BASE_URL + "q=" + CITY + "&units=metric"+"&appid=" +
" aacfd527963a5d91a8b5db80c6fe67b4"
```

```
while True:
            response = requests.get(URL) if
response.status_code == 200:
   data = response.json()
                         main = data['main']
                                              temperature
               humidity = main['humidity']
=main['temp']
                                            pressure =
main['pressure']
   report = data['visibility']
                                         if msg==1:
              msg=random.randint(0,5)
#messge part
message="SLOW DOWN, SCHOOL IS NEAR"
msg==2:
             message="NEED HELP, POLICE STATION"
AHED"
          elif msg==3:
    message="EMERGENCY, HOSPITAL NEARBY"
                                                     elif
msg==4:
             message="DINE IN, RESTAURENT
AVAILABLE"
                 else:
    message="" #Speed Limit part speed=random.randint(0,150)
if speed>=100:
                  speedMsg="Limit Exceeded" elif speed>=60
and speed<100:
                   speedMsg="Moderate"
                                           else:
    speedMsg="Slow"
                 sign=random.randint(0,5)
                                           if sign==1:
#Diversion part
signMsg="Right Diversion"
                            elif sign==3:
    signMsg="Left Diversion" elif sign==5:
    signmsg="U Turn"
                         else:
    signMsg=""
```


```
#Visibility
              if temperature < 24:
                                       visibility="Fog Ahead,
Drive Slow"
                elif temperature < 20:
     visibility="Bad Weather"
                                  else:
     visibility="Clear Weather"
else:
   print("Error in the HTTP request")
 myData={'Temperature':temperature, 'Message':message,
'Sign':signMsg, 'Speed':speedMsg,
'Visibility':visibility}
 client.publishEvent(eventId="status", msgFormat="json",
data=myData, qos=0, onPublish=None)
#PUBLISHING TO IOT WATSON
 print("Published data Successfully: %s", myData)
client.disconnect()
OUTPUT:
```

```
# Symbol Medical Stell Pedig Options Window Help

File Edit Stell Pe
```

7.2 FEATURE 2:

By running the python code, the data will be published in the IBM Cloud.




8. TESTING:


Test cases help guide the tester through a sequence of steps to validate whether a software application is free of bugs, and working as required by the end-user. Learning how to write test cases for software requires basic writing skills, attention to detail, and a good understanding of the application under test (AUT).

8.1 TEST CASES:

NODE RED



OUTPUT




8.2 USER ACCEPTANCE TESTING:

MIT APP INVENTER



9. RESULTS:

9.1 PERFORMANCE METRICS:



10. ADVANTAGES:

Preventing Wrong-way Crashes

The National Highway Traffic Safety Administration has stated that hundreds of lives are lost annually to wrong-way crashes. In addition, thousands of people sustain injuries in such accidents. Based on research and field tests performed by the Florida Department of Transportation, certain kinds of intelligent road indicators may effectively catch the attention of people driving the wrong way on a roadway. The indicators that were tested included blank indicators that light up when they detect the presence of wrong-way vehicles. Another type of sign was designed with lights that light up in an asynchronous manner. Once a driver is alerted by the lights and can see the "Wrong Way" lettering, that person can turn around and proceed in the correct direction. This could save numerous lives and prevent countless injuries.

Better Traffic Management and Safety

Through refined telematics and intelligent technology, it can be easier to "read" the locations and speeds of vehicles, such as those in a fleet. When vehicles and smart traffic control systems are connected via the cloud, the end results may be more manageable traffic, decreased gridlock, and better traffic

Increased Cost Efficiency

We need to explore more cost-effective ways to strengthen the infrastructure. Building roads is expensive. While there is no substitution for new and upgraded roads, smart roadway indicators can be added to increase efficiency. They provide innovative ways to improve traffic flow, reduce congestion, regulate the patterns of traffic, and create an optimal balance of public and private transportation.

Combating Poor Visibility

Road placards cannot help us if we are unable to read them. Many factors may cause drivers to misinterpret roadside signage or to miss it altogether. Aging drivers can have difficulty seeing roadway signs as they drive past them. Inexperienced drivers can easily misunderstand their meanings. Even those of us who have driven for years may find it challenging to remember the messages conveyed by conventional road signs. Additionally, bad

lighting and weather can further decrease our capacity to use the signage as intended. Smart road indicators make it easier for us to detect and implement their alerts and instructions.

DISADVANTAGES:

· Important investment:

Buying a screen is much more expensive than putting up a poster and the solutions to control screens are rarely free. In the long run, it is possible to make the screen more profitable but it will take months or years depending on your needs.

• Editing and renewing the content can be complex:

If the people managing the screens are not graphic designers, it can be difficult to update the content regularly on the screen.

· Return on investment:

ROI can be hard to calculate. There is a high initial spend in installing digital signage and the ROI can become complex when you try and calculate sale's increases with incidents such as screen damage and repair. However, the vulnerability of digital signage screens can be protected with an LCD enclosure preventing the need for additional repair costs.

Still new and improving:

As such there is always going to be a better, cheaper and more effective solution around the corner. Prices for the technology are still falling too which may be leading to many potential installers playing the waiting game until the price and technology is just right.

May require multiple partners:

With hardware such as LCD enclosures, screens, media players, content and networking involved in many campaigns there may be four or five different companies involved in a single project.

· Lack of understanding:

There are many common mistakes made because of a lack of understanding. Poor content, the wrong location and the wrong screen are particularly common especially with outdoor digital signage where demands can differ.

• Environment:

While digital screens require power and therefore can't claim to be green, there is high energy use in the printing, erecting and replacement of traditional print media.

Lack of a clear purpose behind many campaigns:

Many people embark on digital signage without a clear purpose in mind which can affect the effectiveness of the system.

11. CONCLUSION:

Smart signs offer crucial information to drivers as well as other common road users. They not only save the lives of those driving the vehicle, but also those using the road on foot. Neglecting their installation is dangerous for both car drivers as well as pedestrians. Maintaining order and reducing accidents, these speed limit signs are the lifeline of today's road networks across the globe. No smart road transport system can be imagined without these devices.

The world doesn't change on its own but we humans can change the world to

be safe, better, and harmless. Since the road isn't said to be safe let's make it safer with the technologies present and available to us. The Internet of Things is one of the technologies that can lead us to travel on enhanced safe roads. So let's come together to create a better world with no accidents and a smart road for the future generation.

12. FUTURE SCOPE:

IOT obtains the majority of its data with the help of connected cars. These incorporate a large number of sensors that establish communication with the cloud, other vehicles, and devices.

It provides data and information of great utility for the improvement of road safety. The safe system approach to road safety emphasizes safety by design ensuring safe vehicles, road networks, and road users. Evolving towards the future, the road needs to boil with advanced sensors and antenna systems to have peace with the new era.

13. APPENDIX:

13.1 SOURCE CODE:

import wiotp.sdk.device
import time import
random import
ibmiotf.application import
ibmiotf.device
import requests, json

myConfig = { #Configuration
 "identity": {

"orgId": "fvh76j",
"typeId": "SMARTBOARD", "deviceId": "SMARTCONNECTIVITY"},

```
#API Key
"auth": {
"token": "12345678"
#Receiving callbacks from IBM IOT platform def
myCommandCallback(cmd):
 print("Message received from IBM IoT Platform: %s" %
cmd.data['command']) m=cmd.data['command']
client =
wiotp.sdk.device.DeviceClient(config=myConfig,logHandlers=None)
client.commandCallback= myCommandCallback client.connect()
#OpenWeatherMap Credentials
BASE_URL ="https://api.openweathermap.org/data/2.5/weather?" CITY
= "Chennai"
URL = BASE_URL + "q=" + CITY + "&units=metric"+"&appid=" + "
aacfd527963a5d91a8b5db80c6fe67b4"
while
      True:
                   response =
requests.get(URL)
                            if
response.status code == 200:
   data = response.json()
main = data['main']
temperature =main['temp']
humidity = main['humidity']
pressure = main['pressure']
   report = data['visibility']
#messge part
msg=random.randint(0,5)
                           if
msg==1:
```

```
message="SLOW DOWN, SCHOOL IS NEAR"
elif msg==2:
     message="NEED HELP, POLICE STATION AHED"
elif msg==3:
     message="EMERGENCY, HOSPITAL NEARBY"
elif msg==4:
     message="DINE IN, RESTAURENT AVAILABLE"
else:
     message="" #Speed
Limit part
   speed=random.randint(0,150)
if speed>=100:
     speedMsg=" Limit Exceeded"
elif speed>=60 and speed<100:
     speedMsg="Moderate"
else:
     speedMsg="Slow"
#Diversion part
   sign=random.randint(0,5)
if sign==1:
     signMsg="Right Diversion"
elif sign==3:
     signMsg="Left Diversion"
elif sign==5:
     signmsg="U Turn"
else:
     signMsg=""
#Visibility
             if
temperature < 24:
     visibility="Fog Ahead, Drive Slow"
elif temperature < 20:
     visibility="Bad Weather"
else:
```

```
else:
    print("Error in the HTTP request")

myData={'Temperature':temperature, 'Message':message,
'Sign':signMsg, 'Speed':speedMsg, 'Visibility':visibility}

client.publishEvent(eventId="status", msgFormat="json",
data=myData, qos=0, onPublish=None)

#PUBLISHING TO IOT WATSON

print("Published data Successfully: %s", myData)
client.commandCallback= myCommandCallback
time.sleep(5)
```

client.disconnect()

GitHub Link: https://github.com/IBM-EPBL/IBM-Project-20798-1659763505

Project Demo Link:

https://drive.google.com/file/d/1rSehGW0VPe6yQN9WYFsAMr33_mW RuIL/view?usp=share_link