

ASSIGNMENT 4

Assignment Date	01 November 2022
Student Name	Gokul vigneesh S
Maximum Marks	2 Marks
Team ID	PNT2022TMID17444

Question:

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events. Upload document with wokwi share link and images of IBM cloud.

Code:

```
#include <WiFi.h>
#include <WiFiClient.h>
#include <PubSubClient.h>
const int trigPin = 27;
const int echoPin = 26;
//define sound speed in cm/uS
#define SOUND_SPEED 0.034
#define CM_TO_INCH 0.393701
long duration;
float distanceCm;
float distanceInch;
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//-----credentials of IBM Accounts-----

#define ORG "z22obn"//IBM ORGANITION ID
#define DEVICE_TYPE "Assignment-ibm"//Device type mentioned in ibm watson IOT
Platform
#define DEVICE_ID "Sensor"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678" //Token
String data3;
//----- Customise the above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
```

```

char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send

char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
type AND COMMAND IS TEST OF FORMAT STRING

char authMethod[] = "use-token-auth";// authentication method

char token[] = TOKEN;

char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id


WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient);
void setup() {
    Serial.begin(115200); // Starts the serial communication
    pinMode(trigPin, OUTPUT); // Sets the trigPin as an Output
    pinMode(echoPin, INPUT); // Sets the echoPin as an Input
    Serial.println();
    wificonnect();
    mqttconnect();
}
void loop() {
    // Clears the trigPin
    digitalWrite(trigPin, LOW);
    delayMicroseconds(2);
    // Sets the trigPin on HIGH state for 10 micro seconds
    digitalWrite(trigPin, HIGH);
    delayMicroseconds(10);
    digitalWrite(trigPin, LOW);

    // Reads the echoPin, returns the sound wave travel time in microseconds
    duration = pulseIn(echoPin, HIGH);

    // Calculate the distance
    distanceCm = duration * SOUND_SPEED/2;

```

```

// Convert to inches
distanceInch = distanceCm * CM_TO_INCH;

// Prints the distance in the Serial Monitor
Serial.print("Distance (cm): ");
Serial.println(distanceCm);
Serial.print("Distance (inch): ");
Serial.println(distanceInch);

PublishData(distanceCm);
delay(1000);
if (!client.loop()) {
    mqttconnect();
}
}

void PublishData(float Cm) {
    mqttconnect();//function call for connecting to ibm
    /*
        creating the String in in form JSon to update the data to ibm cloud
    */
    String payload = "{\"Distance (cm)\":\"";
    payload += Cm;
    payload += "\"";
    Serial.print("Sending payload: ");
    Serial.println(payload);
    if (client.publish(publishTopic, (char*) payload.c_str())) {
        Serial.println("Publish ok");// if it sucessfully upload data on the cloud
        then it will print publish ok in Serial monitor or else it will print publish
        failed
    } else {
        Serial.println("Publish failed");
    }
}

```

```

}
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }

    initManagedDevice();
    Serial.println();
  }
}
void wificonnect() //function defination for wificonnect
{
  Serial.println();
  Serial.print("Connecting to ");

  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
  }
}

```

```

        Serial.println("subscribe to cmd OK");
    } else
    {
        Serial.println("subscribe to cmd FAILED");
    }
}

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
    Serial.print("callback invoked for topic: ");
    Serial.println(subscribetopic);
    for (int i = 0; i < payloadLength; i++) {
        //Serial.print((char)payload[i]);
        data3 += (char)payload[i];
    }
}
}

```

Output:

The screenshot displays the Arduino IDE interface with a simulation running. On the left, the 'Library Manager' is open, showing the 'wfi-scan.ino' file. The code includes comments and defines for an IoT device, and a setup function that initializes the serial port and pins. The main loop (partially visible) calls 'wificonnect()' and 'mqttconnect()'. On the right, the 'Simulation' window shows a visual representation of the hardware: a blue ultrasonic sensor module connected to an ESP8266 microcontroller board. Below the hardware, the serial output is displayed, showing the sequence of events: a successful subscription, distance measurements in both centimeters and inches, and the resulting JSON payloads being sent over MQTT.

```

19 #define ORG "22200H" //IBM ORGANIZATION ID
20 #define DEVICE_TYPE "Assignment-ibm" //Device type me
21 #define DEVICE_ID "Sensor" //Device ID mentioned in
22 #define TOKEN "12345678" //Token
23 String data3;
24
25
26
27 //----- Customise the above values -----
28 char server[] = ORG ".messaging.internetofthings.ibm
29 char publishTopic[] = "iot-2/evt/Data/fmt/json"; //
30 char subscribetopic[] = "iot-2/cmd/test/fmt/String";
31 char authMethod[] = "use-token-auth"; // authenticat
32 char token[] = TOKEN;
33 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVI
34
35 WiFiClient wifiClient; // creating the instance for
36 PubSubClient client(server, 1883, callback ,wifiCli
37
38 void setup() {
39     Serial.begin(115200); // Starts the serial commun
40     pinMode(trigPin, OUTPUT); // Sets the trigPin as
41     pinMode(echoPin, INPUT); // Sets the echoPin as ar
42     Serial.println();
43     wificonnect();
44     mqttconnect();
45
46

```

Simulation

subscribe to cmd OK

Distance (cm): 100.01

Distance (inch): 39.37

Sending payload: {"Distance (cm)":100.01}

Publish ok

Distance (cm): 99.94

Distance (inch): 39.35

Sending payload: {"Distance (cm)":99.94}

Publish ok

IBM Cloud Alert:

Event	Value	Format	Last Received
Data	{"Distance (cm)":99.98}	json	a few seconds ago
Data	{"Distance (cm)":99.96}	json	a few seconds ago
Data	{"Distance (cm)":99.98}	json	a few seconds ago
Data	{"Distance (cm)":99.98}	json	a few seconds ago
Data	{"Distance (cm)":99.98}	json	a few seconds ago

Link:

<https://wokwi.com/projects/305569599398609>

