ASSIGNMENT-IV

DOCKER & KUBERNETES

Student Name	P.Malarvizhi
Student Roll Number	731719205009
Maximum Marks	2 Marks

app.py

Dockerfile

Requirements.txt

Docker hub

Docker

Dockerplayground

2. Create a docker file for the jobportal application and deploy it in Docker desktop application.

Deploy in docker application

Running in docker desktop

3.Create a IBM container registry and deploy helloworld app or jobportalapp

Deploy helloworld or jobportal

4.Create a Kubernetes cluster in IBM cloud and deploy helloworld imageor jobportal image and also expose the same app to run in nodeport.

Creating a kubernetes cluster in ibm cloud

Expose the same app to run in noteport

```
C:\Windows\system32>kubectl expose deployment flask-app --type=NodePort --name=flask_service
The Service "flask_service" is invalid: metadata.name: Invalid value: "flask_service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start
with an alphabetic character, and end with an alphanumeric character (e.g. 'my-name', or 'abc-123', regex used for validation is '[a-z]([-a-z0-9]*[a-z0-9])?')

C:\Windows\system32>kubectl expose deployment flask-app --type=NodePort --name=flask_service
The Service "flask_service" is invalid: metadata.name: Invalid value: "flask_service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start
with an alphabetic character, and end with an alphanumeric character (e.g. 'my-name', or 'abc-123', regex used for validation is '[a-z]([-a-z0-9]*[a-z0-9])?')

C:\Windows\system32>kubectl expose deployment flask-app --type=NodePort --name=flask_service
The Service "flask_service" is invalid: metadata.name: Invalid value: "flask_service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start
with an alphabetic character, and end with an alphanumeric character (e.g. 'my-name', or 'abc-123', regex used for validation is '[a-z]([-a-z0-9]*[a-z0-9])?')

C:\Windows\system32>kubectl expose deployment flask-app --type=NodePort --name=flask-service
Error from server (AlreadyExists): services "flask-service" already exists

C:\Windows\system32>
C:\Windows\system32>kubectl -n kubernetes-dashboard get depploy
^C
C:\Windows\system32>kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.

C:\Windows\system32>kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.

C:\Windows\system32>kubectl proxy
Starting to serve on 127.0.0.1:8001
^C
C:\Windows\system32>kubectl -n kubernetes-dashboard get deploy
^C
C:\Windows\system32>kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.

C:\Windows\system32>kubectl -n kubernetes-dashboard get pods
No resources found in kubernetes-dashboard namespace.

C:\Windows\system32>kubectl expose deployment flask-app --type=NodePort --name=flask-service
Error from server (AlreadyExists): services "flask-service" already exists

C:\Windows\system32>kubectl get ing
NAME               CLASS     HOSTS    ADDRESS    PORTS    AGE
flask-app-ingress  <none>    *                   80       27m

C:\Windows\system32>kubectl get svc
NAME               TYPE        CLUSTER-IP        EXTERNAL-IP    PORT(S)        AGE
```