

▼ Exercises

Answer the questions or complete the tasks outlined in bold below, use the specific method described if applicable.

**** What is 7 to the power of 4?****

```
base=7
exponent = 4
result = 1
while exponent != 0:
    result *= base
    exponent-=1
print("Answer = " + str(result))
```

Answer = 2401

**** Split this string:****

```
s = "Hi there Sam!"
```

**into a list. **

```
s = "Hi there Sam!"
```

```
x = s.split()
```

```
print(x)
```

Show hidden output


```
s = "Hi there dad!"
```

```
x = s.split()
```

```
print(x)
```

```
['Hi', 'there', 'dad!']
```

**** Given the variables:****



Exercises

Answer the questions or complete the tasks outlined in bold below, use the specific method described if applicable.

```
planet = "Earth"
diameter = 12742
```

**** Use .format() to print the following string: ****

```
The diameter of Earth is 12742 kilometers.
```

```
planet = "Earth"
diameter = 12742
print("The diameter of {} is {} kilometers.".format(planet, diameter))
```

Show hidden output

```
planet = "Earth"
diameter = 12742
print("The diameter of {} is {} kilometers.".format(planet, diameter))
```

```
The diameter of Earth is 12742 kilometers.
```

**** Given this nested list, use indexing to grab the word "hello"**

```
lst = [1,2,[3,4],[5,[100,200,['hello']],23,11],1,7]
lst[3][1][2][0]
```

Show hidden output

```
lst = [1,2,[3,4],[5,[100,200,['hello']],23,11],1,7]
lst[3][1][2][0]
```

```
'hello'
```

**** Given this nest dictionary grab the word "hello". Be prepared, this will be annoying/tricky ****

```
d = {'k1':[1,2,3',{'tricky':['oh','man','inception',{'ta':[1,2,3,['hello']}]}
```

```
lst = [1,2,[3,4],[5,[100,200,['hello']],23,11],1,7]
lst[3][1][2][0]
```

```
'hello'
```

**** What is the main difference between a tuple and a list? ****

#The difference between a tuple and a list is that a tu

**** Create a function that grabs the email website domain from a string in the form: ****

```
user@domain.com
```

So for example, passing "[user@domain.com](#)" would return: domain.com

```
def domain(email):  
    return email.split('@')[-1]
```

```
domain('user@domain.com')  
  
    'domain.com'
```

**** Create a basic function that returns True if the word 'dog' is contained in the input string. Don't worry about edge cases like a punctuation being attached to the word dog, but do account for capitalization. ****

```
def findDog(st):  
    return 'dog' in st.lower().split()
```

```
findDog('Is there a dog ?')  
  
    True
```

**** Create a function that counts the number of times the word "dog" occurs in a string. Again ignore edge cases. ****

```
def countDog(st):  
    count = 0  
    for word in st.lower().split():  
        if word == 'dog':  
            count += 1  
    return count
```

```
countDog("I take a walk with my dog in the evening.the
```

▼ Problem

**You are driving a little too fast, and a police officer stops you. Write a function to return one of 3 possible results: "No ticket", "Small ticket", or "Big Ticket". If your speed is 60 or less, the result is "No Ticket". If speed is between 61 and 80 inclusive, the result is "Small Ticket". If speed is 81 or more, the result is "Big Ticket". Unless it is your birthday (encoded as a boolean value in the parameters of the function) – on your birthday, your speed can be 5 higher in all cases. **

```
def caught_speeding(speed, is_birthday):
```

```
    if is_birthday:
        speeding = speed - 5
    else:
        speeding = speed

    if speeding > 80:
        return 'Big Ticket'
    elif speeding > 60:
        return 'Small Ticket'
    else:
        return 'No Ticket'
```

```
caught_speeding(100,True)
```

```
    'Big Ticket'
```

```
caught_speeding(75,True)
```

```
    'Small Ticket'
```

Create an employee list with basic salary values(at least 5 values for 5 employees) and using a for loop retrieve each employee salary and calculate total salary expenditure.

```
list = ['yadhav', 12000, "rick", 9500, "ram", 12500, "a
print("The employee list : " + str(list))
key_list = ["name", "Basic salary"]
```

```

n = len(list)
res = []
for idx in range(0, n):
    res.append({key_list[0]: list[idx], key_list[1] : list

# printing result
print("The constructed dictionary list : " + str(res))

```

```

The employee list : ['yadhav', 12000, 'rick', 9
-----
-----

```

IndexError

Traceback (most recent call last)

<ipython-input-25-a9853dc15029> in <module>

```

5 res = []

```

```

6 for idx in range(0, n):

```

```

----> 7 res.append({key_list[0]: list[idx],
key_list[1] : list[idx + 1]})

```

```

8

```

```

9 # printing result

```

IndexError: list index out of range

Create two dictionaries in Python:

First one to contain fields as Empid, Empname, Basicpay

Second dictionary to contain fields as DeptName, DeptId.

Combine both dictionaries.

```

dic_1 = {'Empid': 25, 'Empname': "banu" , 'Basicpay' :
dic_2 = {'DeptName':"Accounting" , 'DeptId': 4567 }
dic_1.update(dic_2)
print('Updated dictionary:')
print(dic_1)

```

Updated dictionary:

```

{'Empid': 25, 'Empname': 'banu', 'Basicpay': 2300

```

[Colab paid products](#) - [Cancel contracts here](#)

