ASSIGNMENT -3

Date : 11 October 2022

Name : Haritha.S

Project Name : A NOVEL METHOD FOR HANDWRITTEN DIGIT RECOGNITION SYSTEM

Maximum Marks : 2 Marks

```
#!/usr/bin/env python
# coding: utf-8

# In[88]:


import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import scipy
from scipy import stats
```

```
from sklearn.preprocessing import OneHotEncoder


# In[11]:


dataset = pd.read_csv('C:\\Users\\Devi\\Downloads\\Churn_Modelling (1) (1).csv')


# In[12]:


dataset


# In[13]:


dataset.head()


# In[14]:


dataset.tail()


# # Univariate Analysis

# In[6]:
```

```
df_1=dataset.loc[dataset['NumOfProducts']==1]
df_2=dataset.loc[dataset['NumOfProducts']==2]
df_3=dataset.loc[dataset['NumOfProducts']==3]
```

In[7]:

```
plt.plot(df_1['Age'],np.zeros_like(df_1['Age']))
plt.plot(df_2['Age'],np.zeros_like(df_2['Age']))
plt.plot(df_3['Age'],np.zeros_like(df_3['Age']))
plt.xlabel('Age')
plt.show()
```

Bivariate Analysis

In[8]:

```
sns.FacetGrid(dataset,hue="NumOfProducts",size=5).map(plt.scatter,"Age","Geography").add_legend();
```

Multivariate Analysis

In[9]:

```
sns.pairplot(dataset,hue="NumOfProducts",size=5)
```

Descriptive Statistics

In[16]:

```
dataset.sum()
```

In[17]:

```
dataset.sum(axis=1)
```

In[18]:

```
dataset.median()
```

In[19]:

```
dataset.mean()
```

In[20]:

```
dataset.max()
```

```
# In[21]:
```

```
dataset.std()
```

```
# In[22]:
```

```
dataset.var()
```

```
# In[24]:
```

```
Age=dataset.Age
Age.value_counts()
```

```
# In[25]:
```

```
dataset.describe()
```

```
# # Handle Null Values
```

```
# In[27]:
```

```
dataset.shape
```

```
# In[28]:
```

```
dataset.isnull()
```

```
# In[31]:
```

```
dataset.isnull().sum()
```

```
# In[32]:
```

```
dataset.isnull().sum().sum()
```

```
# # Outlier
```

```
# In[58]:
```

```
sns.displot(dataset['Gender'])
```

In[59]:

```
sns.boxplot(x='Gender',y='Age',data=dataset)
```

In[60]:

```
sns.boxplot(y='Age',data=dataset)
```

In[61]:

```
dataset['Age'].mean()
```

In[67]:

```
data1=dataset[dataset['Age']<40]
```

In[68]:

```
sns.boxplot(y='Age',data=data1)
```

categorial Encoding

In[70]:

```
data_tips=pd.get_dummies(dataset)
data_tips
```

In[75]:

```
one_encde=OneHotEncoder(sparse=False)
encoded_arr=one_encde.fit_transform(dataset[['CustomerId','CreditScore','Age','Tenure']])
encoded_arr
```

split the data into dependent and independent

In[85]:

```
x=dataset.iloc[:,1:4]
y=dataset.iloc[:,4]
x
y
```

In[ ]:

In[ ]:

In[ ]: