EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES

MODEL BUILDING

TRAINING THE MODEL

| Date | 04 November 2022 |
|--------------|---|
| Team ID | PNT2022TMID10153 |
| Team ID | FN120221WIID10133 |
| | |
| Project Name | Emerging Methods for Early Detection of |
| | Forest Fires |

Importing The ImageDataGenerator Library

import keras

from keras.preprocessing.image import ImageDataGenerator

Define the parameters/arguments for ImageDataGenerator class

train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rot ati on_range=180,zoom_range=0.2, horizontal_flip=True) test_datagen=ImageDataGenerator(rescale=1./255)

Applying ImageDataGenerator functionality to trainset

x_train=train_datagen.flow_from_directory(r'/content/drive/MyDriv e/ Dataset/train_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 436 images belonging to 2 classes.

Applying ImageDataGenerator functionality to testset

x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive / Dataset/test_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 121 images belonging to 2 classes.

Import model building libraries

#To define Linear initialisation import Sequential
from keras.models import Sequential
#To add layers import Dense
from keras.layers import Dense
#To create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')

Initializing the model

model=Sequential()

Add CNN Layer

model.add(Convolution2D(32, (3,3),input_shape=(128,128,3),activation='relu')) #add maxpooling layer

```
model.add(MaxPooling2D(pool_size=(2,2)))
 #add flatten layer
 model.add(Flatten())
 Add Hidden Layer
 #add hidden layer
 model.add(Dense(150,activation='relu'))
 #add output layer
 model.add(Dense(1,activation='sigmoid')
 Configure the learning process
 model.compile(loss='binary crossentropy',optimizer="adam",metrics=[
 "ac curacy"])
 Train the model
 model.fit_generator(x_train,steps_per_epoch=14,epochs=10,validation_
 da ta=x test, validation steps=4)
 Epoch 1/10
 14/14 [=======] - 97s 7s/step - loss:
 1.3060 -
 accuracy: 0.7775 - val_loss: 0.5513 - val_accuracy: 0.8512
 Epoch 2/10
 14/14 [=======] - 26s 2s/step - loss:
 0.3178 -
 accuracy: 0.8807 - val_loss: 0.1299 - val_accuracy: 0.9421
 Epoch 3/10
 14/14 [=======] - 26s 2s/step - loss:
 0.2226 -
 accuracy: 0.9106 - val loss: 0.1311 - val accuracy: 0.9421
 Epoch 4/10
 14/14 [=======] - 31s 2s/step - loss:
 0.1836 -
 accuracy: 0.9174 - val loss: 0.1129 - val accuracy: 0.9339
 Epoch 5/10
 14/14 [=======] - 30s 2s/step - loss:
 0.1675 -
```

```
accuracy: 0.9243 - val loss: 0.0925 - val accuracy: 0.9669
Epoch 6/10
14/14 [=======] - 26s 2s/step - loss:
0.1884 -
accuracy: 0.9289 - val_loss: 0.1287 - val_accuracy: 0.9339
Epoch 7/10
14/14 [=======] - 28s 2s/step - loss:
0.1724 -
accuracy: 0.9335 - val loss: 0.0926 - val accuracy: 0.9752
Epoch 8/10
14/14 [=======] - 26s 2s/step - loss:
0.1510 -
accuracy: 0.9404 - val loss: 0.0757 - val accuracy: 0.9752
0.173 -
accuracy: 0.9174 - val_loss: 0.0537 - val_accuracy: 0.9835
Epoch 10/10
14/14 [=======] - 26s
                                                0.154 -
2s/step - loss:
accuracy: 0.9312 - val_loss: 0.0573 - val_accuracy: 0.9835
<keras.callbacks.History at 0x7f05d66a9c90>
```