EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES

VIDEO ANALYSIS

OPEN CV FOR VIDEO PROCESSING

Date	07 November 2022
Team ID	PNT2022TMID40840
Project Name	Emerging Methods for Early Detection of Forest Fires

Importing The ImageDataGenerator Library import keras from keras.preprocessing.image import ImageDataGenerator Define the parameters/arguments for ImageDataGenerator class train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rot ati on_range=180,zoom_range=0.2, horizontal_flip=True) test_datagen=ImageDataGenerator(rescale=1./255) Applying ImageDataGenerator functionality to trainset x_train=train_datagen.flow_from_directory(r'/content/drive/MyDriv e/Dataset/train_set',target_size=(128,128),batch_size=32,

class_mode='binary')

Found 436 images belonging to 2 classes.

Applying ImageDataGenerator functionality to testset

x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive / Dataset/test_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 121 images belonging to 2 classes.

Import model building libraries

#To define Linear initialisation import Sequential from keras.models import Sequential #To add layers import Dense from keras.layers import Dense

#To create Convolution kernel import Convolution2D from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer from keras.layers import Flatten import warnings
warnings.filterwarnings('ignore')

Initializing the model

model=Sequential()

Add CNN Layer

model.add(Convolution2D(32, (3,3),input_shape=(128,128,3),activation='relu')) #add maxpooling layer

```
model.add(MaxPooling2D(pool_size=(2,2)))
#add flatten layer model.add(Flatten())
Add Hidden Layer
#add hidden layer model.add(Dense(150,activation='relu'))
#add output layer
model.add(Dense(1,activation='sigmoid')
Configure the learning process
model.compile(loss='binary_crossentropy',optimizer="adam",metrics=[
"ac curacy"])
Train the model
model.fit_generator(x_train,steps_per_epoch=14,epochs=10,validation_
da ta=x_test, validation_steps=4)
Epoch 1/10
1.3060 - accuracy: 0.7775 - val loss: 0.5513 -
val accuracy: 0.8512
Epoch 2/10
0.3178 - accuracy: 0.8807 - val loss: 0.1299 -
val accuracy: 0.9421
Epoch 3/10
14/14 [=======] - 26s 2s/step - loss:
0.2226 - accuracy: 0.9106 - val loss: 0.1311 -
val_accuracy: 0.9421
Epoch 4/10
14/14 [=======] - 31s 2s/step - loss:
0.1836 - accuracy: 0.9174 - val_loss: 0.1129 -
val accuracy: 0.9339
Epoch 5/10
14/14 [========] - 30s 2s/step - loss:
```

```
0.1675 -
 accuracy: 0.9243 - val loss: 0.0925 - val accuracy: 0.9669
 Epoch 6/10
 14/14 [=======] - 26s 2s/step - loss:
 0.1884 - accuracy: 0.9289 - val_loss: 0.1287 -
 val_accuracy: 0.9339
 Epoch 7/10
 14/14 [=======] - 28s 2s/step - loss:
 0.1724 - accuracy: 0.9335 - val loss: 0.0926 -
 val_accuracy: 0.9752
 Epoch 8/10
 14/14 [=======] - 26s 2s/step - loss:
 0.1510 - accuracy: 0.9404 - val loss: 0.0757 -
 val_accuracy: 0.9752 Epoch 9/10
14/14 [=======] - 26s
                                                     0.173 -
2s/step - loss:
accuracy: 0.9174 - val_loss: 0.0537 - val_accuracy: 0.9835
            14/14 [=========]
Epoch 10/10
 - 26s
        0.154 -
                                                     6
2s/step - loss:
accuracy: 0.9312 - val loss: 0.0573 - val accuracy: 0.9835
 <keras.callbacks.History at 0x7f05d66a9c90>
```

Save The Model

model.save("forest1.h5")

Predictions

#import load_model from keras.model from keras.models import load_model #import image class from keras

```
from tensorflow.keras.preprocessing import image #import
 numpy import numpy as np #import cv2 import cv2
#load the saved model model = load_model("forest1.h5")
 img=image.load_img(r'/content/drive/MyDrive/Dataset/te
 st set/forest/ 0.48007200 1530881924 final forest.jpg')
 x=image.img_to_array(img)
 res = cv2.resize(x, dsize=(128, 128),
 interpolation=cv2.INTER CUBIC)
 #expand the image shape
 x=np.expand_di ms(res,axis=0)
 pred= model.predict(x)
 1/1 [=======] - 0s
 126ms/step pred
array([[0.]],
 dtype=float32) OpenCV
 For Video Processing
pip install twilio
Looking in indexes: https://pypi.org/simple, https://us-
python.pkg.dev/colab-wheels/public/simple/
Requirement already satisfied: twilio in
/usr/local/lib/python3.7/dist-packages (7.15.1)
Requirement already satisfied: pytz in /usr/local/lib/python3.7/dist-
packages (from twilio) (2022.5)
Requirement already satisfied: requests>=2.0.0 in
/usr/local/lib/python3.7/dist-packages (from twilio) (2.23.0)
Requirement already satisfied: PyJWT<3.0.0,>=2.0.0 in
/usr/local/lib/python3.7/dist-packages (from twilio) (2.6.0) Requirement
already satisfied: urllib3!=1.25.0,!=1.25.1,<1.26,>=1.21.1 in
/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0-
>twilio) (1.24.3)
Requirement already satisfied: certifi>=2017.4.17 in
```

```
/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio)
(2022.9.24)
Requirement already satisfied: idna<3,>=2.5 in
/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio)
(2.10)
Requirement already satisfied: chardet<4,>=3.0.2 in
/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio)
(3.0.4)
pip install playsound
Looking in indexes: https://pypi.org/simple, https://us-
python.pkg.dev/colab-wheels/public/simple/
Requirement already satisfied: playsound in
/usr/local/lib/python3.7/dist-packages (1.3.0)
#import opency library
import cv2 #import
numpy import numpy
as np
#import image function from keras
from keras.preprocessing import
image #import load_model from
keras
from keras.models import load_model
#import client from twilio API from
twilio.rest import Client
#import playsound package from
playsound import playsound
WARNING:playsound:playsound is relying on another python
subprocess. Please use 'pip install pygobject' if you want playsound to
run more efficiently.
#load the saved model
model=load model("forest1.h
5") #define video
```

video=cv2.VideoCapture(0) #define

the features

name=['forest','with fire']