Assignment -3 Convolutional Neural Networks

Assignment Date	31 October 2022
Student Name	M.Navaneethakumar
Student Roll Number	620619106019
Maximum Marks	2 Marks

#Import necessary libraries

from tensorflow.keras.models import Sequential

from tensorflow.keras.layers import Dense

from tensorflow.keras.layers import Convolution2D

from tensorflow.keras.layers import MaxPooling2D

from tensorflow.keras.layers import Flatten

#Image augmentation

from tensorflow.keras.preprocessing.image import ImageDataGenerator

```
train_datagen =
```

ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True, vertical_flip=True)

test_datagen = ImageDataGenerator(rescale=1./255)

```
In [1]: #Import necessary libraries
    from tensorflow.keras.models import Sequential
        from tensorflow.keras.layers import Dense
        from tensorflow.keras.layers import Convolution2D
        from tensorflow.keras.layers import MaxPooling2D
        from tensorflow.keras.layers import Flatten

In [2]: #Image augmentation
    from tensorflow.keras.preprocessing.image import ImageDataGenerator
        train_datagen = ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True,vertical_flip=True)
        test_datagen = ImageDataGenerator(rescale=1./255)
```

#data set

```
x_train =
```

 $train_datagen.flow_from_directory(r"E:\Flowers\Training",target_size=(128,128),batch_size=32,class_mode="categorical")$

```
x test =
test_datagen.flow_from_directory(r"E:\Flowers\Testing",target_size=(128,128),batch_size=3
2,class mode="categorical")
x_train.class_indices
model = Sequential()
 In [2]: #Image augmentation
        from tensorflow.keras.preprocessing.image import ImageDataGenerator
        train_datagen = ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True,vertical_flip=True)
        test datagen = ImageDataGenerator(rescale=1./255)
 In [3]: x_train = train_datagen.flow_from_directory(r"E:\Flowers\Training",target_size=(128,128),batch_size=32,class_mode="categorical")
        x_test = test_datagen.flow_from_directory(r"E:\Flowers\Testing",target_size=(128,128),batch_size=32,class_mode="categorical")
        x_train.class_indices
        Found 3003 images belonging to 5 classes.
        Found 1325 images belonging to 5 classes.
 Out[3]: {'daisy': 0, 'dandelion': 1, 'rose': 2, 'sunflower': 3, 'tulip': 4}
#Add layers
#Convolution layer
model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
#Maxpooling layer
model.add(MaxPooling2D(pool_size=(2,2)))
#flatten layer
model.add(Flatten())
#hidden layer
model.add(Dense(units=300,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=200,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=5,kernel_initializer="random_uniform",activation="softmax"))
model.summary()
```

```
In [4]: model = Sequential()
#Add Layers
#Convolution Layer
model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
#Maxpooling Layer
model.add(MaxPooling2D(pool_size=(2,2)))
#flatten Layer
model.add(Flatten())
#hidden Layer
model.add(Dense(units=300,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=200,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=5,kernel_initializer="random_uniform",activation="softmax"))
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 126, 126, 32)	896
max_pooling2d (MaxPooling2D)	(None, 63, 63, 32)	0
flatten (Flatten)	(None, 127008)	0
dense (Dense)	(None, 300)	38102700
dense_1 (Dense)	(None, 200)	60200
dense_2 (Dense)	(None, 5)	1005

Total params: 38,164,801 Trainable params: 38,164,801 Non-trainable params: 0

#compile the model

model.compile(loss="categorical_crossentropy",optimizer="adam",metrics=["accuracy"])

#Fit the model

model.fit_generator(x_train,steps_per_epoch=75,epochs=15,validation_data=x_test,validation_steps=80)

```
In [6]: #compile the model
                model.compile(loss="categorical_crossentropy",optimizer="adam",metrics=["accuracy"])
                model.fit generator(x train, steps per epoch=75, epochs=15, validation data=x test, validation steps=80)
                 \verb|C:\Users\hp\Anaconda3\lib\site-packages\ipykernel\_launcher.py: 4: UserWarning: \verb|`Model.fit\_generator'| is deprecated and will be related to the packages of the packages
                emoved in a future version. Please use `Model.fit`, which supports generators.
                  after removing the cwd from sys.path.
                Epoch 1/15
                                         :============================== ] - ETA: 0s - loss: 1.0726 - accuracy: 0.5791WARNING:tensorflow:Your input ran out of dat
               Epoch 2/15
               75/75 [====
Epoch 3/15
                                         Fpoch 4/15
                                              Epoch 5/15
                                                      ========] - 73s 962ms/step - loss: 0.8177 - accuracy: 0.6789
                Epoch 6/15
                                              Epoch 7/15
                                                     =======] - 73s 966ms/step - loss: 0.8099 - accuracy: 0.6868
                Fnoch 8/15
                                                   Epoch 9/15
                                                  -----] - 70s 926ms/step - loss: 0.7146 - accuracy: 0.7215
                Epoch 10/15
75/75 |============= | - 69s 911ms/step - loss: 0.6867 - accuracy: 0.7446
Epoch 11/15
75/75 [=============] - 69s 920ms/step - loss: 0.6735 - accuracy: 0.7404
Epoch 12/15
```

75/75 [========= - 75s 995ms/step - loss: 0.6296 - accuracy: 0.7724

75/75 [=============] - 75s 988ms/step - loss: 0.6024 - accuracy: 0.7775

#Save the model

Epoch 13/15

Epoch 14/15

Epoch 15/15

model.save("flower.h5")

from tensorflow.keras.models import load_model

from tensorflow.keras.preprocessing import image

import numpy as np

model = load_model("Flower.h5")

```
In [7]: #Save the model
model.save("flower.h5")
```

#Test the model:

```
img = image.load img(r"C:\Users\hp\Downloads\rose.jpg",target size=(128,128))
```

img

type(img)

```
x = image.img\_to\_array(img)
X
x.shape
x = np.expand\_dims(x,axis=0)
x.shape
pred\_prob = model.predict(x)
pred_prob
 In [8]: from tensorflow.keras.models import load_model
          from tensorflow.keras.preprocessing import image
          import numpy as np
          model = load_model("Flower.h5")
In [10]: #Testing with the image
          img = image.load_img(r"C:\Users\hp\Downloads\rose.jpg",target_size=(128,128))
          img
          type(img)
Out[10]: PIL.Image.Image
In [11]: x = image.img_to_array(img)
          x.shape
          x = np.expand_dims(x,axis=0)
          x.shape
Out[11]: (1, 128, 128, 3)
In [12]: pred_prob = model.predict(x)
          pred_prob
Out[12]: array([[0., 0., 1., 0., 0.]], dtype=float32)
class_name = ["daisy", "dandelion", "rose", "sunfower", "tulip"]
pred_id = pred_prob.argmax(axis=1)[0]
pred_id
print("Predicted flower is",str(class_name[pred_id]))
```

```
In [13]: class_name = ["daisy","dandelion","rose","sunfower","tulip"]
In [15]: pred_id = pred_prob.argmax(axis=1)[0]
    pred_id
    print("Predicted flower is",str(class_name[pred_id]))
    Predicted flower is rose
```