Sprint 04

Signs with Smart Connectivity for Better Road Safety

Team ID	PNT2022TMID11468
Project Name	Signs with smart connectivity for Better road safety

Node RED :

Node RED flow :






```
// get Direction given UID msg.payload =
global.get(String(msg.payload.uid));
```

```
return msg;
// get UID msg.payload = msg.payload.uid;
return msg;
//      get     Location
msg.payload  = msg.payload.location;
return msg;
//      get     Visibility
msg.payload  = msg.payload.visibility;
return msg;
//      get     Temperature
msg.payload  = msg.payload.temperature;
return msg;
```

getSpeed API flow :




```
weatherObj = JSON.parse(JSON.stringify(msg.payload));
localityObj= global.get("data");
var suggestedSpeedPercentage = 100;
var preciseObject =  {          temperature
        : weatherObj.main.temp - 273.15, location
: localityObj.location, visibility        :
weatherObj.visibility/100,     uid       :
      localityObj.uid,
      direction : global.get("direction") };

msg.payload = preciseObject;

       return msg;

      weatherObj=JSON.parse(JSON.stringify

(msg.payload)); localityObj

         =          global.get("data");
var suggestedSpeedPercentage = 100;
var
         preciseObject =          {          temperature
         : weatherObj.main.temp - 273.15,
      weather : weatherObj.weather.map(x=>x.id).filter(code => code<700),
visibility : weatherObj.visibility/100 };
```

```
 if(preciseObject.visibility<=40) suggestedSpeedPercentage -=30

switch(String(preciseObject.weather)[-1])     //     https://openweathermap.org/weather-
 conditions refer weather codes meaning here
 { case "0" : suggestedSpeedPercentage -=10;break; case "1" :
       suggestedSpeedPercentage -=20;break; case "2"
       :
       suggestedSpeedPercentage -=30;break; }

 msg.payload = preciseObject;

 var doNotHonk = 0;
 if(localityObj.hospitalZone=="1"||localityObj.schoolZone=="1") doNotHonk
       = 1;

 var              returnObject              =              {              suggestedSpeed
       :  localityObj.usualSpeedLimit*(suggestedSpeedPercentage/100),  doNotHonk  :
       doNotHonk
 }
msg.payload     =     String(returnObject.suggestedSpeed)     +     "     kmph     \n\n"     +
 (returnObject.doNotHonk==1?"Do Not Honk":"") + "$" + global.get(String(localityObj.uid));

 return msg;
```




```
global.set(String(msg.payload.uid),msg.payload.dir);

 return msg;
```

Circuit Diagram :



ESP 32 CODE :

```
#include <WiFi.h> #include
<HTTPClient.h> #include
<Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>

const char* ssid = "Wokwi-GUEST";
const char* password = "";

#define TFT_DC 2
#define TFT_CS 15
Adafruit_ILI9341 tft = Adafruit_ILI9341(TFT_CS, TFT_DC);

String myLocation = "Chennai,IN"; String usualSpeedLimit =
"70"; // kmph

int schoolZone = 32; int hospitalZone
= 26;     int uid = 2504; // ID Unique to this Micro Contoller String

getString(char x)

{
      String s(1, x); return
      s;
}

String stringSplitter1(String fullString,char delimiter='$')
{
      String returnString = "";
      for(int i = 0; i<fullString.length();i++) { char c
            = fullString[i]; if(delimiter==c) break;
            returnString+=String(c);
```

```
    }
    return(returnString);
}

String stringSplitter2(String fullString,char delimiter='$')
{
    String returnString = ""; bool flag
    = false; for(int i = 0; i<fullString.length();i++) {
    char c = fullString[i];    if(flag)
    returnString+=String(c); if(delimiter==c) flag =
    true;
    }
    return(returnString);
}

void rightArrow()
{ int refX = 50; int refY =
  tft.getCursorY() + 40;

  tft.fillRect(refX,refY,100,20,ILI9341_RED);
  tft.fillTriangle(refX+100,refY-
30,refX+100,refY+50,refX+40+100,refY+10,ILI9341_RED);
}

void leftArrow()
{ int refX = 50; int refY =
  tft.getCursorY() + 40;

  tft.fillRect(refX+40,refY,100,20,ILI9341_RED); tft.fillTriangle(refX+40,refY-
  30,refX+40,refY+50,refX,refY+10,ILI9341_RED);
}

void upArrow()
{ int refX = 125; int refY =
  tft.getCursorY() + 30;

  tft.fillTriangle(refX-
40,refY+40,refX+40,refY+40,refX,refY,ILI9341_RED); tft.fillRect(refX-
15,refY+40,30,20,ILI9341_RED); }

String APICall() {
  HTTPClient http;

  String    url    =    "https://node-red-grseb-2022-11-05-test.eu-
gb.mybluemix.net/getSpeed?";
  url += "location="+myLocation+"&";
  url += "schoolZone="+(String)digitalRead(schoolZone)+(String)"&"; url +=
  "hospitalZone="+(String)digitalRead(hospitalZone)+(String)"&";url +=
  "usualSpeedLimit="+(String)usualSpeedLimit+(String)"&";
  url +=    "uid="+(String)uid; http.begin(url.c_str());
```

```
        int httpResponseCode = http.GET();if
        (httpResponseCode>0) {
      String payload = http.getString();
      http.end();
      return(payload);
    } else
    {
      Serial.print("Error code: ");
      Serial.println(httpResponseCode);
    } http.end();
}

void myPrint(String contents) {
    tft.fillScreen(ILI9341_BLACK);
    tft.setCursor(0, 20); tft.setTextSize(4);
    tft.setTextColor(ILI9341_RED);
    //tft.println(contents);

    tft.println(stringSplitter1(contents)); String c2 =
    stringSplitter2(contents); if(c2=="s") //
    represents Straight
    { upArrow();
    } if(c2=="l") // represents
    left
    { leftArrow();
    }
    if(c2=="r") // represents right
    { rightArrow();
    }
}

void setup() {
    WiFi.begin(ssid, password, 6);

    tft.begin();
    tft.setRotation(1);

    tft.setTextColor(ILI9341_WHITE);
    tft.setTextSize(2);
    tft.print("Connecting to WiFi");

    while (WiFi.status() != WL_CONNECTED)
       { delay(100); tft.print(".");
    }

    tft.print("\nOK! IP="); tft.println(WiFi.localIP());
}

void loop() { myPrint(APICall());
```

delay(100);}

Output :

Node RED Dashboard :



Wokwi Output :




main.ino
diagram.json
libraries.txt
Library Manager
Simulation
00:03.249
51%
#include <WiFi.h>
#include <HTTPClient.h>
#include <Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>
const char* ssid = "Wokwi-GUEST";
const char* password = "";
#define TFT_DC 2
#define TFT_CS 15
Adafruit_ILI9341 tft = Adafruit_ILI9341(TFT_
String myLocation = "Chennai,IN";
String usualSpeedLimit = "70"; // kmph
int schoolZone = 32;
int hospitalZone = 26;
int uid = 2504;
String getString(char x)
{
String s(1, x);
return s;
}
String stringSplitter1(String fullString,cha
{
String returnString = "";
for(int i = 0; i<fullString.length();i++
char c = fullString[i];
if(delimiter==c)
break;
returnString+=String(c);
}
ESP32
70 kmph
ILI9341


main.ino
diagram.json
libraries.txt
Library Manager
Simulation
00:08.899
26%
#include <WiFi.h>
#include <HTTPClient.h>
#include <Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>
const char* ssid = "Wokwi-GUEST";
const char* password = "";
#define TFT_DC 2
#define TFT_CS 15
Adafruit_ILI9341 tft = Adafruit_ILI9341(TFT_
String myLocation = "Chennai,IN";
String usualSpeedLimit = "70"; // kmph
int schoolZone = 32;
int hospitalZone = 26;
int uid = 2504;
String getString(char x)
{
String s(1, x);
return s;
}
String stringSplitter1(String fullString,cha
{
String returnString = "";
for(int i = 0; i<fullString.length();i++
char c = fullString[i];
if(delimiter==c)
break;
returnString+=String(c);
}
ESP32
70 kmph
Do Not Honk
ILI9341


main.ino
diagram.json
libraries.txt
Library Manager
Simulation
00:29.914
75%
https://node-red-grseb-2022-11
set/setDirection?uid=2504&dir=r
Incognito
{"uid":"2504","dir":"r"}
#include <WiFi.h>
#include <HTTPClient.h>
#include <Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>
const char* ssid = "Wokwi-GUEST";
char c = fullString[i];
if(delimiter==c)
break;
returnString+=String(c);
}
ESP32
70 kmph
Do Not Honk
ILI9341


main.ino
diagram.json
libraries.txt
Library Manager
Simulation
00:33.680
35%
#include <WiFi.h>
#include <HTTPClient.h>
#include <Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>
const char* ssid = "Wokwi-GUEST";
https://node-red-grseb-2022-11
Incognito
{"uid":"2504","dir":"1"}
char c = fullString[i];
if(delimiter==c)
break;
returnString+=String(c);
ESP32
70 kmph
Do Not Honk
ILI9341