Sprint 4

Team ID	PNT2022TMID31307
Project Name	Personal Assistance for Seniors Who Are Self
	Reliant

Code for Simulation:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include <LiquidCrystal I2C.h>
#include "DHT.h"// Library for dht11
#define DHTPIN 15
                  // what pin we're connected to
#define DHTTYPE DHT11 // define type of sensor DHT 11
#define LED 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr
of dht connected
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "64yf7x"//IBM ORGANITION ID
#define DEVICE TYPE "b11m3edevicetype"//Device type mentioned in ibm watson
IOT Platform
#define DEVICE_ID "b11m3edeviceid"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "-&EMtr71-v-Gz2G))e"
//Token
String data3="";
int buzz= 13;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server
Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
LiquidCrystal_I2C lcd(0x27,16,2);
WiFiClient wifiClient; // creating the instance for wificlient
```

```
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
void setup()// configureing the
ESP32
 Serial.begin(115200);
dht.begin();
pinMode(buzz, OUTPUT);
pinMode(LED,OUTPUT);
delay(10);
Serial.println();
wificonnect();
mqttconnect();
} void loop()// Recursive
Function
if(!client.loop()) {
mqttconnect();
}
}
/*....retrieving to
Cloud....*/
 void PublishData(float temp, float humid) {
mqttconnect();//function call for connecting to ibm
   }
void mqttconnect() {
if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)){
   Serial.print(".");
   delay(500);
   initManagedDevice();
   Serial.println();
void wificonnect() //function defination for
wificonnect
{
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to
establish the connection
 while (WiFi.status() != WL_CONNECTED) {          delay(500);
    Serial.print(".");
  }
 Serial.println("");
```

```
Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice()
if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++){</pre>
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
  Serial.println("Medicine Name: "+ data3);
if(data3 != "") {
      lcd.init();
      lcd.print(data3);
      digitalWrite(LED,HIG
              tone(buzz,
      H);
      100, 1000);
      delay(2000);
      digitalWrite(LED,LOW
      );
      noTone(buzz);
      delay(1000);
  }
  else {
digitalWrite(LED,LOW;
  }
data3=""
}
```