

Project Design Phase-II
Functional Requirement Template

Date	06 October 2022
Team ID	PNT2022TMID31372
Project Name	Project – Real -Time Communication System Powered By AI For Specially Abled
Maximum Marks	2 Marks

Functional Requirements:

- Here , the **Desktop along with the Camera** is presented as **black box**.
- Deaf/Dumb is the person, who will **show different signs based on the type of information being conveyed**.
- **Normal Person is the passive user** of the desktop.

The **System requirements** that are required are specified below,

- Deaf/Dumb person should be able to **perform a sign that represents digit/number**.
- Deaf/Dumb person should be able to **perform a sign that represents a character**.
- Deaf/Dumb person should be able to **perform a sign , where group of characters forms a word**.
- Deaf/Dumb person should be able to **perform a sign, where group of words forms a sentence**.
- Especially Deaf people especially should be able to **see the translation of signs to text format**.
- Dumb person should be able to **understand the conversion of text into voice mode**.
- **Normal users should be able to understand the corresponding information conveyed by disabled through sign language**.

Default Operation:

- Users of the app **face the camera and perform the concerned hand sign to convey information**.
- System/Desktop **analyses the sign made by the user**.
- Once analysis gets finished, then the **concerned signs together are shown as a text based and also through voice**.

Unexpected Operations:

- **Desktop indicates that the user's hand sign is not within the frame or inRegion of Interest(ROI).**

1. Users of the app **show the hand sign towards the camera.**
2. Desktop shows that the sign **is not within ROI.**
3. Still User , make sure to present his/her sign within frame.
4. At last, **Desktop finally detects the hand sign.**

- **Signs are not recognized**

1. **Excepts the signs that are trained and included in the dataset, the Desktop will never detect the sign rather than this.**
2. User Performs the sign and sees that after 50ms, **the concerned letter occupies the space of text.**

- **Speech/Voice assistant is implemented**

Speech assistant is to be implemented in order to **convert the output text into voice .**