

Assignment -4

Team ID	PNT2022TMID12669
Project Name	Project - IoT based safety gadget for Child Safety Monitoring and Notification
Name	Aditya

QUESTION:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events. Upload document with wokwi share link and images of ibm cloud.

CODE:

```
#include <WiFi.h>
#include <PubSubClient.h>
#include <ArduinoJson.h>

WiFiClient wifiClient;
#define ORG "fvdupc"

#define DEVICE_TYPE "abcd"
#define DEVICE_ID "rasp" #define
TOKEN "12345678" #define speed
0.034 char
server[] = ORG
".messaging.internetofthings.ibmcloud.com"; char publishTopic[]
= "iot-2/evt/abcd_1/fmt/json"; char topic[] = "iot-
2/cmd/home/fmt/String"; char authMethod[] = "use-tokenauth";
char token[] = TOKEN; char clientId[] = "d:" ORG ":"
DEVICE_TYPE ":" DEVICE_ID; PubSubClient client(server, 1883,
wifiClient); void publishData();

const int trigpin=5;
const int echopin=18;
String command;
String data="";
String lat="14.167589";
String lon="80.248510";
String name="point2";
String
icon=""; long
duration; int
dist;

void setup()
{
```

```

    Serial.begin(115200);
    pinMode(trigpin, OUTPUT);
    pinMode(echopin, INPUT);
    wifiConnect(); mqttConnect();
} void
loop()
{    publishData();
delay(500);    if
(!client.loop()) {
mqttConnect();
}
} void
wifiConnect()
{
    Serial.print("Connecting to ");
    Serial.print("Wifi"); WiFi.begin("Wokwi-GUEST", "",
6); while (WiFi.status() != WL_CONNECTED) {
        delay(500);
        Serial.print(".");
    }
    Serial.print("WiFi connected, IP address: ");
    Serial.println(WiFi.localIP());
} void
mqttConnect()
{    if (!client.connected())
    {
        Serial.print("Reconnecting MQTT client to ");
        Serial.println(server); while (!client.connect(clientId, authMethod,
token)) { Serial.print("."); delay(1000);
        }
        initManagedDevice();
        Serial.println();
    }
} void
initManagedDevice()
{    if (client.subscribe(topic))
    {
        Serial.println(client.subscribe(topic));
        Serial.println("subscribe to cmd OK");
    } else {
        Serial.println("subscribe to cmd FAILED");
    } } void publishData()
{    digitalWrite(trigpin,LOW);
    digitalWrite(trigpin,HIGH);
    delayMicroseconds(10);
    digitalWrite(trigpin,LOW);
    duration=pulseIn(echopin,HIGH)
    ; dist=duration*speed/2;
if(dist<100){
dist=100dist;
icon="fatrash";    }else{
dist=0; icon="fa-trasho";
}
}


```

```

DynamicJsonDocument doc(1024);
String payload;
doc["Name"]=name;
doc["Latitude"]=lat;
doc["Longitude"]=lon;
doc["Icon"]=icon;
doc["FillPercent"]=dist;
serializeJson(doc, payload);
delay(3000);
Serial.print("\n");
Serial.print("Sending payload: "); Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
{ Serial.println("Publish OK");
} else {
    Serial.println("Publish FAILED");
}
}

```

CONNECTIONS:



OUTPUT:

WOKWI

SAVE

SHARE

Docs

sketch.ino

diagram.json

libraries.txt


Library Manager

```
1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 #include <ArduinoJson.h>
4
5 WiFiClient wificlient;
6
7 #define ORG "fvdupc"
8 #define DEVICE_TYPE "abcd"
9 #define DEVICE_ID "rasp"
10 #define TOKEN "12345678"
11 #define speed 0.034
12
13 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
14 char publishTopic[] = "iot-2/evt/abcd_1/fmt/json";
15 char topic[] = "iot-2/cmd/home/fmt/string";
16 char authMethod[] = "use-token-auth";
17 char token[] = TOKEN;
18 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
19 PubSubClient client(server, 1883, wificlient);
20 void publishData();
21
22 const int trigpin=5;
23 const int echopin=18;
24 String command;
25 String data="";
26 String lat="14.167589";
27 String lon="80.248510";
28 String name="point2";
29 String icon="";
30
31 long duration;
32 int dist;
33
34 void setup()
35 {
```

Simulation

00:06.799

Restart the simulation



subscribe to cmd OK

Sending payload:
{ "Name": "point2", "Latitude": "14.167589", "Longitude": "80.248510", "Icon": "fa-trash-o", "FillPercent": 0 }

Publish OK