SMART WASTE MANAGEMENT SYSTEM FOR METROPOLITAN CITIES

DOMAIN – INTERNET OF THINGS (IoT)

A PROJECT REPORT

SUBMITTED BY TEAM ID: PNT2022TMID25449

MANO B MENTOR: A.N. Duraivel

JENSY J

NEELAVANNAK ANNAN S MUNIRAJ N

In the partial fulfillment of the requirements for the award of a degree of BACHELOR OF ENGINEERING in ELECTRONIC AND COMMUNICATION ENGINEERING

KINGS ENGINEERING COLLEGE

IRUNGATTUKOTTAI

2022 – 2023

CONTENT

1. INTRODUCTION

Project Overview

Purpose

2. LITERATURE SURVEY

Existing problem

References

Problem Statement Definition

3. IDEATION & PROPOSED SOLUTION

Empathy Map Canvas

Ideation & Brainstorming

Proposed Solution

Problem Solution fit

4. REQUIREMENT ANALYSIS

Functional requirement

Non-Functional requirements

5. PROJECT DESIGN

Data Flow Diagrams

Solution & Technical Architecture

User Stories

6. PROJECT PLANNING & SCHEDULING

Sprint Planning & Estimation

Sprint Delivery Schedule

Reports from JIRA

7. CODING & SOLUTIONING (Explain the features added in the project along with code)

Feature 1

Feature 2

Database Schema (if Applicable)

8. TESTING

Test Cases

User Acceptance Testing

9. RESULTS

Performance Metrics

10. ADVANTAGES & DISADVANTAGES

11. CONCLUSION

12. FUTURE SCOPE

13. APPENDIX

Source Code

GitHub & Project Demo Link

1. INTRODUCTION

Internet of Things is nothing but the applications performing with the help of internet access.

IoT Communication over the internet has grown from user - user interaction to device — device interactions these days. The IoT concepts were proposed years back but still it's in the initial stage of commercial deployment. Home automation industry and transportation industries are seeing rapid growth with IoT. The basic project idea is to design a smart waste detection system which would automatically notify the officials about the current status of various garbage bins in the city, would have realtime monitoring capabilities, which would be remotely controlled using IoT techniques. This paper introduces you to the use of IoT on one such area, that is, Garbage Detection in smart ways using IoT and see how this can also be a major part of developing a city into a smart city.

Project Overview

A big challenge in the urban cities is that of waste management as there is a rapid growth in the rate of urbanization and thus there is a need of sustainable urban development plans. As the concept of smart cities is very much trending these days and the smart cities cannot be complete without smart waste management system. There needs to be system that gives prior information of the filling of the bin that alerts the municipality so that they can clean the bin on time and safeguard the environment. To avoid all such situations we intend to propose a solution for this problem "Smart Garbage Bin", which will alarm and inform the authorized person when the garbage bin is about to fill. Then message will be send to the authorized person to collect the garbage from the particular area. The authorized person will sends the message from his web application to the garbage collectors by sending a SMS .This system maintain a dry waste and a wet waste separately. This will help to reduce the overflow of the garbage bin and thus keeping the environment clean.

Purpose

This project helps the citizens to make their surroundings and environment clean, pollution free and lead a healthy life throughout. It avoids the possibility garbage overflow, unhygienic environment, air-borne and water-borne disease, etc...

2. LITERATURE SURVEY

EXISTING PROBLEM

In the existing system garbage is collected by the corporation weekly once or twice. Sometimes the garbage stinks and overflows from the bin and spread over the roads and pollutes the environment. This also produces a heavy air pollution and routes to various air-borne diseases. Many a times the street dogs and other animals eat these waste and scatter these waste around the surroundings which creates the spread of various diseases and situation of unclean environment.

Disadvantages of existing system:

- Time consuming and less effective.
- Overflow of waste from the bin.
- Unhygienic Environment and look of the city.
- Stinky smell and unpleasant situations.

PROPOSED SYSTEM:

In this proposed system there will be no issues repeated that of previous system. In this system the bin is designed in such a way that when the waste level reaches the threshold limit it

automatically closes the bin and intimates the alert to the admin . The bins are provided with low cost embedded device which helps in tracking the level of the garbage bins and a unique ID will be provided for every dustbin in the city . These details can be accessed by the concern authorities from their place with the help of internet and an immediate action can be made to clean the bin. The admin can monitor the level of the bin and can trace the location where it exists.

Advantages:

- Real time information on the fill level of the dustbin.
- Deployment of dustbin based on the actual needs.
- Cost Reduction and resource optimization.
- Improves Environment quality.

REFERENCES:

- [1] Ikuo Ihara; Nagaoka University of Technology; Ultrasonic Sensing: Fundamentals and Its Applications to Non-destructive Evaluation.
- [2] Arduino, "Available at http://www.arduino.cc," 2010.
- [3] M. Batty, "Smart Cities, Big Data," Environment and Planning B: Planning and Design 2012, vol. 39, pp. 191–93.
- [4] Xu Li, Student Member, IEEE, Performance Evaluation of Vehicle-Based Mobile Sensor Networks for Traffic Monitoring.
- [5] Yusuf Abdullahi Badamasi, The Working Principle Of An Arduino, Electronics, Computer and Computation (ICECCO), 2014 11th International Conference on 29 Sept.-1 Oct. 2014.


Problem Statement

The waste management system provided earlier are not very reliable, efficient, cost effective and does not have any advanced processing features like automatic close of bin and alert intimations system .The following is a well articulated problem statement that allows you to find the ideal solution for the challenges faced.




| Problem statement | I am (customer) | I'm trying to | But | Because | Which makes me feel |
|-------------------|------------------------------|---|---|---|--|
| PS-1 | People (smart dustbin) | Elimination of missed pickups | Irregular collection service | Refusal to learn about compliance | Environmental Degradation |
| PS-2 | Smart dustbin | Sense all type of waste material it is in the form of solid or liquid | Requires of these type of sensors | Execution of new sensors for the problem | Uncleanness |
| PS-3 | Tracker | Using container tracking your waste changes to smart pastures | Irregular collection coverage | Inappropriate Collection waste | Sanitary landfill and unhygienic condition |

3. IDEATION & PROPOSED SOLUTION EMPATHY MAP CANVAS




Ideation and Brainstorming



PROPOSED SOLUTION

| S.No. | Parameter | Description |
|-------|--|---|
| 1. | Problem Statement (Problem to be solved) | To maintain waste in the metropolitan cities and to maintain the clean environment which is polluted by the wastes and to dispose wastes. |
| 2. | Idea / Solution description | -Software can be implemented -Fine can be implemented -Create awareness |
| 3. | Novelty / Uniqueness | This system provides awareness among the people and safeguard the environment with the help of people. |
| 4. | Social Impact / Customer Satisfaction | Clean cities Healthy environment Peaceful life |
| 5. | Business Model (Revenue Model) | -Offering software as a service model to government. -Making use of useful wastes and making it us money. |
| 6. | Scalability of the Solution | To help government to maintain clean environment. |

PROBLEM SOLUTION FIT



4 . REQUIREMENT ANALYSIS

FUNCTIONAL REQUIREMENT

Following are the functional requirements of the proposed solution.

| FR No. | Functional Requirement (Epic) | Sub Requirement (Story / Sub-Task) |
|--------|-------------------------------|--|
| FR-1 | User Authentication | Collecting data from the transmitted signal |
| FR-2 | IBM Watson IOT Platform | Stores the sensed data and alerts. |
| FR-3 | Node RED | Designs the wireframing and connection of user interface |
| FR-4 | Web User Interface | Created by Node RED service connected to IBM Watson IOT platform |
| FR-5 | Database | Fetched data is intimated and updated in the database |
| FR-6 | Python script | Generates random data to the iot device and transmits to the Watson cloud. |


NON-FUNCTIONAL REQUIREMENT

Following are the non-functional requirements of the proposed solution.


| Non-Functional Requirement | Description |
|----------------------------|---|
| Usability | Separate bins for recyclable and non |
| Security | Data fetched can be only accessed by authorized user |
| Reliability | Accurate data and availabity is displayed |
| Performance | Detects and intimates alerts on reaching fixed limit. |
| Availability | Accessible through 24/7 by user and authorizer |
| Scalability | Holds vast accessibility by the user |
| | Usability Security Reliability Performance Availability |

5. PROJECT DESIGN

. DATA FLOW DIAGRAM



. SOLUTION ARCHITECTURE AND TECHNICAL ARCHITECTURE



USER STORIES

| User Type | Functional Requirement (Epic) | User Story Number | User Story / Task | Acceptance criteria | Priority | Release |
|---|-------------------------------------|----------------------|---|--|----------|----------|
| Customer (Mobile user / Web user) | Signup | USN-1 | User can signup using their email and password and confirm the details. | I can access my account / dashboard | High | Sprint-1 |
| | | USN-2 | A confirmation mail is sent to the user. | I can receive confirmation email & click confirm | High | Sprint-1 |
| | Login | USN-3 | User can login using login credentials | User can log on to the website | High | Sprint-1 |
| | Dashboard | USN-4 | User can specify the location and area to check the availability of bins. | User can access dashboard and search for bins in specified areas | High | Sprint-2 |
| | 8 | USN-5 | User can post the queries and grievances in the report section | Options are provided to solve user issues | Medium | Sprint-2 |
| | | | | | | |

6. PROJECT PLANNING AND SCHEDULING

. SPRINT PLANNING AND ESTIMATION


| TITLE | DESCRIPTION | | |
|--|---|--|--|
| Literature Survey and Information Gathering | Surveying on the topic of selected project & gathering information by referring the, technical papers ,research publications etc. | | |
| Prepare Empathy Map | Prepare Empathy Map Canvas to capture the user pains & gains on particular issue. | | |
| Ideation | Jot down the ideas by organizing the brainstorming session and prioritize the top 3 ideas based on the feasibility & importance. | | |
| Proposed Solution | Prepare your proposed solution of the project which includes the novelty, feasibility of idea, business model, social impact, scalability of solution, etc. | | |
| Problem Solution Fit | Prepare problem - solution fit document. | | |
| Solution Architecture | Prepare solution architecture document. | | |
| Customer Journey Map | Prepare the customer journey maps to understand the user interactions & experiences with the application (entry to exit) | | |
| Functional Requirement | Prepare the functional requirement for the project. | | |
| Data Flow Diagrams | Draw the data flow diagrams to understand the flow of execution o the project. | | |
| Technology Architecture | Prepare the technology architecture diagram. | | |
| Milestone & Activity List | Prepare the milestones & activity list of the project. | | |
| Delivery of Sprints | Submit the coding development of the project and submit in sprints. Sprint -1 Sprint -2 Sprint -3 Sprint -4 | | |

SPRINT DELIVERY SCHEDULE


| Sprint | Functional Requirement (Epic) | User Story Number | User Story / Task | Story Points | Priority |
|------------|----------------------------------|----------------------|---|--------------|----------|
| Sprint-1 | Sign up / Sign in | USN - 1 | User can signup using their email and password and confirm the details. | 10 | High |
| Sprint-1 | | USN - 2 | A confirmation mail is sent to the user. | 10 | High |
| Sprint-2 | Login | USN - 3 | User can login using login credentials and is authenticated. | 20 | Low |
| Sprint-3 | Dashboard | USN - 4 | User can view the previous login activities of the account and updates. | 10 | Medium |
| Sprint - 4 | Search Location | USN - 5 | User can search for the bins available around the location. | 10 | High |
| Sprint - 4 | Results / Grievances | USN - 6 | User can post their grievances related to the bins and gets the results of bin status around the location from IBM Cloud. | 10 | High |

JIRA REPORTS

ROADMAP



SPRINT BURNDOWN CHART



7. CODING AND SOLUTION

Wokwi code for Sensor transmission


```
#include <WiFi.h>
                                              // library for wifi
#include <PubSubClient.h>
                                              // library for MQTT
#include <LiquidCrystal I2C.h>
#include <mjson.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);
//----- credentials of IBM Accounts --
#define ORG "9gbe4w"
                                          // IBM organisation id
#define DEVICE_TYPE "SWMSMC"
                                          // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "ibmproject"
                                          // Device ID mentioned in ibm watson iot platform
#define TOKEN "sUNA41tG6-Pq)0rk5X"
                                          // Token
//----customise above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
                                                                           // server name
char publishTopic[] = "iot-2/evt/data/fmt/json";
                                                                          // topic name and type of event perform and format
in which data to be send
char topic[] = "iot-2/cmd/led/fmt/String";
                                                                           // cmd Represent type and command is test format of
strings
char authMethod[] = "use-token-auth";
                                                                            // authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
                                                                           //Client id
WiFiClient wifiClient;
                                                                          // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define ECHO_PIN 12
#define TRIG_PIN 13
float dist;
String data3;
bool SealBin = true;
void setup()
 Serial.begin(115200);
 pinMode(LED_BUILTIN, OUTPUT);
 pinMode(TRIG_PIN, OUTPUT);
 pinMode(ECHO_PIN, INPUT);
 //pir pin
 pinMode(34, INPUT);
 //ledpins
 pinMode(23, OUTPUT);
 pinMode(2, OUTPUT);
 pinMode(4, OUTPUT);
 pinMode(15, OUTPUT);
 lcd.init();
 lcd.backlight();
 lcd.setCursor(1, 0);
 lcd.print("");
wifiConnect();
 mqttConnect();
float readcmCM()
 digitalWrite(TRIG_PIN, LOW);
 delayMicroseconds(2);
 digitalWrite(TRIG_PIN, HIGH);
 delayMicroseconds(10);
 digitalWrite(TRIG_PIN, LOW);
 int duration = pulseIn(ECHO_PIN, HIGH);
 return duration * 0.034 / 2;
```

```
void loop()
 lcd.clear();
 publishData();
 delay(500);
 if (!client.loop())
     mqttConnect();
                                                      // function call to connect to IBM
}
/* ·····retrieving to cloud-
void wifiConnect()
{
 Serial.print("Connecting to ");
 Serial.print("Wifi");
 WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED)
   {
     delay(500);
     Serial.print(".");
  Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
void mqttConnect()
 {
   if (!client.connected())
     {
       Serial.print("Reconnecting MQTT client to ");
        Serial.println(server);
       while (!client.connect(clientId, authMethod, token))
         {
           Serial.print(".");
           delay(500);
       initManagedDevice();
       Serial.println();
void initManagedDevice()
   if (client.subscribe(topic))
        Serial.println("IBM subscribe to cmd OK");
     }
   else
     {
       Serial.println("subscribe to cmd FAILED");
void publishData()
{
  float cm = readcmCM();
  if(digitalRead(34))
                                                    //pir motion detection
   Serial.println("Motion Detected");
   Serial.println("Lid Opened");
   digitalWrite(15, HIGH);
 if(digitalRead(34)== true)
  if(cm <= 100)
                                                             //Bin level detection
 {
   digitalWrite(2, HIGH);
   Serial.println("High Alert!!!,Trash bin is about to be full");
```

```
Serial.println("Lid Closed");
    lcd.print("Full! Don't use");
    delay(2000);
    lcd.clear();
    digitalWrite(4, LOW);
    digitalWrite(23, LOW);
  else if(cm > 100 && cm < 180)
    digitalWrite(4, HIGH);
    Serial.println("Warning!!,Trash is about to cross 50% of bin level");
    digitalWrite(2, LOW);
    digitalWrite(23, LOW);
  else if(cm > 180)
    digitalWrite(23, HIGH);
    Serial.println("Bin is available");
    digitalWrite(2,LOW);
    digitalWrite(4, LOW);
    delay(10000);
    Serial.println("Lid Closed");
 }
 else
  Serial.println("No motion detected");
   digitalWrite(2, LOW);
    digitalWrite(15, LOW);
    digitalWrite(4, LOW);
    digitalWrite(23, LOW);
}
}
  else
    digitalWrite(15, LOW);
 }
 if(cm <= 100)
digitalWrite(21,HIGH);
String payload = "{\"High_Alert\":";
payload += cm;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
                                                                   // if data is uploaded to cloud successfully, prints publish ok
else prints publish failed
Serial.println("Publish OK");
}
else if(cm <= 180)</pre>
digitalWrite(22,HIGH);
String payload = "{\"Warning\":";
payload += cm ;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishTopic, (char*) payload.c_str()))
Serial.println("Publish OK");
else
```

```
Serial.println("Publish FAILED");
else if(cm > 180)
digitalWrite(23,HIGH);
String payload = "{";
payload += cm;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
                                                                   // if data is uploaded to cloud successfully, prints publish ok
else prints publish failed
Serial.println("Publish OK");
}
 float inches = (cm / 2.54);
                                                                   //print on lcd
 lcd.setCursor(0,0);
 lcd.print("Inches");
 lcd.setCursor(4,0);
 lcd.setCursor(12,0);
 lcd.print("cm");
 lcd.setCursor(1,1);
 lcd.print(inches, 1);
 lcd.setCursor(11,1);
 lcd.print(cm, 1);
 lcd.setCursor(14,1);
 delay(1000);
 lcd.clear();
//handles commands from user side
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
    data3 += (char)payload[i];
 Serial.println("data: "+ data3);
  const char *s =(char*) data3.c_str();
 double pincode = 0;
        const char *buf;
        int len;
        if (mjson_find(s, strlen(s), "\$.command", &buf, &len)) // And print it
          String command(buf,len);
          if(command=="\"SealBin\"")
            SealBin = true;
          }
         }
 data3="";
```

. Sensor Connection Setup




PHYSICAL COMPONENTS:


- PIR MOTION SENSOR
- ULTRASONIC DISTANCE SENSOR
- ESP32-ARDUINO MICROCONTROLLER

OUTPUT:

WOKWI SETUP



WEB UI





The admin gets notification when the bin detects motion and if the bin level crosses 50 percent it indicates warning and if it crosses 90 percent it gives a High alert and closes the bin. If the admin wants to seal the bin the admin can command seal bin until it is accessed for cleaning.

Test Case:

Maximum Size of Bin: 200 cm Safe limit: below 100 cm

Minimum threshold limit of bin: 100 cm Maximum threshold limit of bin: 180 cm

| S.no | Bin Level | Bin Status | Location |
|------|-------------|------------|--------------|
| | (cm filled) | | |
| 1 | 45 | Safe | Kanyakumari |
| 2 | 78 | Safe | Coimbatore |
| 3 | 112 | Warning | Trichy |
| 4 | 169 | Warning | Chennai |
| 5 | 186 | Warning | Ooty |
| 6 | 193 | High_Alert | Tirunelveli |
| 8 | 0 | Safe | Chengalpattu |
| 9 | 35 | Safe | Madurai |
| 10 | 101 | Warning | Salem |
| 11 | 132 | Warning | Thanjavore |
| 12 | 158 | Warning | Vellore |
| 13 | 93 | High_Alert | Erode |
| 14 | 93 | High_Alert | Karur |
| 15 | 93 | High_Alert | Cuddalore |
| 16 | 30 | Safe | Kumbakonam |
| 17 | 110 | Warning | Ambur |
| 18 | 180 | Warning | Sivakasi |
| 19 | 195 | High_Alert | Neyveli |
| 20 | 80 | Safe | Krishnagiri |

Note: The bin location provided above is default. When the user access the bin , the location and status of the bin displayed to the admin.

USER ACCEPTANCE TESTING

1. Purpose of Document

The purpose of this document is to briefly explain the test coverage and open issues of the Smart Waste Management System project at the time of the release to User Acceptance Testing (UAT).

2. Defect Analysis

This report shows the number of resolved or closed bugs at each severity level, and how they were resolved.

| Resolution | Severity 1 | Severity 2 | Severity 3 | Severity 4 | Subtotal |
|----------------|------------|------------|------------|------------|----------|
| By Design | 10 | 4 | 3 | 3 | 20 |
| Duplicate | 1 | 0 | 3 | 0 | 4 |
| External | 2 | 3 | 0 | 1 | 6 |
| Fixed | 11 | 2 | 4 | 20 | 37 |
| Not Reproduced | 0 | 0 | 1 | 0 | 1 |
| Skipped | 0 | 0 | 1 | 1 | 2 |
| Won't Fix | 0 | 5 | 2 | 1 | 8 |
| Totals | 24 | 14 | 13 | 26 | 78 |

3. TEST CASE ANALYSIS


This report shows the number of test cases that have passed, failed and untested.

| Section | Total Cases | Not Tested | Fail | Pass |
|---------------------|-------------|------------|------|------|
| Print Engine | 7 | 0 | 0 | 7 |
| Client Application | 51 | 0 | 0 | 51 |
| Security | 2 | 0 | 0 | 2 |
| Outsource Shipping | 3 | 0 | 0 | 3 |
| Exception Reporting | 9 | 0 | 0 | 9 |
| Final Report Output | 4 | 0 | 0 | 4 |
| Version Control | 2 | 0 | 0 | 2 |


9. RESULTS

Performance Metrics





. Admin Web UI





10. ADVANTAGES AND DISADVANTAGES

ADVANTAGES

- Reduction in Collection Cost
- No Missed Pickups
- Reduced Overflows
- Waste Generation Analysis
- CO2 Emission Reduction

DISADVANTAGES

- System requires a greater number of waste bins for separate waste collection as per population in the city.
- This results into high initial cost due to expensive smart dustbins compare to other methods. Sensor nodes used in the dustbins have limited memory size.

11. CONCLUSION:

A Smart Waste Management system that is more effective than the one in use now is achievable by using sensors to monitor the filling of bins. Our conception of a "smart waste management system" focuses on monitoring waste management, offering intelligent technology for waste systems, eliminating human intervention, minimizing human time and effort, and producing a healthy and trashfree environment. The suggested approach can be implemented in smart cities where residents have busy schedules that provide little time for garbage management. If desired, the bins might be put into place in a metropolis where a sizable container would be able to hold enough solid trash for a single unit. But these may price bit high.

12. FUTURE SCOPE:

There are several future works and improvements for the proposed system, including the following:

• Changes the system of user authentication and atomic lock of bins, which would aid in protecting the bin from damage or theft.

- The concept of green points would encourage the involvement of residents or end users, making the idea successful and aiding in the achievement of collaborative waste management efforts, thus fulfilling the idea of 'Swachh Bharath'.
- Having case study or data analytics on the type and times waste is collected on different days
 or seasons, making the bin level predictable and remove the reliance on electronic
 components, and fixing the coordinates.
- Improving the Server's and Android's graphical interfaces

13. APPENDIX

• Esp32 - Microcontroller :

ESP32 is a series of low-cost, low-power system on a chip microcontrollers with integrated Wi-Fi and dual-mode Bluetooth.

Memory: 320 KiB

> SRAM CPU: Tensilica Xtensa LX6 microprocessor @ 160 or 240 MHz

Power: 3.3 V DC

Manufacturer: Espressif Systems

Predecessor: ESP8266

• Sensors:

- ➤ PIR motion sensor: PIR sensors allow you to sense motion, almost always used to detect whether a human has moved in or out of the sensors range.
- Ultrasonic Distance Sensor: Ultrasonic Sensors measure the distance to the target by measuring the time between the emission and reception.

. Source code

```
#include <WiFi.h>
                                           // library for wifi
#include <PubSubClient.h>
                                            // library for MQTT
#include <LiquidCrystal_I2C.h>
#include <mjson.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);
//----credentials of IBM Accounts
#define ORG "9gbe4w"
                                         // IBM organisation id
#define DEVICE_TYPE "SWMSMC"
                                         // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "ibmproject"
                                         // Device ID mentioned in ibm watson iot platform
#define TOKEN "sUNA41tG6-Pq)0rk5X"
//----customise above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
                                                                       // server name
char publishTopic[] = "iot-2/evt/data/fmt/json";
// topic name and type of event perform and format in which data to be send
char topic[] = "iot-2/cmd/led/fmt/String";
// cmd Represent type and command is test format of strings
char authMethod[] = "use-token-auth";
// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
                                                                       //Client id
WiFiClient wifiClient;
                                                                       // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define ECHO_PIN 12
#define TRIG_PIN 13
float dist;
String data3;
bool SealBin = true;
void setup()
 Serial.begin(115200);
 pinMode(LED_BUILTIN, OUTPUT);
 pinMode(TRIG_PIN, OUTPUT);
 pinMode(ECHO_PIN, INPUT);
 //pir pin
 pinMode(34, INPUT);
 //ledpins
 pinMode(23, OUTPUT);
 pinMode(2, OUTPUT);
 pinMode(4, OUTPUT);
 pinMode(15, OUTPUT);
 lcd.init();
 lcd.backlight();
 lcd.setCursor(1, 0);
 lcd.print("");
 wifiConnect();
 mqttConnect();
float readcmCM()
 digitalWrite(TRIG_PIN, LOW);
 delayMicroseconds(2);
 digitalWrite(TRIG_PIN, HIGH);
 delayMicroseconds(10);
 digitalWrite(TRIG PIN, LOW);
 int duration = pulseIn(ECHO_PIN, HIGH);
 return duration * 0.034 / 2;
void loop()
```

```
{
 lcd.clear();
 publishData();
 delay(500);
  if (!client.loop())
   {
     mqttConnect();
                                                       // function call to connect to IBM
                   ·····retrieving to cloud-
void wifiConnect()
{
 Serial.print("Connecting to ");
  Serial.print("Wifi");
  WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED)
     delay(500);
     Serial.print(".");
  Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
void mqttConnect()
  {
   if (!client.connected())
     {
       Serial.print("Reconnecting MQTT client to ");
       Serial.println(server);
       while (!client.connect(clientId, authMethod, token))
           Serial.print(".");
           delay(500);
       initManagedDevice();
void initManagedDevice()
 {
   if (client.subscribe(topic))
     {
       Serial.println("IBM subscribe to cmd OK");
   else
     {
        Serial.println("subscribe to cmd FAILED");
     }
void publishData()
{
  float cm = readcmCM();
  if(digitalRead(34))
                                                     //pir motion detection
   Serial.println("Motion Detected");
   Serial.println("Lid Opened");
   digitalWrite(15, HIGH);
 if(digitalRead(34)== true)
  if(cm <= 100)
                                                              //Bin level detection
  {
   digitalWrite(2, HIGH);
   Serial.println("High Alert!!!,Trash bin is about to be full");
   Serial.println("Lid Closed");
   lcd.print("Full! Don't use");
   delay(2000);
```

```
lcd.clear();
    digitalWrite(4, LOW);
    digitalWrite(23, LOW);
  else if(cm > 100 && cm < 180)
    digitalWrite(4, HIGH);
    Serial.println("Warning!!,Trash is about to cross 50% of bin level");
    digitalWrite(2, LOW);
    digitalWrite(23, LOW);
  else if(cm > 180)
    digitalWrite(23, HIGH);
    Serial.println("Bin is available");
    digitalWrite(2,LOW);
    digitalWrite(4, LOW);
 }
    delay(10000);
    Serial.println("Lid Closed");
}
 else
  Serial.println("No motion detected");
   digitalWrite(2, LOW);
    digitalWrite(15, LOW);
    digitalWrite(4, LOW);
    digitalWrite(23, LOW);
}
}
  else
    digitalWrite(15, LOW);
 }
 if(cm <= 100)
{
digitalWrite(21,HIGH);
String payload = "{\"High_Alert\":";
payload += cm;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
                                                                   // if data is uploaded to cloud successfully,prints publish ok
else prints publish failed
Serial.println("Publish OK");
else if(cm <= 180)
digitalWrite(22,HIGH);
String payload = "{\"Warning\":";
payload += cm;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishTopic, (char*) payload.c_str()))
Serial.println("Publish OK");
}
else
Serial.println("Publish FAILED");
```

```
else if(cm > 180)
digitalWrite(23,HIGH);
String payload = "{";
payload += cm;
payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
                                                                   // if data is uploaded to cloud successfully, prints publish ok
else prints publish failed
Serial.println("Publish OK");
}
}
  float inches = (cm / 2.54);
                                                                    //print on lcd
 lcd.setCursor(0,0);
 lcd.print("Inches");
 lcd.setCursor(4,0);
 lcd.setCursor(12,0);
 lcd.print("cm");
 lcd.setCursor(1,1);
 lcd.print(inches, 1);
 lcd.setCursor(11,1);
 lcd.print(cm, 1);
 lcd.setCursor(14,1);
 delay(1000);
 lcd.clear();
//handles commands from user side
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {</pre>
   data3 += (char)payload[i];
 Serial.println("data: "+ data3);
  const char *s =(char*) data3.c_str();
 double pincode = 0;
        const char *buf;
        int len:
        if (mjson_find(s, strlen(s), "$.command", &buf, &len)) // And print it
        {
          String command(buf,len);
          if(command=="\"SealBin\"")
            SealBin = true;
          }
          }
 data3="";
```

. GITHUB LINK

<u>LINK</u>: https://github.com/IBM-EPBL/IBM-Project-39740-1660494184

<u>VIDEO DEMO LINK:</u> https://drive.google.com/drive/folders/1DF_l6rklGaHQnNWV_QZP3mCaq5S1S82u