Final Code

Team Id	PNT2022TMID36194
Project	Gas Leakage Monitoring and Alerting
	System For Industries
Team Members	Manikandan S,Keerthi J,Rupavathi S,Lavanya

FINAL CODE:

```
#include <LiquidCrystal.h>
LiquidCrystal lcd(6, 7, 8, 9, 10, 11);
float gasPin = A0;
float gasLevel;
int ledPin = 2;
int buttonPin = 3;
int buzzPin = 4;
int buttonState;
int fan = 5;
void setup(){
 pinMode(ledPin, OUTPUT);
 pinMode(buttonPin, INPUT);
 pinMode(gasPin,INPUT);
 pinMode(fan,OUTPUT);
 Serial.begin(9600);
 lcd.begin(16, 2);
 lcd.setCursor(0,0);
 lcd.print(" Welcome");
 lcd.setCursor(0,2);
lcd.print("PNT2022TMID33446");
 delay(500);
 lcd.clear();
void loop(){
 // Read the value from gas sensor and button
 gasLevel = analogRead(gasPin);
 buttonState = digitalRead(buttonPin);
 // call the function for gas detection and button work
 gasDetected(gasLevel);
 buzzer(gasLevel);
 exhaustFanOn(buttonState);
// Gas Leakage Detection & Automatic Alarm and Fan ON
```

```
void gasDetected(float gasLevel){
 if(gasLevel >= 200){
 digitalWrite(buzzPin,HIGH);
 digitalWrite(ledPin,HIGH);
 digitalWrite(fan,HIGH);
 lcd.setCursor(0,0);
 lcd.print("GAS:");
 lcd.print(gasLevel);
 lcd.setCursor(0,2);
 lcd.print("FAN ON");
 delay(1000);
 lcd.clear();
 }else{
 digitalWrite(ledPin,LOW);
 digitalWrite(buzzPin,LOW);
 digitalWrite(fan,LOW);
 lcd.setCursor(0,0);
 lcd.print("GAS:");
 lcd.print(gasLevel);
 lcd.setCursor(0,2);
 lcd.print("FAN OFF");
 delay(100);
 lcd.clear();
 }
}
//BUZZER
void buzzer(float gasLevel){
if(gasLevel>=200)
 for(int i=0; i<=30; i=i+10)
 tone(4,i);
 delay(300);
 noTone(4);
 delay(4300);
 }
 }
}
// Manually Exhaust FAN ON
void exhaustFanOn(int buttonState){
 if(buttonState == HIGH){
 digitalWrite(fan,HIGH);
 lcd.setCursor(0,0);
```

```
lcd.print("Button State:");
lcd.print(buttonState);
lcd.setCursor(0,2);
lcd.print("FAN ON");
delay(10000);
lcd.clear();
}
```

OUTPUT:

