

SMART FARMER-IOT ENABLED SMART FARMING APPLICATION

SPRINT – 4

Date: 19-11-2022

Team ID: PNT2022TMID34083

Project Name: Smart Farmer-IoT Enabled Smart Farming Application

Receiving commands from IBM cloud using Python program :

```
import time

import sys

import ibmiotf.application

import ibmiotf.device

import random

#Provide your IBM Watson Device Credentials
"orgId": "ck2tfo",

"typeId": "NodeMLIC",

"deviceId": "1234"

"token" : "87654321"

# Initialize GPIO

def myCommandCallback(cmd):      print("Command
received: %s" % cmd.data['command'])

status=cmd.data['command']      if status=="motoron": print
("motor is on")      elif status == "motoroff":      print
("motor is off")      else :

    print ("please send proper command")

try:

    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken} deviceCli
= ibmiotf.device.Client(deviceOptions)
```

```

#.....

except Exception as e: print("Caught exception
connecting device: %s" % str(e))sys.exit()

# Connect and send a datapoint "hello" with value "world" into the cloud as an event
of type "greeting" 10 times deviceCli.connect()

while True:

    #Get Sensor Data from DHT11
    temp=random.randint(90,110)
    Humid=random.randint(60,100)
    Mois=random. Randint(20,120)

    data = { 'temp' : temp, 'Humid': Humid ,
'Mois': Mois}

    #print data    def myOnPublishCallback(
):

        print ("Published Temperature = %s C" % temp, "Humidity = %s %% "
%Humid, "Moisture =%s deg c" % Mois "to IBM Watson")

        success = deviceCli.publishEvent("IoTSensor", "json", data,
qos=0,on_publish=myOnPublishCallback)    if not success:
            print("Not connected to IoTF")
time.sleep(10)

    deviceCli.commandCallback = myCommandCallback #
Disconnect the device and application from the cloud
deviceCli.disconnect()

```

```

File Edit Format Run Options Window Help
import time
import sys
import ibmio.application
import ibmiotf.device
import random

#provide your IBM Watson Device Credentials
organization = "ck2tfo"
deviceType = "NodeMLIC"
deviceID = "1234"
authMethod = "token"
authToken = "87654321"

#Initialize GPIO
def myCommandCallback(cmd):
    print("message received from IBM Iot Platform: %s" %cmd.data['command'])
    m=cmd.data['command']
    if(m=="motoron"):
        print("motor is switched on")
    elif(m=="motoroff"):
        print("motor is switched OFF")
    else :
        print("please send proper command")
try :
    deviceoptions = ("org": organization,"type":deviceType,"id":deviceId,"auth-method":authme
    devicecli = ibmiotf.device.client(deviceoptions)
#.....
while True:


```

```

Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson

```

Flow Chart



Observations & Results

```
Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```

Screen3

Smart Agriculture

Temperature 60


Humidity 95

Moisture 90

MOTOR ON

MOTOR OFF





Advantages & Disadvantages Advantages:

- Farms can be monitored and controlled remotely.
- Increase in convenience to farmers.
- Less labor cost.
- Better standards of living.

Disadvantages:

- Lack of internet/connectivity issues.
- Added cost of internet and internet gateway infrastructure.
- Farmers wanted to adapt the use of Mobile App.

Conclusion

Thus the objective of the project to implement an IOT system in order to help farmers to control and monitor their farms has been implemented successfully.