
IBM – Nalaiya Thiran Assignment 1 SMART HOME

Submitted by
Deepa Shree .S
960219104038

CIRCUIT DIAGRAM



SOURCE CODE

```
// C++ code
int t=2;
int e=3;
void setup()
 Serial.begin(9600);
pinMode(t,OUTPUT);
pinMode(e,INPUT);
pinMode(12,OUTPUT);
void loop()
//ultrasonic sensor
digitalWrite(t,LOW);
digitalWrite(t,HIGH);
delayMicroseconds(10);
digitalWrite(t,LOW);
float dur=pulseIn(e,HIGH);
float dis=(dur*0.0343)/2;
Serial.print("Distance is: ");
Serial.println(dis);
//LED ON
if(dis > = 100)
digitalWrite(8,HIGH);
```

```
digitalWrite(7,HIGH);
}
//Buzzer for ultrasonic Sensor
if(dis>=100)
for(int i=0; i<=30000; i=i+10)
tone(12,i);
delay(1000);
noTone(12);
delay(1000);
}
}
//Temperate Sensor
double a= analogRead(A0);
double t=(((a/1024)*5)-0.5)*100;
Serial.print("Temp Value: ");
Serial.println(t);
delay(1000);
//LED ON
if(t>=100)
digitalWrite(8,HIGH);
digitalWrite(7,HIGH);
```

```
//Buzzer for Temperature Sensor
if(t>=100)
for(int i=0; i<=30000; i=i+10)
tone(12,i);
delay(1000);
noTone(12);
delay(1000);
}
//LED OFF
if(t<100)
digitalWrite(8,LOW);
digitalWrite(7,LOW);
}
}
```

TINKERCAD LINK

 $\underline{https://www.tinkercad.com/things/1q4wk9dyCGW-super-snicket-}\\ \underline{migelo/editel}$

OUTPUT

Distance is: 98.61 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.44 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.42 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.39 Temp Value: -49.51 Distance is: 98.42 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.42 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 98.61 Temp Value: -49.51 Distance is: 109.86 Distance is: 85.90 Temp Value: -49.51 Distance is: 85.90 Temp Value: -49.51 Distance is: 86.09 Temp Value: -49.51 Distance is: 85.87 Tomp Value: 40 E4

