PROJECT DEVELOPMENT-DELIVERY OF SPRINT-2

DATE	17 NOVEMBER 2022
TEAM ID	PNT2022TMID34030
PROJECT NAME	Smart Waste Management for Metropolitian Cities

Code for Data Transfer from Sensors

```
#include <WiFi.h>                    //library for wifi
#include <PubSubClient.h>            //library for MQTT
#include <LiquidCrystal_I2C.h> LiquidCrystal_I2C
lcd(0x27, 20, 4);

//        credentials of IBM Accounts_____.

#define ORG "ktymlx"                 //IBM organisation id
#define DEVICE_TYPE "new"            // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "09876"            // Device ID mentioned in ibm watson iot platform
#define TOKEN "Kamesh@2002"   // Token

//     customise above value_____.

char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name char publishTopic[] = "iot-2/evt/data/fmt/json"; char
topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings char authMethod[] = "usetokenauth"; // authentication method char token[] = TOKEN;
```

```
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;    //Client id

//_____________________________________________________________

WiFiClient wifiClient;                          // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);

#define ECHO_PIN 12
#define TRIG_PIN 13 float
dist;

void setup()
{
Serial.begin(115200);
pinMode(LED_BUILTIN, OUTPUT);
pinMode(TRIG_PIN, OUTPUT);
pinMode(ECHO_PIN, INPUT);
//pir pin pinMode(4, INPUT);

//ledpins pinMode(23,
OUTPUT); pinMode(2,
OUTPUT); pinMode(4,
OUTPUT); pinMode(15,
OUTPUT);
lcd.init(); lcd.backlight(); lcd.setCursor(1,
0); lcd.print(""); wifiConnect();
mqttConnect(); }
```

```
float readcmCM()
{
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2); digitalWrite(TRIG_PIN,
HIGH); delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW); int duration =
pulseIn(ECHO_PIN, HIGH); return
duration * 0.034 / 2;
}
void loop()
{
lcd.clear();
publishData(); delay(500);
if (!client.loop())
{
mqttConnect();                          //function call to connect to IBM
}
}
/*_____retrieving to cloud_____*/
void wifiConnect()
{
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
{
delay(500);
```

```
Serial.print(".");
}
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
}
void mqttConnect()
{
if (!client.connected())
{
Serial.print("Reconnecting MQTT client to ");
Serial.println(server); while
(!client.connect(clientId, authMethod, token))
{
Serial.print("."); delay(500);
}
initManagedDevice(); Serial.println();
}
}
void initManagedDevice()
{
if (client.subscribe(topic))
{
Serial.println("IBM subscribe to cmd OK");
}
else
{
Serial.println("subscribe to cmd FAILED");
```

```
}
}
void publishData()
{
float cm = readcmCM();
if(digitalRead(34))                    //PIR motion detection
{
Serial.println("Motion
Detected"); Serial.println("Lid
Opened"); digitalWrite(15, HIGH);
}
else
{
digitalWrite(15, LOW);
}
if(digitalRead(34)== true)
{
if(cm <= 100)                          //Bin level detection
{
digitalWrite(2, HIGH);
Serial.println("High Alert!!!,Trash bin is about to be full");
Serial.println("Lid Closed"); lcd.print("Full! Don't use"); delay(2000);
lcd.clear(); digitalWrite(4, LOW);
digitalWrite(23, LOW);
}
else if(cm > 150 && cm < 250)
{
```

```
digitalWrite(4, HIGH);
Serial.println("Warning!!,Trash is about to cross 50% of bin level");
digitalWrite(2,
LOW);
digitalWrite(23, LOW);
}
else if(cm > 250 && cm <=400)
{
digitalWrite(23, HIGH); Serial.println("Bin is
available"); digitalWrite(2,LOW);
digitalWrite(4, LOW);
}
delay(10000); Serial.println("Lid Closed");
}
else
{
Serial.println("No motion detected");
}
if(cm <= 100)
{
digitalWrite(21,HIGH);
String payload = "{\"High Alert!!\":\"";
payload += cm; payload
+= "left\" }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload); if (client.publish(publishTopic, (char*) payload.c_str()))
// if data is uploaded to cloud successfully,prints publish
```

```
ok or prints publish failed
{
Serial.println("Publish OK");
}
}
if(cm <= 250)
{
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: "); Serial.println(cm);
if(client.publish(publishTopic,
(char*) payload.c_str()))
{
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}
float inches = (cm / 2.54); //print on LCD lcd.setCursor(0,0);
lcd.print("Inches"); lcd.setCursor(4,0);
lcd.setCursor(12,0); lcd.print("cm"); lcd.setCursor(1,1); lcd.print(inches, 1);
lcd.setCursor(11,1);
lcd.print(cm, 1); lcd.setCursor(14,1); delay(1000); lcd.clear();
}
```

Connection Diagram: