Assignment -4

| Assignment Date | 01 November 2022 |
|---------------------|------------------|
| Student Name | Vigneshkumar S |
| Student Roll Number | 611219106096 |
| Maximum Marks | 2 Marks |

Question:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events. Upload document with wokwi share link and images of ibm cloud.

Solution:

Wokwi link: https://wokwi.com/projects/347030404430037586

Code:

```
#include <WiFi.h>
#include <WiFiClient.h>
#include < PubSubClient.h >
const int trigPin = 5;
const int echoPin = 18;
//define sound speed in cm/uS
#define SOUND_SPEED 0.034
#define CM_TO_INCH 0.393701
long duration;
float distanceCm;
float distanceInch;
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
```


```
#define ORG "ixvk0i"//IBM ORGANITION ID
#define DEVICE_TYPE "Vigneshkumar"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "vignesh123"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "W(!wo(hn9?grLU(gRG" //Token
String data3;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format
in which data to be send
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient);
void setup() {
 Serial.begin(115200); // Starts the serial communication
 pinMode(trigPin, OUTPUT); // Sets the trigPin as an Output
 pinMode(echoPin, INPUT); // Sets the echoPin as an Input
 Serial.println();
 wificonnect();
 mqttconnect();
}
void loop() {
// Clears the trigPin
 digitalWrite(trigPin, LOW);
```

```
delayMicroseconds(2);
 // Sets the trigPin on HIGH state for 10 micro seconds
 digitalWrite(trigPin, HIGH);
 delayMicroseconds(10);
 digitalWrite(trigPin, LOW);
 // Reads the echoPin, returns the sound wave travel time in microseconds
 duration = pulseIn(echoPin, HIGH);
 // Calculate the distance
 distanceCm = duration * SOUND_SPEED/2;
 // Convert to inches
 distanceInch = distanceCm * CM_TO_INCH;
 // Prints the distance in the Serial Monitor
 Serial.print("Distance (cm): ");
 Serial.println(distanceCm);
 Serial.print("Distance (inch): ");
 Serial.println(distanceInch);
 PublishData(distanceCm);
 delay(1000);
 if (!client.loop()) {
  mqttconnect();
 }
}
 void PublishData(float Cm) {
 mqttconnect();//function call for connecting to ibm
```

```
creating the String in in form JSon to update the data to ibm cloud
 */
 String payload = "{\"Distance (cm)\":";
 payload += Cm;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok in
Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
 }
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
   delay(500);
  }
   initManagedDevice();
   Serial.println();
 }
```

```
}
void wificonnect() //function defination for wificonnect
{
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
 }
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else
 {
  Serial.println("subscribe to cmd FAILED");
 }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
```

```
for (int i = 0; i < payloadLength; i++) {
    //Serial.print((char)payload[i]);
    data3 += (char)payload[i];
}</pre>
```



Images of IBM cloud:

