

ASSIGNMENT -4

ProblemStatement:-SMSSPAMClassification

AssignmentDate	26October2022
StudentName	ARUNKUMAR.S
StudentRegNumber	4206191040009
MaximumMarks	2Marks

1. Download the Data set:- Data set

<https://www.kaggle.com/code/kredy10/simple-lstm-for-text-classification/data>

The files contain one message per line. Each line is composed by two columns: v1 contains the label (ham or spam) and v2 contains the raw text.

▲ v1		▲ v2		▲		▲	
class		sms					
ham	87%	5169 unique values	[null]	99%	[null]	100%	
spam	13%		bt not his girlfrnd... ...	0%	MK17 92H. 450Ppw...	0%	
			Other (47)	1%	Other (10)	0%	

[illegible]

2.Importrequiredlibrary

Import the necessary libraries

```
[1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
%matplotlib inline
```

3.Readdatasetand dopre-processing

```
In [2]: df = pd.read_csv("spam.csv", encoding='latin-1')
df.head()
```

Out[2]:

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only in	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

The Columns 2,3,4 will be dropped as they contain no relevant information

```
In [3]: data = df.copy()
data.drop(columns=["Unnamed: 2", "Unnamed: 3", "Unnamed: 4"], inplace=True)
data = data.rename(columns={"v1": "label", "v2": "text"})
```

In [4]: data.head()

Out[4]:

	label	text
0	ham	Go until jurong point, crazy.. Available only in
1	ham	Ok lar... Joking wif u oni...
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...
3	ham	U dun say so early hor... U c already then say...

Preproceesing:

```
In [17]: from tensorflow.keras.preprocessing.sequence import pad_sequences
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
from tensorflow.keras.layers import Dropout
from tensorflow.keras.layers import Flatten
from tensorflow.keras.layers import Embedding
from tensorflow.keras.callbacks import EarlyStopping

In [18]: # prepare tokenizer
t = Tokenizer()
t.fit_on_texts(X_train)

# integer encode the documents
encoded_train = t.texts_to_sequences(X_train)
encoded_test = t.texts_to_sequences(X_test)

vocab_size = len(t.word_index) + 1

print(encoded_train[0:2])

[[38, 30, 8, 5, 273, 1989, 81, 116, 26, 11, 1656, 322, 10, 53, 18, 299, 30, 349, 1990], [799, 15, 2555, 1442, 1127, 192, 2556, 171, 12, 98, 1991, 44, 195, 1657, 2557, 1992, 2558, 21, 9, 4, 203, 1025, 225]]
```

4. CreateModel

```
In [7]: data['label'] = data['label'].map( {'spam': 1, 'ham': 0} )
data.head()
```

```
Out[7]:
```

	label	text
0	0	Go until jurong point, crazy.. Available only ...
1	0	Ok lar... Joking wif u oni...
2	1	Free entry in 2 a wkly comp to win FA Cup fina...
3	0	U dun say so early hor... U c already then say...
4	0	Nah I don't think he goes to usf, he lives aro...

```
In [8]: data_ham = data[data['label'] == 0].copy()
data_spam = data[data['label'] == 1].copy()
```

WordClouds

WordClouds


```
In [9]: def show_wordcloud(df, title):
    text = ' '.join(df['text'].astype(str).tolist())
    stopwords = set(wordcloud.STOPWORDS)

    fig_wordcloud = wordcloud.WordCloud(stopwords=stopwords, background_color='lightgrey',
                                         colormap='viridis', width=800, height=600).generate(text)

    plt.figure(figsize=(10,7), frameon=True)
    plt.imshow(fig_wordcloud)
    plt.axis('off')
    plt.title(title, fontsize=20 )
    plt.savefig("wd.png")
    plt.show()
```

WordCloud: Ham messages

```
In [10]: show_wordcloud(data_ham, "Ham messages")
```



WordCloud: Spam messages

```
In [11]: show_wordcloud(data_spam, "Spam messages")
```



5. Add Layers (LSTM, Dense-(Hidden Layers), Output)

6. Compile the Model

```
In [19]: # pad documents to a max length of 4 words
max_length = 8
padded_train = pad_sequences(encoded_train, maxlen=max_length, padding='post')
padded_test = pad_sequences(encoded_test, maxlen=max_length, padding='post')

print(padded_train)

[[ 322  10  53 ...  30 349 1990]
 [1992 2558  21 ... 203 1025 225]
 [ 83 1443  4 ...  2 3794 3795]
 ...
 [1477  30 2063 ... 239  30 2064]
 [ 763 1679 1161 ...  0  0  0]
 [  8 155  20 ...  8 290 175]]
```

```
In [20]: # define the model
model = Sequential()
model.add(Embedding(vocab_size, 24, input_length=max_length))
model.add(Flatten())
model.add(Dense(500, activation='relu'))
model.add(Dense(200, activation='relu'))
model.add(Dropout(0.5))
model.add(Dense(100, activation='relu'))
model.add(Dense(1, activation='sigmoid'))

# compile the model
model.compile(optimizer='rmsprop', loss='binary_crossentropy', metrics=['accuracy'])

# summarize the model
print(model.summary())
```

Model: "sequential_1"

Layer (type)	Output Shape	Param #
embedding_1 (Embedding)	(None, 8, 24)	190920
flatten_1 (Flatten)	(None, 192)	0
dense_2 (Dense)	(None, 500)	96500
dense_3 (Dense)	(None, 200)	100200
dropout (Dropout)	(None, 200)	0
dense_4 (Dense)	(None, 100)	20100
dense_5 (Dense)	(None, 1)	101
Total params: 407,821		
Trainable params: 407,821		
Non-trainable params: 0		

None

7. Fit the Model

```
In [21]: early_stop = EarlyStopping(monitor='val_loss', mode='min', verbose=1, patience=10)

# fit the model
model.fit(x=padded_train,
          y=y_train,
          epochs=50,
          validation_data=(padded_test, y_test), verbose=1,
          callbacks=[early_stop]
        )

Epoch 1/50
140/140 [=====] - 1s 4ms/step - loss: 0.2034 - accuracy: 0.9195 - val_loss: 0.1061 - val_accuracy: 0.9758
Epoch 2/50
140/140 [=====] - 0s 3ms/step - loss: 0.0447 - accuracy: 0.9865 - val_loss: 0.0840 - val_accuracy: 0.9821
Epoch 3/50
140/140 [=====] - 0s 3ms/step - loss: 0.0136 - accuracy: 0.9969 - val_loss: 0.0997 - val_accuracy: 0.9839
Epoch 4/50
140/140 [=====] - 0s 3ms/step - loss: 6.0631e-04 - accuracy: 0.9998 - val_loss: 0.2119 - val_accuracy: 0.9830
Epoch 5/50
140/140 [=====] - 0s 3ms/step - loss: 1.2411e-06 - accuracy: 1.0000 - val_loss: 0.2899 - val_accuracy: 0.9803
Epoch 6/50
140/140 [=====] - 0s 3ms/step - loss: 3.1918e-08 - accuracy: 1.0000 - val_loss: 0.2903 - val_accuracy: 0.9821
Epoch 7/50
140/140 [=====] - 0s 3ms/step - loss: 4.8863e-09 - accuracy: 1.0000 - val_loss: 0.2921 - val_accuracy: 0.9830
Epoch 8/50
140/140 [=====] - 0s 2ms/step - loss: 9.7544e-10 - accuracy: 1.0000 - val_loss: 0.2946 - val_accuracy: 0.9830
Epoch 9/50
140/140 [=====] - 0s 3ms/step - loss: 1.3770e-09 - accuracy: 1.0000 - val_loss: 0.3048 - val_accuracy: 0.9821
Epoch 10/50
140/140 [=====] - 0s 3ms/step - loss: 1.3219e-09 - accuracy: 1.0000 - val_loss: 0.3032 - val_accuracy: 0.9812
Epoch 11/50
140/140 [=====] - 0s 3ms/step - loss: 1.1548e-09 - accuracy: 1.0000 - val_loss: 0.3015 - val_accuracy: 0.9830
Epoch 12/50
140/140 [=====] - 0s 3ms/step - loss: 8.7392e-10 - accuracy: 1.0000 - val_loss: 0.3087 - val_accuracy: 0.9830
```

8. Save The Model

```
In [29]: model.save("spam_model")

WARNING:tensorflow:From /Users/mac/opt/anaconda3/envs/deeplearning/lib/python3.7/site-packages/tensorflow/python/training/tracking/tracking.py:111: Model.state_updates (from tensorflow.python.keras.engine.training) is deprecated and will be removed in a future version.
Instructions for updating:
This property should not be used in TensorFlow 2.0, as updates are applied automatically.
WARNING:tensorflow:From /Users/mac/opt/anaconda3/envs/deeplearning/lib/python3.7/site-packages/tensorflow/python/training/tracking/tracking.py:111: Layer.updates (from tensorflow.python.keras.engine.base_layer) is deprecated and will be removed in a future version.
Instructions for updating:
This property should not be used in TensorFlow 2.0, as updates are applied automatically.
INFO:tensorflow:Assets written to: spam_model/assets
```

```
In [30]: with open('spam_model/tokenizer.pkl', 'wb') as output:
        pickle.dump(t, output, pickle.HIGHEST_PROTOCOL)
```

9. TestTheModel

```
In [31]: s_model = tf.keras.models.load_model("spam_model")

with open('spam_model/tokenizer.pkl', 'rb') as input:
    tokenizer = pickle.load(input)

# s_model.summary()
```

```
In [38]: sms_spam = ["We know someone who you know that fancies you. Call 09058097218 to find out who. POBox 6, LS15HB "]
sms_ham = ["I'll text Tanya when I get home, hang on"]

sms_proc = tokenizer.texts_to_sequences(sms_ham)
sms_proc = pad_sequences(sms_proc, maxlen=max_length, padding='post')

pred = (model.predict(sms_proc) > 0.5).astype("int32").item()
pred
```

```
In [39]: pred = (model.predict(sms_proc) > 0.5).astype("int32").item()
pred
```

```
Out[39]: 0
```

```
In [33]: X_test[5]
```

```
Out[33]: "I'll text carlos and let you know, hang on"
```

```
Text 1:
```