#### **ASSIGNMENT 4**

## **QUESTION:**

char token[] = TOKEN;

char clientId[] = "d:" ORG ":" DEVICE\_TYPE ":" DEVICE\_ID;

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events.

# CODE: #include <WiFi.h> #include < PubSubClient.h > void callback(char\*subscribetopic, byte\* payload, unsigned int payloadLength); //----credentials of IBM Accounts-----#define ORG"Ashfaq1824"//IBM ORGANITION ID #define DEVICE\_TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform #define DEVICE\_ID "12345"//Device ID mentioned in ibm watson IOT Platform #define TOKEN "12345678" //Token String data3; char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; charpublishTopic[] = "iot-2/evt/Data/fmt/json"; charsubscribetopic[] = "iot-2/cmd/test/fmt/String"; char authMethod[] = "use-token-auth";

```
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback, wifiClient);
const int trigPin = 5;
const int echoPin = 18;
#define SOUND_SPEED 0.034
long duration;
float distance;
void setup()
Serial
.begin(115200);
pinMode(trigPin, OUTPUT);
pinMode(echoPin, INPUT);
wificonnect();
mqttconnect();
}
void loop()
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
duration = pulseIn(echoPin, HIGH);
distance = duration * SOUND_SPEED/2;
```


```
Serial
.print("Distance (cm): ");
Serial
.println(distance);
if(distance<100)
{
Serial
.println("ALERT!!");
delay(1000);
PublishData(distance);
delay(1000);
if (!client.loop())
{mqttconnect();
}
delay(1000);
}
void PublishData(float dist)
{mqttconnect();
String payload = "{\"Distance\":";
payload += dist;
payload += ",\"ALERT!!\":""\"Distance less than 100cms\"";
payload += "}";
Serial
.print("Sending payload: ");
```

```
Serial
.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())){
Serial
.println("Publish ok");
} else {
Serial
.println("Publish failed");
}
}
void mqttconnect() {
if (!client.connected())
Serial
.print("Reconnecting client to ");
Serial
.println(server);
while (!!!client.connect(clientId, authMethod, token)) {
Serial
.print(".");
delay(500);
}initManagedDevice();
Serial
.println();
}
void wificonnect()
```

```
{
Serial
.println();
Serial
.print("Connecting to ");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
{delay(500);
Serial
.print(".");
Serial
.println("");
Serial
.println("WiFi connected");
Serial
.println("IP address: ");
Serial
.println(WiFi.localIP());
}
void initManagedDevice() {
if (client.subscribe(subscribetopic))
Serial
.println((subscribetopic));
Serial
.println("subscribe to cmdOK");
} else {
```

```
Serial
.println("subscribe to cmdFAILED");
}
}
void callback(char*subscribetopic, byte*payload, unsigned int payloadLength)
{
Serial
.print("callback invoked for topic: ");
.println(subscribetopic);
for (int i = 0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);
data3+= (char)payload[i];
}
Serial
.println("data: "+ data3);
data3="";
}
```

### SCHEMATIC/CIRCUIT DIAGRAM:



### **IBM CLOUD OUTPUT:**

