Assignment -4 Internet of Things (IoT)

Assignment Date	30 October 2022
Student Name	Shakthi S P
Student Roll Number	310619106125
Maximum Marks	2 Marks

1.Write Code and connections in wokwi for ultrasonic sensor. whatever distance is less than 100 cms send "Alert" to ibm cloud aand display in device recent events.

```
Solution:
//Pins
const int TRIG_PIN = 7;
const int ECHO_PIN = 8;
//Anything over 400 cm (23200 us pulse) is "out of range" const unsigned
int MAX_DIST = 23200;
void setup() {
// The Trigger pin will tell the sensor to range findPin
Mode(TRIG_PIN, OUTPUT);
digital Write(TRIG_PIN, LOW);
//Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensorpinMode(ECHO_PIN,
INPUT);
// We'll use the serial monitor to view the sensor outputSerial.begin(9600);
}
void loop() {
```

unsigned long t1;


```
unsigned long t2;
unsigned long pulse_width;float
cm;
float inches;
// Hold the trigger pin high for at least 10 us
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10); digitalWrite(TRIG_PIN,
LOW);
// Wait for pulse on echo pin
while (digitalRead( ECHO_PIN )==0 );
// Measure how long the echo pin was held high (pulse width)
// Note: the micros() counter will overflow after-70 mint1= micros
 while (digitalRead(ECHO_PIN) == 1);t2=
 micros();
 pulse\_width = t2-t1;
// Calculate distance in centimeters and inches. The constants
//are found in the datasheet, and calculated from the assumed speed
// of sound in air at sea level (- 340m/s)
cm=pulse_Width / 58;
inches = pulse_width/148.0;
```

Output:

1. If the distance is less than 100 cms, it alerts.

```
WOKWI → SHARE ♥
   hc-sr04.ino diagram json ◆ Library Manager ▼
                                                                                                                                                                                                               ₫00:00.466 (%58%
            const int TRIG_PIN = 7;
const int ECHO_PIN = 8;
            // Anything over 400 cm (23200 us pulse) is "out of range" const unsigned int MAX_DIST = 23200;
            void setup() {
              // The Trigger pin will tell the sensor to range find
pinMode(TRIG_PIN, OUTPUT);
digitalWrite(TRIG_PIN, LOW);
                                                                                                                                                   DE TOTAL (PAR -) ES
                                                                                                                                                   OOU UNO
              //Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensor
pinMode(ECHO_PIN, INPUT);
               // We'll use the serial monitor to view the sensor output {\tt Serial.begin(9600);}
                                                                                                                                                        NEW POWER AND THE
              unsigned long t1;
unsigned long t2;
unsigned long pulse_width;
float cm;
float inches;
                                                                                                                    The Measured Distance in cm : 84.14
                                                                                                                                                                                                                    // Hold the trigger pin high for at least 10 us
```

2. If the distance is more than 100 cms, it won't alert



3. Simulation and code execution

