

# Project Development Phase

## SPRINT DELIVERY – 4

Team ID	PNT2022TMID34687
Project Name	Smart Farmer-IoT Enabled Smart Farming Application
Date	16 November 2022

### 5.5 Receiving commands from IBM cloud using Python program

```
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random
```

#### #Provide your IBM Watson Device Credentials

```
organization = "157uf3" deviceType = "abcd"
deviceId = "7654321" authMethod = "token"
authToken = "87654321"
```

## # Initialize GPIO

```
def myCommandCallback(cmd):    print("Command
received: %s" % cmd.data['command'])
status=cmd.data['command']    if status=="motoron":
print ("motor is on")        elif status == "motoroff": print
("motor is off")    else : print ("please send proper
command")

try:

    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method":  authMethod,  "auth-token":  authToken}
deviceCli = ibmiotf.device.Client(deviceOptions)

    #.....

except Exception as e:

    print("Caught exception connecting device: %s" % str(e))

sys.exit()

# Connect and send a datapoint "hello" with value "world" into the cloud as an
event of type "greeting" 10 times deviceCli.connect()

while True:

    #Get      Sensor      Data      from      DHT11
temp=random.randint(90,110)
Humid=random.randint(60,100)
```

```

Mois=random. Randint(20,120) data = {
    'temp' : temp, 'Humid': Humid ,
    'Mois': Mois}

    #print data    def myOnPublishCallback():

        print ("Published Temperature = %s C" % temp, "Humidity = %s %" %
Humid, "Moisture =%s deg c" % Mois "to IBM Watson")

        success = deviceCli.publishEvent("IoTSensor", "json", data, qos=0,
on_publish=myOnPublishCallback)    if not success:
            print("Not connected to IoT")

time.sleep(10)    deviceCli.commandCallback    =
myCommandCallback # Disconnect the device and
application from the cloud
deviceCli.disconnect()

```

```
ibmiotpublishsubscribe.py - C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py (3.7.0)
File Edit Format Run Options Window Help

import time
import sys
import ibmiotf.application
import ibmiotf.device
import random


#Provide your IBM Watson Device Credentials
organization = "157uf3"
deviceType = "abcd"
deviceId = "7654321"
authMethod = "token"
authToken = "87654321"

# Initialize GPIO
def myCommandCallback(cmd):
    print("Command received: %s" % cmd.data['command'])
    status=cmd.data['command']
    if status=="motoron":
        print ("motor is on")
    elif status == "motoroff":
        print ("motor is off")
    else :
        print ("please send proper command")

try:
    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth-method": authMe
    deviceCli = ibmiotf.device.Client(deviceOptions)
    #.....
Ln 22 Col 21
```

```
Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```

## 6.Flow Chart



## 7.Observations & Results

```
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```



## Measured Data

Moisture : 59

Temperature(c): 90

Humidity(%): 85

## Switchboard


Motor on

Motor off



FARMING MEASURE DATA

Farming Measure Data



Switchboard

MOTOR SWITCH ON

MOTOR SWITCH OFF

## 8. Advantages & Disadvantages Advantages:

- Farms can be monitored and controlled remotely.
- Increase in convenience to farmers.
- Less labor cost.
- Better standards of living.

## Disadvantages:

- Lack of internet/connectivity issues.
- Added cost of internet and internet gateway infrastructure.
- Farmers wanted to adapt the use of Mobile App.

## 9. Conclusion

Thus the objective of the project to implement an IOT system in order to help farmers to control and monitor their farms has been implemented successfully.