#### Assignment -4

## **SMS SPAM Classification**

### Question-1:

Download the dataset

#### Question-2:

Import required library

#### **Solution**

import nltk import pandas as pd import re

from nltk.corpus import stopwords from nltk.stem.porter import PorterStemmer

 $from \, sklearn. feature\_extraction. text \, import \, Count Vectorizer$ 

from sklearn.model\_selection import train\_test\_split

from tensorflow.keras.models import Sequential from tensorflow.keras.layers import Dense



## Question-3:

Read dataset and do pre-processing

# Solution

data=pd.read\_csv('/content/drive/MyDrive/assignment 4/spam.csv',encoding='latin')

```
nltk.download('stopwords')
ps=PorterStemmer()
input=[]
for i in range(0,5572):
 review=data['v2'][i]
 review=re.sub('[^a-zA-Z]',' ',review)
 review=review.lower()
 review=review.split()
 review=[ps.stem(word) for word in review if not word in set(stopwords.words('english'))]
 review=' '.join(review)
 input.append(review)
 cv=CountVectorizer(max features=7000)
x=cv.fit_transform(input).toarray()
y=data['v1'].values
x_train,x_test,y_train,y_test= train_test_split(x,y,test_size=0.2)
  Read dataset
  [ ] data=pd.read_csv('/content/drive/MyDrive/assignment 4/spam.csv',encoding='latin')
  Preprocessing
  [ ] nltk.download('stopwords')
       [nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Package stopwords is already up-to-date!
  [ ] ps=PorterStemmer()
   input=[]
  [] for i in range(0,5572):
review=data['v2'][i]
review=re.sub('[^a-zA-Z]',' ',review)
review=review.lower()
review=review.split()
         review=[ps.stem(word) for word in review if not word in set(stopwords.words('english'))] review=' '.join(review) input.annend(review)

    Os completed at 8:54 PM

   [ ] cv=CountVectorizer(max_features=7000)
   [ ] x=cv.fit_transform(input).toarray()
       array([[0, 0, 0, ..., 0, 0, 0], [0, 0, 0, ..., 0, 0, 0], [0, 0, 0, ..., 0, 0, 0],
  [ ] y=data['v1'].values
       array(['ham', 'ham', 'spam', ..., 'ham', 'ham', 'ham'], dtype=object)
                                                                                                                                 1 V 🗢 🗖 🛊 🖟 🔋 :
   x.shape
       (5572, 6221)
  [ ] x_train,x_test,y_train,y_test= train_test_split(x,y,test_size=0.2)
```

## Question-4:

Create Model

#### Solution

model=Sequential()

### Question-5:

Add Layers (LSTM, Dense-(Hidden Layers), Output)

#### **Solution**

model.add(Dense(units=6221,activation='relu')) model.add(Dense(units=7000,activation='relu')) model.add(Dense(units=1,activation='sigmoid'))



## Question-6:

Compile The Model

### **Solution**

model.compile(optimizer='adam',loss='binary\_crossentropy',metrics=['accuracy'])




## Question-7:

Fit The Model

## **Solution**

model.fit(x\_train,y\_train,epochs=5)



## Solution

model.save("Flowers.h5")

Fit the model

[ ] model.save('spam.h5')