

ASSIGNMENT 4

PNT2022TMID38188

SUBMITTED BY SHARMILA.B

Ultrasonic sensor simulation in Wokwi

Question :

Write a code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100cms send an "Alert" to IBM cloud and display in the device recent events.

Code:

```
#include <WiFi.h> #include <PubSubClient.h> void callback(char*
subscribetopic, byte* payload, unsigned int payloadLength);
//-----credentials of IBM Accounts-----
#define ORG "kotoq5"//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "12345"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678" //Token String data3; char server[] = ORG
    ".messaging.internetofthings.ibmcloud.com";      char
publishTopic[] =      "iot-2/evt/Data/fmt/json";      char
subscribetopic[]      =      "iot-2/cmd/test/fmt/String";      char
authMethod[] = "use-token-auth";
```

```
char token[] = TOKEN; char clientId[] = "d:" ORG ":"  
DEVICE_TYPE ":" DEVICE_ID;  
WiFiClient wifiClient;  
PubSubClient client(server, 1883, callback ,wifiClient);  
const int trigPin = 5; const int echoPin = 18; #define  
SOUND_SPEED 0.034 long duration; float distance; void  
setup() { Serial.begin(115200); pinMode(trigPin,  
OUTPUT); pinMode(echoPin, INPUT); wificonnect();  
mqttconnect(); } void loop() { digitalWrite(trigPin,  
LOW); delayMicroseconds(2); digitalWrite(trigPin,  
HIGH); delayMicroseconds(10); digitalWrite(trigPin,  
LOW); duration = pulseIn(echoPin, HIGH); distance =  
duration * SOUND_SPEED/2; Serial.print("Distance (cm):  
"); Serial.println(distance); if(distance<100)  
{  
Serial.println("ALERT!!");  
delay(1000);
```

```

PublishData(distance)
; delay(1000); if
(!client.loop()) {
mqttconnect(); } }
delay(1000); } void
PublishData(float dist)
{ mqttconnect();
String payload = "{\"Distance\":\""; payload += dist; payload
+= ", \"ALERT!!\":\"\"Distance less than 100cms\""; payload
+= "}";
Serial.print("Sending          payload:          ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial.println("Publish ok");
} else {
Serial.println("Publish failed");
} } void mqttconnect() { if
(!client.connected()) {
Serial.print("Reconnecting      client      to      ");
Serial.println(server); while
(!!!client.connect(clientId, authMethod, token)) {
Serial.print("."); delay(500);
}
}
initManagedDevice();
Serial.println();
} } void
wificonnect()
{
Serial.println(); Serial.print("Connecting to ");
WiFi.begin("Wokwi-GUEST", "", 6); while (WiFi.status() !=
WL_CONNECTED) { delay(500);
Serial.print(".");
}
Serial.println(""); Serial.println("WiFi connected"); Serial.println("IP
address: "); Serial.println(WiFi.localIP());
} void initManagedDevice() {
if

```

```

(client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic)); Serial.println("subscribe to
  cmd OK");
} else {
  Serial.println("subscribe to cmd FAILED");
} } void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength) {
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic); for (int i =
0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]); data3 +=
(char)payload[i];
  }
  Serial.println("data: "+ data3);
  data3="";
}

```

Diagram.json:

```

{
  "version": 1,
  "author": "sweetysharon",
  "editor": "wokwi",
  "parts": [
    { "type": "wokwi-esp32-devkit-v1", "id": "esp", "top": -4.67, "left": -114.67, "attrs": {}
    },
    { "type": "wokwi-hc-sr04", "id": "ultrasonic1", "top": 15.96, "left": 89.17, "attrs": {} }
  ],
  "connections": [
    [ "esp:TX0", "$serialMonitor:RX", "", [] ],
    [ "esp:RX0", "$serialMonitor:TX", "", [] ],
    [
      "esp:VIN",
      "ultrasonic1:VCC",
      "red",

```

```

    [ "h-37.16", "v-178.79", "h200", "v173.33", "h100.67" ] ],
  [ "esp:GND.1", "ultrasonic1:GND", "black", [ "h39.87", "v44.04", "h170" ] ],
  [ "esp:D5", "ultrasonic1:TRIG", "green", [ "h54.54", "v85.07", "h130.67" ] ],
  [ "esp:D18", "ultrasonic1:ECHO", "green", [ "h77.87", "v80.01", "h110" ] ]


}

```

Wokwi simulation link:

<https://wokwi.com/projects/346508314441417298>

Circuit Diagram:



Output:

Wokwi output:

```
Connecting to ....
WiFi connected
IP address:
10.10.0.2
Reconnecting client to ytluse.messaging.internetofthings.ibmcloud.com
iot-2/cmd/test/fmt/String
subscribe to cmd OK

Distance (cm): 399.92
Distance (cm): 399.96
Distance (cm): 399.94
Distance (cm): 399.98
Distance (cm): 399.94
Distance (cm): 399.92
Distance (cm): 399.94
```

IBM cloud output:

The screenshot shows the IBM Cloud IoT Platform console. On the left is a dark sidebar with icons for various functions. The main area has a top navigation bar with tabs: 'Browse', 'Action', 'Device Types', and 'Interfaces'. To the right of these tabs is a blue button labeled 'Add Device' with a plus icon. Below the navigation bar, there's a sub-navigation bar with tabs: 'Identity', 'Device Information', 'Recent Events' (which is selected), 'State', and 'Logs'. A close button 'X' is on the far right of this sub-bar. The main content area under 'Recent Events' contains a text description: 'The recent events listed show the live stream of data that is coming and going from this device.' Below this is a table with four columns: 'Event', 'Value', 'Format', and 'Last Received'. The table contains four rows of data, all with 'event_1' in the 'Event' column and 'json' in the 'Format' column. The 'Value' column contains JSON objects with 'distance' and 'Alert' fields. The 'Last Received' column shows 'a few seconds ago' for each entry.

Event	Value	Format	Last Received
event_1	{"distance":7,"Alert":"Distance less than 10"}	json	a few seconds ago
event_1	{"distance":9,"Alert":"Distance less than 10"}	json	a few seconds ago
event_1	{"distance":8,"Alert":"Distance less than 10"}	json	a few seconds ago
event_1	{"distance":9,"Alert":"Distance less than 10"}	json	a few seconds ago