

PROJECT DEVELOPMENT PHASE

DELIVERY OF SPRINT-1

DATE	29 OCTOBER 2022
TEAM ID	PNT2022TMID43633
PROJECT NAME	Car Resale Value Prediction
MAXIMUM MARK	4 Marks

Import library and load dataset in python

```
In [1]: import pandas as pd
import numpy as np
import matplotlib as plt
from sklearn. preprocessing import LabelEncoder
import pickle
```

```
In [2]: df = pd.read_csv("D:\IBM Dataset\autos.csv",header=0,sep=',',encoding='Latin1',
```

Cleaning the Dataset

```
In [3]: df[df.seller != 'gewerblich']
df=df.drop( 'seller', 1)
df[df.offerType != 'Gesuch']
df=df.drop( 'offerType', 1)

C:\Users\arun\AppData\Local\Temp\ipykernel_10288\858333111.py:2: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only
  df=df.drop( 'seller', 1)
C:\Users\arun\AppData\Local\Temp\ipykernel_10288\858333111.py:4: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only
  df=df.drop( 'offerType', 1)

In [4]: df = df[ (df.powerPS > 50) & (df.powerPS < 900) ]
df = df[ (df.yearOfRegistration >= 1950) & (df.yearOfRegistration < 2017)]

In [5]: df.drop(['name', 'abtest', 'dateCrawled', 'nrOfPictures', 'lastSeen', 'postalCode', 'dateCreated'],axis='columns',inplace=True)

In [6]: new_df = df.copy()
new_df = new_df.drop_duplicates(['price', 'vehicleType', 'yearOfRegistration', 'gearbox', 'powerPS', 'model', 'kilometer', 'monthOfRegistration', 'fuelType', 'notRepairedDamage'])

In [7]: new_df.gearbox.replace(('manuell', 'automatik'),('manual', 'automatic'),inplace=True)
new_df.fuelType.replace(('benzin', 'andere', 'elektro'),('petrol', 'others', 'electirc'),inplace=True)
new_df.vehicleType.replace(('kleinwagen', 'cabrio', 'kombi', 'andere'),('small car', 'convertible', 'combination', 'others'),inplace=True)
new_df.notRepairedDamage.replace(('ja', 'nein'),('Yes', 'No'),inplace=True)
```

Removing the outliers and filling NaN values using the fillna() function

```
In [8]: new_df = new_df[(new_df.price >= 100) & (new_df.price <= 150000)]
```

```
In [9]: new_df['notRepairedDamage'].fillna(value='not-declared',inplace=True)
new_df['fuelType'].fillna(value='not-declared',inplace=True)
new_df['gearbox'].fillna(value='not-declared',inplace=True)
new_df['vehicleType'].fillna(value='not-declared',inplace=True)
new_df['model'].fillna(value='not-declared',inplace=True)
```

```
In [23]: new_df.to_csv("autos_preprocessed.csv")
```