

FOR BODY DAMAGE

IMAGE PRE PROCESSING

1. Import The ImageDataGenerator Library

```
from tensorflow.keras.preprocessing.image import ImageDataGenerator
```

:2. Configure ImageDataGenerator Class

Image Data Augmentation

```
train_datagen = ImageDataGenerator(rescale = 1./255,  
                                   shear_range = 0.1,  
                                   zoom_range = 0.1,  
                                   horizontal_flip = True)
```

```
test_datagen = ImageDataGenerator(rescale = 1./255)
```

3. Apply ImageDataGenerator Functionality To Trainset And Testset

```
training_set =  
train_datagen.flow_from_directory('/content/drive/MyDrive/IBM -  
PROJECT/Data set/body-20221023T072112Z-001/body/training',  
                                target_size = (224,  
224),  
                                batch_size = 10,  
                                class_mode =  
'categorical')  
test_set =  
test_datagen.flow_from_directory('/content/drive/MyDrive/IBM -  
PROJECT/Data set/body-20221023T072112Z-001/body/validation',  
                                target_size = (224, 224),  
                                batch_size = 10,  
                                class_mode =  
'categorical')
```

Found 979 images belonging to 3 classes.

Found 171 images belonging to 3 classes.

MODEL BUILDING

1. Importing The Model Building Libraries

```
import tensorflow as tf  
from tensorflow.keras.layers import Input, Lambda, Dense, Flatten  
from tensorflow.keras.models import Model  
from tensorflow.keras.applications.vgg16 import VGG16  
from tensorflow.keras.applications.vgg19 import VGG19  
from tensorflow.keras.preprocessing import image  
from tensorflow.keras.preprocessing.image import  
ImageDataGenerator, load_img
```

```
from tensorflow.keras.models import Sequential
import numpy as np
from glob import glob
```

2. Loading The Model

```
IMAGE_SIZE = [224, 224]
```

```
train_path = '/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/training'
valid_path = '/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/validation'
```

```
vgg16 = VGG16(input_shape=IMAGE_SIZE + [3], weights='imagenet',
include_top=False)
```

Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/vgg16/vgg16_weights_tf_dim_ordering_tf_kernels_notop.h5
58889256/58889256 [=====] - 0s 0us/step

3. Adding Flatten Layer

```
for layer in vgg16.layers:
    layer.trainable = False
```

```
folders = glob('/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/training/*')
```

```
folders
```

```
['/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/training/02-side',
 '/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/training/01-rear',
 '/content/drive/MyDrive/IBM - PROJECT/Data set/body-20221023T072112Z-001/body/training/00-front']
```

```
x = Flatten()(vgg16.output)
```

```
len(folders)
```

```
3
```

4. Adding Output Layer

```
prediction = Dense(len(folders), activation='softmax')(x)
```

5. Creating A Model Object

```
model = Model(inputs=vgg16.input, outputs=prediction)
```

```
model.summary()
```

```
Model: "model"
```

Layer (type)	Output Shape	Param #
input_1 (InputLayer)	[(None, 224, 224, 3)]	0
block1_conv1 (Conv2D)	(None, 224, 224, 64)	1792
block1_conv2 (Conv2D)	(None, 224, 224, 64)	36928
block1_pool (MaxPooling2D)	(None, 112, 112, 64)	0
block2_conv1 (Conv2D)	(None, 112, 112, 128)	73856
block2_conv2 (Conv2D)	(None, 112, 112, 128)	147584
block2_pool (MaxPooling2D)	(None, 56, 56, 128)	0
block3_conv1 (Conv2D)	(None, 56, 56, 256)	295168
block3_conv2 (Conv2D)	(None, 56, 56, 256)	590080
block3_conv3 (Conv2D)	(None, 56, 56, 256)	590080
block3_pool (MaxPooling2D)	(None, 28, 28, 256)	0
block4_conv1 (Conv2D)	(None, 28, 28, 512)	1180160
block4_conv2 (Conv2D)	(None, 28, 28, 512)	2359808
block4_conv3 (Conv2D)	(None, 28, 28, 512)	2359808
block4_pool (MaxPooling2D)	(None, 14, 14, 512)	0
block5_conv1 (Conv2D)	(None, 14, 14, 512)	2359808
block5_conv2 (Conv2D)	(None, 14, 14, 512)	2359808
block5_conv3 (Conv2D)	(None, 14, 14, 512)	2359808
block5_pool (MaxPooling2D)	(None, 7, 7, 512)	0
flatten (Flatten)	(None, 25088)	0
dense (Dense)	(None, 3)	75267
=====		
Total params: 14,789,955		
Trainable params: 75,267		
Non-trainable params: 14,714,688		

6. Configure The Learning Process

```
model.compile(  
    loss='categorical_crossentropy',  
    optimizer='adam',  
    metrics=['accuracy']  
)
```

7. Train The Model

```
r = model.fit_generator(  
    training_set,  
    validation_data=test_set,  
    epochs=25,  
    steps_per_epoch=len(training_set),  
    validation_steps=len(test_set)  
)
```

/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:6:
UserWarning: `Model.fit_generator` is deprecated and will be removed
in a future version. Please use `Model.fit`, which supports
generators.

```
Epoch 1/25  
98/98 [=====] - 560s 6s/step - loss: 1.2275 -  
accuracy: 0.5383 - val_loss: 0.8698 - val_accuracy: 0.6608  
Epoch 2/25  
98/98 [=====] - 584s 6s/step - loss: 0.7810 -  
accuracy: 0.7007 - val_loss: 0.8931 - val_accuracy: 0.6491  
Epoch 3/25  
98/98 [=====] - 538s 5s/step - loss: 0.4842 -  
accuracy: 0.8264 - val_loss: 0.8348 - val_accuracy: 0.6842  
Epoch 4/25  
98/98 [=====] - 537s 5s/step - loss: 0.3813 -  
accuracy: 0.8560 - val_loss: 0.9010 - val_accuracy: 0.6901  
Epoch 5/25  
98/98 [=====] - 537s 5s/step - loss: 0.2735 -  
accuracy: 0.8999 - val_loss: 1.0660 - val_accuracy: 0.6901  
Epoch 6/25  
98/98 [=====] - 538s 5s/step - loss: 0.2211 -  
accuracy: 0.9295 - val_loss: 1.0073 - val_accuracy: 0.7076  
Epoch 7/25  
98/98 [=====] - 536s 5s/step - loss: 0.2163 -  
accuracy: 0.9224 - val_loss: 0.9560 - val_accuracy: 0.7251  
Epoch 8/25  
98/98 [=====] - 538s 6s/step - loss: 0.1728 -  
accuracy: 0.9397 - val_loss: 1.0719 - val_accuracy: 0.6491  
Epoch 9/25  
98/98 [=====] - 540s 6s/step - loss: 0.1423 -  
accuracy: 0.9581 - val_loss: 1.0706 - val_accuracy: 0.6901
```

Epoch 10/25
98/98 [=====] - 539s 6s/step - loss: 0.1118 - accuracy: 0.9704 - val_loss: 1.1651 - val_accuracy: 0.6842
Epoch 11/25
98/98 [=====] - 538s 5s/step - loss: 0.0808 - accuracy: 0.9785 - val_loss: 1.1212 - val_accuracy: 0.7076
Epoch 12/25
98/98 [=====] - 549s 6s/step - loss: 0.0751 - accuracy: 0.9857 - val_loss: 1.1451 - val_accuracy: 0.6842
Epoch 13/25
98/98 [=====] - 555s 6s/step - loss: 0.0730 - accuracy: 0.9816 - val_loss: 1.0812 - val_accuracy: 0.6842
Epoch 14/25
98/98 [=====] - 535s 5s/step - loss: 0.1074 - accuracy: 0.9734 - val_loss: 1.2204 - val_accuracy: 0.6842
Epoch 15/25
98/98 [=====] - 539s 6s/step - loss: 0.0598 - accuracy: 0.9888 - val_loss: 1.6480 - val_accuracy: 0.6316
Epoch 16/25
98/98 [=====] - 543s 6s/step - loss: 0.0810 - accuracy: 0.9806 - val_loss: 1.2050 - val_accuracy: 0.6901
Epoch 17/25
98/98 [=====] - 541s 6s/step - loss: 0.1196 - accuracy: 0.9632 - val_loss: 1.3478 - val_accuracy: 0.6374
Epoch 18/25
98/98 [=====] - 543s 6s/step - loss: 0.0915 - accuracy: 0.9755 - val_loss: 1.2961 - val_accuracy: 0.7018
Epoch 19/25
98/98 [=====] - 544s 6s/step - loss: 0.0687 - accuracy: 0.9806 - val_loss: 1.2175 - val_accuracy: 0.6842
Epoch 20/25
98/98 [=====] - 546s 6s/step - loss: 0.0492 - accuracy: 0.9918 - val_loss: 1.3791 - val_accuracy: 0.6784
Epoch 21/25
98/98 [=====] - 543s 6s/step - loss: 0.0674 - accuracy: 0.9847 - val_loss: 1.5585 - val_accuracy: 0.6433
Epoch 22/25
98/98 [=====] - 537s 5s/step - loss: 0.0740 - accuracy: 0.9775 - val_loss: 1.7693 - val_accuracy: 0.6550
Epoch 23/25
98/98 [=====] - 538s 6s/step - loss: 0.0822 - accuracy: 0.9765 - val_loss: 1.9127 - val_accuracy: 0.6374
Epoch 24/25
98/98 [=====] - 541s 6s/step - loss: 0.1048 - accuracy: 0.9653 - val_loss: 1.5448 - val_accuracy: 0.6316
Epoch 25/25
98/98 [=====] - 544s 6s/step - loss: 0.1373 - accuracy: 0.9551 - val_loss: 1.4574 - val_accuracy: 0.6842

8. Save The Model

```
from tensorflow.keras.models import load_model

model.save('/content/drive/MyDrive/Intelligent Vehicle Damage
Assessment & Cost Estimator For Insurance Companies/Model/body.h5')
```

9. Test The Model

```
from tensorflow.keras.models import load_model
import cv2
from skimage.transform import resize

model = load_model('/content/drive/MyDrive/Intelligent Vehicle Damage
Assessment & Cost Estimator For Insurance Companies/Model/body.h5')
```

```
def detect(frame):
    img = cv2.resize(frame, (224, 224))
    img = cv2.cvtColor(img, cv2.COLOR_BGR2RGB)
```

```
    if(np.max(img)>1):
        img = img/255.0
    img = np.array([img])
    prediction = model.predict(img)
    label = ["front", "rear", "side"]
    preds = label[np.argmax(prediction)]
    return preds
```

```
import numpy as np
```

```
data = "/content/drive/MyDrive/IBM - PROJECT/Data set/body-
20221023T072112Z-001/body/training/00-front/0008.jpeg"
image = cv2.imread(data)
print(detect(image))
```

```
1/1 [=====] - 0s 498ms/step
front
```

FOR LEVEL DAMAGE

IMAGE PRE PROCESSING

1. Import The ImageDataGenerator Library

```
from tensorflow.keras.preprocessing.image import ImageDataGenerator
```

1. Configure ImageDataGenerator Class

```
train_datagen = ImageDataGenerator(rescale = 1./255,
                                   shear_range = 0.1,
                                   zoom_range = 0.1,
                                   horizontal_flip = True)
```

```
test_datagen = ImageDataGenerator(rescale = 1./255)
```

1. Apply ImageDataGenerator Functionality To Trainset And Testset

```
training_set =  
train_datagen.flow_from_directory('/content/drive/MyDrive/IBM -  
PROJECT/Data set/level-20221023T072121Z-001/level/training',  
                                target_size = (224,  
224),  
                                batch_size = 10,  
                                class_mode =  
'categorical')  
test_set =  
test_datagen.flow_from_directory('/content/drive/MyDrive/IBM -  
PROJECT/Data set/level-20221023T072121Z-001/level/validation',  
                                target_size = (224, 224),  
                                batch_size = 10,  
                                class_mode =  
'categorical')
```

Found 979 images belonging to 3 classes.
Found 171 images belonging to 3 classes.

MODEL BUILDING

1. Importing The Model Building Libraries

```
import tensorflow as tf  
from tensorflow.keras.layers import Input, Lambda, Dense, Flatten  
from tensorflow.keras.models import Model  
from tensorflow.keras.applications.vgg16 import VGG16  
from tensorflow.keras.applications.vgg19 import VGG19  
from tensorflow.keras.preprocessing import image  
from tensorflow.keras.preprocessing.image import  
ImageDataGenerator, load_img  
from tensorflow.keras.models import Sequential  
import numpy as np  
from glob import glob
```

2. Loading The Model

```
IMAGE_SIZE = [224, 224]
```

```
train_path = '/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/training'  
valid_path = '/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/validation'
```

```
vgg16 = VGG16(input_shape=IMAGE_SIZE + [3], weights='imagenet',  
include_top=False)
```

Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/vgg16/vgg16_weights_tf_dim_ordering_tf_kernels_notop.h5
58889256/58889256 [=====] - 0s 0us/step

3. Adding Flatten Layer

```
for layer in vgg16.layers:  
    layer.trainable = False
```

```
folders = glob('/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/training/*')
```

```
folders
```

```
['/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/training/03-severe',  
 '/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/training/02-moderate',  
 '/content/drive/MyDrive/IBM - PROJECT/Data set/level-  
20221023T072121Z-001/level/training/01-minor']
```

```
x = Flatten()(vgg16.output)
```

```
len(folders)
```

```
3
```

4. Adding Output Layer

```
prediction = Dense(len(folders), activation='softmax')(x)
```

5. Creating A Model Object

```
model = Model(inputs=vgg16.input, outputs=prediction)
```

```
model.summary()
```

```
Model: "model"
```

Layer (type)	Output Shape	Param #
input_1 (InputLayer)	[(None, 224, 224, 3)]	0
block1_conv1 (Conv2D)	(None, 224, 224, 64)	1792
block1_conv2 (Conv2D)	(None, 224, 224, 64)	36928
block1_pool (MaxPooling2D)	(None, 112, 112, 64)	0
block2_conv1 (Conv2D)	(None, 112, 112, 128)	73856
block2_conv2 (Conv2D)	(None, 112, 112, 128)	147584
block2_pool (MaxPooling2D)	(None, 56, 56, 128)	0
block3_conv1 (Conv2D)	(None, 56, 56, 256)	295168
block3_conv2 (Conv2D)	(None, 56, 56, 256)	590080

block3_conv3 (Conv2D)	(None, 56, 56, 256)	590080
block3_pool (MaxPooling2D)	(None, 28, 28, 256)	0
block4_conv1 (Conv2D)	(None, 28, 28, 512)	1180160
block4_conv2 (Conv2D)	(None, 28, 28, 512)	2359808
block4_conv3 (Conv2D)	(None, 28, 28, 512)	2359808
block4_pool (MaxPooling2D)	(None, 14, 14, 512)	0
block5_conv1 (Conv2D)	(None, 14, 14, 512)	2359808
block5_conv2 (Conv2D)	(None, 14, 14, 512)	2359808
block5_conv3 (Conv2D)	(None, 14, 14, 512)	2359808
block5_pool (MaxPooling2D)	(None, 7, 7, 512)	0
flatten (Flatten)	(None, 25088)	0
dense (Dense)	(None, 3)	75267

```
=====
Total params: 14,789,955
Trainable params: 75,267
Non-trainable params: 14,714,688
```

6. Configure The Learning Process

```
model.compile(
    loss='categorical_crossentropy',
    optimizer='adam',
    metrics=['accuracy']
)
```

7. Train The Model

```
r = model.fit_generator(
    training_set,
    validation_data=test_set,
    epochs=25,
    steps_per_epoch=len(training_set),
    validation_steps=len(test_set)
)
```

```
/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:6:
UserWarning: `Model.fit_generator` is deprecated and will be removed
in a future version. Please use `Model.fit`, which supports
```

generators.

Epoch 1/25

98/98 [=====] - 606s 6s/step - loss: 1.1697 - accuracy: 0.5608 - val_loss: 0.9855 - val_accuracy: 0.6140

Epoch 2/25

98/98 [=====] - 596s 6s/step - loss: 0.7030 - accuracy: 0.7099 - val_loss: 0.9670 - val_accuracy: 0.6199

Epoch 3/25

98/98 [=====] - 594s 6s/step - loss: 0.4431 - accuracy: 0.8202 - val_loss: 1.0758 - val_accuracy: 0.5965

Epoch 4/25

98/98 [=====] - 592s 6s/step - loss: 0.3887 - accuracy: 0.8570 - val_loss: 1.0519 - val_accuracy: 0.6257

Epoch 5/25

98/98 [=====] - 592s 6s/step - loss: 0.3058 - accuracy: 0.8856 - val_loss: 1.5903 - val_accuracy: 0.6140

Epoch 6/25

98/98 [=====] - 596s 6s/step - loss: 0.2978 - accuracy: 0.9019 - val_loss: 1.1763 - val_accuracy: 0.6140

Epoch 7/25

98/98 [=====] - 598s 6s/step - loss: 0.2060 - accuracy: 0.9295 - val_loss: 1.2846 - val_accuracy: 0.6082

Epoch 8/25

98/98 [=====] - 596s 6s/step - loss: 0.1685 - accuracy: 0.9387 - val_loss: 1.1337 - val_accuracy: 0.6023

Epoch 9/25

98/98 [=====] - 595s 6s/step - loss: 0.1926 - accuracy: 0.9305 - val_loss: 1.1559 - val_accuracy: 0.6725

Epoch 10/25

98/98 [=====] - 594s 6s/step - loss: 0.1206 - accuracy: 0.9653 - val_loss: 1.2013 - val_accuracy: 0.6433

Epoch 11/25

98/98 [=====] - 595s 6s/step - loss: 0.1151 - accuracy: 0.9663 - val_loss: 1.2582 - val_accuracy: 0.6023

Epoch 12/25

98/98 [=====] - 595s 6s/step - loss: 0.0615 - accuracy: 0.9857 - val_loss: 1.1696 - val_accuracy: 0.6608

Epoch 13/25

98/98 [=====] - 597s 6s/step - loss: 0.0659 - accuracy: 0.9837 - val_loss: 1.1735 - val_accuracy: 0.6374

Epoch 14/25

98/98 [=====] - 597s 6s/step - loss: 0.0417 - accuracy: 0.9939 - val_loss: 1.1479 - val_accuracy: 0.6433

Epoch 15/25

98/98 [=====] - 597s 6s/step - loss: 0.0504 - accuracy: 0.9898 - val_loss: 1.5237 - val_accuracy: 0.5673

Epoch 16/25

98/98 [=====] - 596s 6s/step - loss: 0.0437 -

```

accuracy: 0.9888 - val_loss: 1.4307 - val_accuracy: 0.6140
Epoch 17/25
98/98 [=====] - 602s 6s/step - loss: 0.0428 -
accuracy: 0.9877 - val_loss: 1.2403 - val_accuracy: 0.6433
Epoch 18/25
98/98 [=====] - 605s 6s/step - loss: 0.0359 -
accuracy: 0.9949 - val_loss: 1.3156 - val_accuracy: 0.6433
Epoch 19/25
98/98 [=====] - 598s 6s/step - loss: 0.0289 -
accuracy: 0.9959 - val_loss: 1.4142 - val_accuracy: 0.6140
Epoch 20/25
98/98 [=====] - 594s 6s/step - loss: 0.0256 -
accuracy: 0.9980 - val_loss: 1.3567 - val_accuracy: 0.6316
Epoch 21/25
98/98 [=====] - 598s 6s/step - loss: 0.0248 -
accuracy: 0.9990 - val_loss: 1.3492 - val_accuracy: 0.6257
Epoch 22/25
98/98 [=====] - 596s 6s/step - loss: 0.0222 -
accuracy: 1.0000 - val_loss: 1.3326 - val_accuracy: 0.6491
Epoch 23/25
98/98 [=====] - 597s 6s/step - loss: 0.0137 -
accuracy: 0.9990 - val_loss: 1.4157 - val_accuracy: 0.6199
Epoch 24/25
98/98 [=====] - 595s 6s/step - loss: 0.0398 -
accuracy: 0.9888 - val_loss: 1.4562 - val_accuracy: 0.6257
Epoch 25/25
98/98 [=====] - 597s 6s/step - loss: 0.0292 -
accuracy: 0.9939 - val_loss: 1.5857 - val_accuracy: 0.5965

```

8. Save The Model

```

from tensorflow.keras.models import load_model

model.save('/content/drive/MyDrive/Intelligent Vehicle Damage
Assessment & Cost Estimator For Insurance Companies/Model/level.h5')

```

9. Test The Model

```

from tensorflow.keras.models import load_model
import cv2
from skimage.transform import resize

model = load_model('/content/drive/MyDrive/Intelligent Vehicle Damage
Assessment & Cost Estimator For Insurance Companies/Model/level.h5')

def detect(frame):
    img = cv2.resize(frame, (224, 224))
    img = cv2.cvtColor(img, cv2.COLOR_BGR2RGB)

    if(np.max(img)>1):
        img = img/255.0

```

```
img = np.array([img])
prediction = model.predict(img)
label = ["minor", "moderate", "severe"]
preds = label[np.argmax(prediction)]
return preds

import numpy as np

data = "/content/drive/MyDrive/IBM - PROJECT/Data set/level-20221023T072121Z-001/level/validation/01-minor/0008.jpeg"
image = cv2.imread(data)
print(detect(image))

1/1 [=====] - 1s 674ms/step
minor
```