

MAHENDRA ENGINEERING COLLEGE FOR WOMEN

ASSIGNMENT- III SOLUTION

NAME OF THE STUDENT ; G.JEVITHRA

REGISTER NUMBER ; 611419104026

YEAR/DEPARTMENT ; IV- CSE

```
import numpy as np
```

```
import pandas as pd
```

```
from PIL import ImageFile
```

```
from tqdm import tqdm
```

```
import h5py
```

```
import cv2
```

```
import matplotlib.pyplot as plt
```

```
%matplotlib inline
```

```
import seaborn as sns
```

```
from sklearn.model_selection import train_test_split
```

```
from sklearn.metrics import confusion_matrix
```

```
from sklearn.metrics import plot_confusion_matrix
```

```
from tensorflow.keras.utils import to_categorical
```

```
from tensorflow.keras.preprocessing import image as keras_image
```

```
from tensorflow.keras.models import Sequential, load_model
```

```
from tensorflow.keras.layers import Dense
```

ASSIGNMENT- III SOLUTION

```
from tensorflow.keras.layers import Activation, Dropout

from tensorflow.keras.layers import Conv2D, MaxPooling2D, GlobalMaxPooling2D

from tensorflow.keras.callbacks import ReduceLROnPlateau, ModelCheckpoint

from tensorflow.keras.layers import LeakyReLU

def model():

    model = Sequential()

    model.add(Conv2D(128, (3, 3), input_shape=x_train.shape[1:]))

    model.add(LeakyReLU(alpha=0.02))

    model.add(MaxPooling2D(pool_size=(2, 2)))

    model.add(Dropout(0.25))

    model.add(Conv2D(128, (3, 3)))

    model.add(LeakyReLU(alpha=0.02))

    model.add(MaxPooling2D(pool_size=(2, 2)))

    model.add(Dropout(0.25))

    model.add(GlobalMaxPooling2D())

    model.add(Dense(512))

    model.add(LeakyReLU(alpha=0.02))

    model.add(Dropout(0.5))
```

MAHENDRA ENGINEERING COLLEGE FOR WOMEN

ASSIGNMENT- III SOLUTION

```
model.add(Dense(10))

model.add(Activation('softmax'))


model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])


return model


model = model()


# To save the best model

checkpointer = ModelCheckpoint(filepath='weights.best.model.hdf5', verbose=2, save_best_only=True)


# To reduce learning rate dynamically

lr_reduction = ReduceLROnPlateau(monitor='val_loss', patience=5, verbose=2, factor=0.2)


# Train the model

history = model.fit(x_train, y_train, epochs=75, batch_size=32, verbose=2,
                    validation_data=(x_valid, y_valid),
                    callbacks=[checkpointer,

data_generator = keras_image.ImageDataGenerator(shear_range=0.3,
                                                zoom_range=0.3,
                                                rotation_range=30,
                                                horizontal_flip=True)


dg_history = model.fit_generator(data_generator.flow(x_train, y_train, batch_size=64),
                                steps_per_epoch = len(x_train)//64, epochs=7, verbose=2,
```

MAHENDRA ENGINEERING COLLEGE FOR WOMEN

ASSIGNMENT- III SOLUTION

```
validation_data=(x_valid, y_valid),
```

```
callbacks=[checkpointer,lr_reduction])
```