

In [1]:

```
import numpy as np#used for numerical analysis
import tensorflow #open source used for both ML and DL for computation
from tensorflow.keras.models import Sequential #it is a plain stack of layers
from tensorflow.keras import layers #A layer consists of a tensor-in tensor-out computati
on function
#Dense layer is the regular deeply connected neural network layer
from tensorflow.keras.layers import Dense,Flatten
#Faltten-used fot flattening the input or change the dimension
from tensorflow.keras.layers import Conv2D,MaxPooling2D,Dropout #Convolutional layer
#MaxPooling2D-for downsampling the image
from keras.preprocessing.image import ImageDataGenerator
```

In [2]:

```
# Initializing the CNN
classifier = Sequential()

# First convolution layer and pooling
classifier.add(Conv2D(32, (3, 3), input_shape=(64, 64, 3), activation='relu'))
classifier.add(MaxPooling2D(pool_size=(2, 2)))

# Second convolution layer and pooling
classifier.add(Conv2D(32, (3, 3), activation='relu'))

# input_shape is going to be the pooled feature maps from the previous convolution layer
classifier.add(MaxPooling2D(pool_size=(2, 2)))

# Flattening the layers
classifier.add(Flatten())

# Adding a fully connected layer
classifier.add(Dense(units=128, activation='relu'))
classifier.add(Dense(units=5, activation='softmax')) # softmax for more than 2
```

In [3]:

```
classifier.summary()#summary of our model
```

Model: "sequential"

Layer (type)	Output Shape	Param #
=====		
conv2d (Conv2D)	(None, 62, 62, 32)	896
max_pooling2d (MaxPooling2D)	(None, 31, 31, 32)	0
conv2d_1 (Conv2D)	(None, 29, 29, 32)	9248
max_pooling2d_1 (MaxPooling2D)	(None, 14, 14, 32)	0
flatten (Flatten)	(None, 6272)	0
dense (Dense)	(None, 128)	802944
dense_1 (Dense)	(None, 5)	645
=====		
Total params: 813,733		
Trainable params: 813,733		
Non-trainable params: 0		