

Gas leakage monitoring and alerting system for industries

PROJECT NAME	GAS LEAKAGE MONITORING & ALERTING SYSTEM FOR INDUSTRIES
TEAM ID	PNT2022TMID15951
TEAM MEMBERS	1)E. Nisha (Team leader) 2)S. Siva 3)R. Sona 4)RB. Shibin
BRANCH	ELECTRONICS AND COMMUNICATION ENGINEERING

ABSTRACT

Leakage of any kind of gas has been a concern in recent years, whether it is in a residential setting, a business, a cafe, or a canteen. In this paper development of an IoT based gas wastage monitoring, leakage detecting and alerting system is proposed. This paper elaborates design such an intelligent system that will help save gas and smartly prevent accidents. The system needs to be integrated with the cooker. The technology includes ultrasonic sensors that determine if the cooker is being utilized for cooking purposes or not. If it is discovered that the cooker is not in use, the system uses an automatic switching off mechanism to cut off the gas supply. The moment gas leakage will probably be recognized, users will be informed via SMS through GSM, and so that user can solve the issue as soon as possible. The system will monitor flame and fire through flame sensor. When a fire is detected, the buzzer begins to sound. Aside from that, the system also has a cloud storage capability. The usage of gas for each user each day may be tracked with the aid of this cloud storage solution. At the end of the day, this procedure will assist in detecting per user natural gas usage. The system has been tested and it is able to monitor gas wastage, leakage and send a SMS to the user.

The resulting performance indicated its effectiveness toward saving a significant portion of the wasted gas in domestic.

INTRODUCTION

Now a days the home safety detection system plays the important role for the security of people. Since all the people from the home goes to work on daily bases, it makes impossible to check on the appliances available at home specially LPG gas cylinder, wired circuits, Etc. Since last three years there is a tremendous hike in the demands of liquefied petroleum gas (LPG) and natural gas. To meet this access amount of demand for energy and replace oil and coal due to their environmental disadvantage, LPG and natural gas are preferred. These gases are mostly used on large scale in industry, heating, home appliances and motor fuel. So as to track this leakage gas, the system includes MQ6 gas sensor. Through this, explosion or getting affected by the leakage of gas could be avoided.

OBJECTIVE

The design of a sensor-based automatic gas leakage detector with an alert and control system has been proposed. This is an affordable, less power using, lightweight, portable, safe, user friendly, efficient, multi featured and simple system device for detecting gas. Gas leakage detection will not only provide us with significance in the health department but it will also lead to raise our economy, because when gas leaks it not only contaminates the atmosphere, but also wastage of gases will hurt our economy. The need for ensuring safety in workplaces is expected to be the key driving force for the market over the coming years.

PROBLEM FORMULATION

Gas leakage is nothing but the leak of any gaseous molecule from a stove, or a pipeline, or cylinder etc. This can occur either purposefully or even unintendedly. As we are aware that these kinds of leaks are dangerous to our health, and when it becomes explosive it could cause great danger to the people, home, workplace, industry and the environment.

Few of the major incidents that took place due to gas leakage include the Bhopal disaster and the vizag gas leak. The Bhopal disaster is known to be the worst industrial accident ever. Approximately 45 tons of methyl isocyanate was leaked from the insecticide plant. Methyl isocyanate is an organic compound and a chemical that could come from the carbamate pesticides. This colourless, poisonous and flammable liquid is something that human beings have to be away from.

Vizag gas leak was a resultant of the escape of styrene that were unattended for a long period. This colourless oily liquid can spread in fumes. So, a detector must be made in such a way that could detect any kind of gas, fume, leak, smoke etc. However harmful and dangerous it can be, the detector could be attached with certain parameters that could help to prevent the issue.

LIST THE COMPONENTS

S. No	Name of the Component	Quantity
1.	Arduino UNO R3	1
2.	Breadboard	1
3.	LED	2
4.	Resistor	5
5.	Piezo	1
6.	Gas Sensor	1
7.	LCD 16*2	1

ARDUINO UNO R3



Arduino Uno R3 is one kind of ATmega328P based microcontroller board. It includes the whole thing required to hold up the microcontroller; just attach it to a PC with the help of a USB cable, and give the supply using AC-DC adapter or a battery to get started. The term Uno means “one” in the language of “Italian” and was selected for marking the release of Arduino’s IDE 1.0 software. The R3 Arduino Uno is the 3rd as well as most recent modification of the Arduino Uno. Arduino board and IDE software are the reference versions of Arduino and currently progressed to new releases.

BREADBOARD



A breadboard is a widely used tool to design and test circuit. You do not need to solder wires and components to make a circuit while using a bread board. It is easier to mount components & reuse them. Since, components are not soldered you can change your circuit design at any point without any hassle. It consists of an array of conductive metal clips encased in a box made of white ABS plastic, where each clip is insulated with another clips. Generally, it consists of two sections each with 5 rows and 64 columns. Every column is electrically connected from inside.

LED



LED (Light Emitting Diode) is an optoelectronic device which works on the principle of electro-luminescence. Electro-luminescence is the property of the material to convert electrical energy into light energy and later it radiates this light energy. In the same way, the semiconductor in LED emits light under the influence of electric field. The symbol of LED is formed by merging the symbol of P-N Junction diode and outward arrows.

RESISTOR



A passive electrical component with two terminals that are used for either limiting or regulating the flow of electric current in electrical circuits.

PEIZO




A piezo is a device that generates a voltage when force is applied or becomes deformed when voltage is supplied.

GAS SENSOR



A gas sensor is a device which detects the presence or concentration of gases in the atmosphere. Based on the concentration of the gas the sensor produces a corresponding potential difference by changing the resistance of the material inside the sensor, which can be measured as output voltage.


LCD 16*2




16x2 LCD is one kind of electronic device used to display the message and data. The term LCD full form is Liquid Crystal Display. The display is named 16x2 LCD because it has 16 Columns and 2 Rows, it can be displayed (16x2=32) 32 characters in total and each character will be made of 5x8 Pixel Dots. These displays are mainly based on multi-segment light emitting diodes. There are a lot of combinations of display available in the market like 8x1, 8x2, 10x2, 16x1, etc.


PROPOSED METHOD

Arduino UNO (ATmega-328) is the main unit of the system which performs the following tasks. A signal conditioning of the Arduino UNO is done by output signal of the sensor, provided input to Arduino. The detection results displayed on LCD. Indicates the people of danger in work place, factory, home. Buzzer activity with beep(siren) sound is made. Also send alert SMS to the in charge of the plant whose number is saved in SIM card by using GSM modem. The SMS received depends upon the leak of gas in the detection area of the sensor.





CIRCUIT DIAGRAM



SOLUTION STATEMENT

The system can be taken as a small attempt in connecting the existing primary gas detection methods to a mobile platform integrated with IOT platforms. The gases are sensed in an area of 1m radius of the rover and the sensor output data's are continuously transferred to the local server. The accuracy of sensors aren't up to the mark thus stray gases are also detected which creates an amount of error in the outputs of the sensors, especially in case of methane. Further the availability and storage of toxic gases like hydrogen sulphide also creates problems for testing the assembled hardware. As the system outside the pipeline, the complication of system maintenance and material selection of the system in case of corrosive gases is reduced. Thus, the system at this stage can only be used as a primary indicator of leakage inside a plant.

CONCLUSION

After this project performance, can conclude that detection of the LPG gas leakage is incredible in the project system. Applicable usefully in the industrial and domestic purpose. In danger situations we are able to save the life by using this system. An alert is indicated by the GSM module. A sensor node senses gas like CO₂, oxygen, propane. The estimated range of transmission and consumption of power is obtained. The simple procedures and Arduino UNO Microcontroller area used to build the sensor.

