Assignmen t 4

Student Name: GOWTHAM K

Student Roll No: PNT2022TMIDI7635

Maximum Marks: 2 Marks

Project Name: IoT based safety gadget for child

safety monitoring notification

Ouestion:

Write a code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100cms send an "Alert" to IBM cloud and display in the device recent events.

Code:

```
#include
<WiFi.h>
#include
<PubSubClient.h>
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//------credentials of IBM Accounts-----
#define ORG "kotoq5"//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32"//Device type mentioned in ibm
watson IOT Platform#define DEVICE_ID "12345"//Device ID
mentioned in ibm watson IOT Platform #define TOKEN "12345678"
//Token
String data3;
```

```
char server[] = ORG
".messaging.internetofthings.ibmcloud.com"; char
publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribetopic[] = "iot-
2/cmd/test/fmt/String"; char authMethod[] =
"use-token-auth";
```

```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback ,wifiClient);
const int trigPin = 5;
const int echoPin =
18:#define
SOUND_SPEED
0.034 long
duration; float
distance: void
setup()
{ Serial.begin(1152
00);
pinMode(trigPin,
OUTPUT):
pinMode(echoPin,
INPUT); wificonnect();
mqttconnect();
void loop()
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
```

```
duration = pulseIn(echoPin,
HIGH); distance = duration *
SOUND_SPEED/2;
Serial.print("Distance (cm):
"); Serial.println(distance);
if(distance<100)
{
    Serial.println("ALERT!!");
    delay(1000);</pre>
```

```
PublishData(distance)
; delay(1000);
if (!client.loop())
{mqttconnect();
delay(1000);
void PublishData(float dist)
{mqttconnect();
String payload =
"{\"Distance\":"; payload +=
dist;
payload += ",\"ALERT!!\":""\"Distance less than
100cms\""; payload += "}";
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial println("Publish ok");
} else {
Serial println("Publish failed");
void mqttconnect() {
if (!client.connected())
{ Serial.print("Reconnecting
```


```
client to"); Serial.println(server);
while (!!!client.connect(clientId, authMethod, token)) {
    Serial.print(".")
; delay(500);
}
```

```
initManagedDevice();
Serial.println();
void wificonnect()
Serial.println(); Serial.print("Connecting to ");
WiFi.begin("Wokwi-GUEST", "", 6); while
(WiFi.status() !=WL CONNECTED) { delay(500);
Serial.print(".");
Serial println(""); Serial println("WiFi
connected"); Serial.println("IP address:
"); Serial.println(WiFi.localIP());
void initManagedDevice() {
if (client.subscribe(subscribetopic))
{ Serial.println((subscribetopic));
Serial.println("subscribe to cmd OK");
} else {
Serial println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
for (int i = 0; i < payloadLength; i++) {
```

```
//Serial.print((char)payload[i])
; data3 += (char)payload[i];
Serial.println("data: "+
data3); data3="";
     Diagram.json:
  "version": 1,
  "author"
  "sweetysharon",
  "editor": "wokwi",
  "parts": [
   { "type": "wokwi-esp32-devkit-v1", "id": "esp", "top": -4.67, "left": -114.67, "attrs": {} },
   { "type": "wokwi-hc-sr04", "id": "ultrasonic1", "top": 15.96, "left": 89.17, "attrs": {} }
  "connections": [
   [ "esp:TX0", "$serialMonitor:RX", "", [] ],
    [ "esp:RX0", "$serialMonitor:TX", "",
    [] ],[
     "esp:VIN",
      "ultrasonic1:VC
```

```
C"
, "red",
[ "h-37.16", "v-178.79", "h200", "v173.33", "h100.67" ]
],
[ "esp:GND.1", "ultrasonic1:GND", "black", [ "h39.87", "v44.04", "h170" ] ],
[ "esp:D5", "ultrasonic1:TRIG", "green", [ "h54.54", "v85.07", "h130.67" ] ],
[ "esp:D18", "ultrasonic1:ECHO", "green", [ "h77.87", "v80.01", "h110" ] ]
```

Circuit Diagram:



Output:

output:

```
Connecting to ...
WiFi connected
IP address:
10.10.0.2
Reconnecting client to ytluse.messaging.internetofthings.ibmcloud.com
iot-2/cmd/test/fmt/String
subscribe to cmd OK

Distance (cm): 399.92
Distance (cm): 399.96
Distance (cm): 399.98
Distance (cm): 399.98
Distance (cm): 399.98
Distance (cm): 399.94
Distance (cm): 399.94
Distance (cm): 399.92
Distance (cm): 399.94
```

IBM cloud output:

