M.A.M.COLLEGE OF ENGINEERING AND TECHNOLOGY INFORMATION TECHNOLOGY IBM NALAIYA THIRAN

Delivery plan sprint-1

TITTLE NAME : Child Safety Monitoring And Notification system

DOMAIN NAME : Internet Of Things (IOT)

TEAM LEAD NAME: Priyadharshini M

TEAM MEMBERS NAME: Vijayalakshmi S

Ragavi R

Swetha K

MENTOR NAME: Fathimaa Chandhini

Team ID : PNT2022TMID45225

Team ID: PNT2022TMID45225

Project Title: Safety Gadget for child safety monitoring and notification

Delivery plan sprint-1

Live Location Tracking:-

GPS is installed on gadget to track its current location can be tracked on android app and via SMS request sent from parent phone to safety gadget. Outputs of live location tracking.

Panic Alert Systems:-

Panic alert system on the gadget is triggered during a panic situation, automatic call and SMS are triggered to the parental phone. The alert is also updated to the cloud for the purpose of app monitoring. Fig. 4. Outputs of panic alert system.

Stay Connected Feature:-

Stay connected feature is used to trigger call and predefined SMS anytime from gadget to parental phone by just pressing a button and also parents can make SMS and call the gadget anytime.

Health Monitoring System:-

Health monitoring system is implemented using a heart beat sensor, temperature sensor which is updated to the cloud and also can be monitored via app. The current value of sensors can be obtained using SMS requests sent to gadgets from the parent phone. Outputs of health monitoring system.

Gadget Plugged or Unplugged Monitoring:-

Gadget plug or unplugged is monitored using a contact switch installed on smart gadget, as soon as the device is unplugged, an alert is provided to the parent phone via SMS and it is also updated to cloud for app monitoring.

Boundary monitoring system:-

Boundary monitoring system is used to track the safety gadget using the binding gadget by implementing signal strength concept. As soon as the safety gadget moves far away from the BLE listener gadget then an alert is provided to itself. Listener device and broadcast device.