EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES

MODEL BUILDING

PREDICTIONS

Date	04 November 2022
Team ID	PNT2022TMID50173
Project Name	Emerging Methods for Early Detection of Forest Fires

Importing The ImageDataGenerator Library

import keras

from keras.preprocessing.image import ImageDataGenerator

Define the parameters/arguments for ImageDataGenerator class

train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rot ati on_range=180,zoom_range=0.2, horizontal_flip=True) test_datagen=ImageDataGenerator(rescale=1./255)

Applying ImageDataGenerator functionality to trainset

x_train=train_datagen.flow_from_directory(r'/content/drive/MyDriv e/ Dataset/train_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 436 images belonging to 2 classes.

Applying ImageDataGenerator functionality to testset

```
x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive / Dataset/test_set',target_size=(128,128),batch_size=32, class_mode='binary')
```

Found 121 images belonging to 2 classes.

Import model building libraries

```
#To define Linear initialisation import Sequential
from keras.models import Sequential
#To add layers import Dense
from keras.layers import Dense
#To create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')
```

Initializing the model

```
model=Sequential()

Add CNN Layer

model.add(Convolution2D(32,
(3,3),input_shape=(128,128,3),activation='relu'))

#add maxpooling layer
```

```
model.add(MaxPooling2D(pool_size=(2,2)))
#add flatten layer
model.add(Flatten())
```

Add Hidden Layer

```
#add hidden layer
model.add(Dense(150,activation='relu'))
#add output layer
model.add(Dense(1,activation='sigmoid')
)
Configure the learning process
model.compile(loss='binary_crossentropy',optimizer="adam",metrics=[
"ac curacy"])
Train the model
model.fit generator(x train, steps per epoch=14, epochs=10, validation
da ta=x_test,validation_steps=4)
Epoch 1/10
14/14 [=======] - 97s 7s/step - loss:
1.3060 -
accuracy: 0.7775 - val loss: 0.5513 - val accuracy: 0.8512
Epoch 2/10
14/14 [=======] - 26s 2s/step - loss:
0.3178 -
accuracy: 0.8807 - val loss: 0.1299 - val accuracy: 0.9421
Epoch 3/10
14/14 [=======] - 26s 2s/step - loss:
0.2226 -
accuracy: 0.9106 - val loss: 0.1311 - val accuracy: 0.9421
Epoch 4/10
0.1836 -
accuracy: 0.9174 - val_loss: 0.1129 - val_accuracy: 0.9339
Epoch 5/10
14/14 [=======] - 30s 2s/step - loss:
0.1675 -
accuracy: 0.9243 - val loss: 0.0925 - val accuracy: 0.9669
Epoch 6/10
14/14 [=======] - 26s 2s/step - loss:
```

```
0.1884 -
accuracy: 0.9289 - val loss: 0.1287 - val accuracy: 0.9339
Epoch 7/10
14/14 [=======
                0.1724 -
accuracy: 0.9335 - val loss: 0.0926 - val accuracy: 0.9752
Epoch 8/10
14/14 [======
                   0.1510 -
accuracy: 0.9404 - val loss: 0.0757 - val accuracy: 0.9752
Epoch 9/10
0.173 -
accuracy: 0.9174 - val loss: 0.0537 - val accuracy: 0.9835
Epoch 10/10
14/14 [=======] - 26s
                                             0.154 -
2s/step - loss:
accuracy: 0.9312 - val loss: 0.0573 - val accuracy: 0.9835
<keras.callbacks.History at 0x7f05d66a9c90>
```

Save The Model

model.save("forest1.h5")

Predictions

```
#import load_model from
keras.model from keras.models
import load_model #import image
class from keras
from tensorflow.keras.preprocessing import image #import numpy
import numpy as np
#import cv2
import cv2
#load the saved model
model = load_model("forest1.h5")
img=image.load_img(r'/content/drive/MyDrive/Dataset/test_set/forest
/ 0.48007200_1530881924_final_forest.jpg')
```

```
x=image.img_to_array(img)
res = cv2.resize(x, dsize=(128, 128), interpolation=cv2.INTER_CUBIC)
#expand the image shape
x=np.expand_dims(res,axis=
0) pred= model.predict(x)

1/1 [========] - 0s 126ms/step
pred
array([[0.]], dtype=float32)
```