

# **EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES**

## **Video Analysis**

### **Creating An Account In Twilio Service**

<b>Date</b>	06 November 2022
<b>Team ID</b>	PNT2022TMID50173
<b>Project Name</b>	Emerging Methods for Early Detection of ForestFires

#### ***Importing The ImageDataGenerator Library***

```
import keras  
from keras.preprocessing.image import ImageDataGenerator
```

#### ***Define the parameters/arguments for ImageDataGenerator class***

```
train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,  
rotation_range=180,zoom_range=0.2, horizontal_flip=True)  
test_datagen=ImageDataGenerator(rescale=1./255)
```

#### ***Applying ImageDataGenerator functionality to trainset***

```
x_train=train_datagen.flow_from_directory(r'/content/drive/MyDrive/Dataset/train_set',  
target_size=(128,128),batch_size=32, class_mode='binary')
```

Found 436 images belonging to 2 classes.

## ***Applying ImageDataGenerator functionality to testset***

```
x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive/Dataset/test_set',  
target_size=(128,128),batch_size=32, class_mode='binary')
```

Found 121 images belonging to 2 classes.

## ***Import model building libraries***

```
#To define Linear initialisation import Sequential  
from keras.models import Sequential  
#To add layers import Dense  
from keras.layers import Dense  
#To create Convolution kernel import Convolution2D  
from keras.layers import Convolution2D  
#import Maxpooling layer  
from keras.layers import MaxPooling2D  
#import flatten layer  
from keras.layers import Flatten import  
warnings warnings.filterwarnings('ignore')
```

## ***Initializing the model***

```
model=Sequential()
```

|

## ***Add CNN Layer***

```
model.add(Convolution2D(32, (3,3),input_shape=(128,128,3),activation='relu'))  
#add maxpooling layer  
model.add(MaxPooling2D(pool_size=(2,2)))  
#add flatten layer  
model.add(Flatten())
```

## ***Add Dense Layer***

```
#add hidden layer  
model.add(Dense(150,activation='relu'))  
#add output layer  
model.add(Dense(1,activation='sigmoid'))
```

## ***Configure the learning process***

```
model.compile(loss='binary_crossentropy',optimizer="adam",metrics=["accuracy"])
```

## ***Train the model***

```

model.fit_generator(x_train,steps_per_epoch=14,epochs=10,validation_data=x_test,validation_steps=4)
Epoch 1/10
14/14 [=====] - 205s 15s/step - loss: 2.7344 - accuracy: 0.7454 - val_loss: 0.2016 - val_accuracy: 0.9256
Epoch 2/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.8945 - val_loss: 0.2290 - val_accuracy: 0.9339
Epoch 3/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.8922 - val_loss: 0.0524 - val_accuracy: 0.9835
Epoch 4/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9174 - val_loss: 0.1570 - val_accuracy: 0.9421
Epoch 5/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9083 - val_loss: 0.0767 - val_accuracy: 0.9752
Epoch 6/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9335 - val_loss: 0.0749 - val_accuracy: 0.9752
Epoch 7/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9312 - val_loss: 0.1264 - val_accuracy: 0.9421
Epoch 8/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9266 - val_loss: 0.0652 - val_accuracy: 0.9835
Epoch 9/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9358 - val_loss: 0.0567 - val_accuracy: 0.9835
Epoch 10/10
14/14 [=====] - 20s 1s/step - loss: accuracy: 0.9404 - val_loss: 0.0448 - val_accuracy: 0.9917
0.3267 -
0.2991 -
0.2418 -
0.1984 -
0.1643 -
0.1538 -
0.1732 -
0.1514 -
0.1445 -
<keras.callbacks.History at 0x7f51fdf33610>

```

***Save The Model***

```
model.save("forest1.h5")
```

## ***Predictions***

```
#import load_model from keras.model

from keras.models import load_model

#import image class from keras
from tensorflow.keras.preprocessing import image #import numpy import numpy as
np
#import cv2
import cv2

#load the saved model
model = load_model("forest1.h5")

img=image.load_img(r'/content/drive/MyDrive/Dataset/test_set/forest/
0.48007200_1530881924_final_forest.jpg')
x=image.img_to_array(img)
res = cv2.resize(x, dsize=(128, 128), interpolation=cv2.INTER_CUBIC) #expand the
image shape

x=np.expand_dims(res,axis=0)
pred= model.predict(x)
1/1 [=====] - 0s 94ms/step pred
array([[0.]], dtype=float32)
```

## ***OpenCV For Video Processing***

```
pip install twilio
Looking in indexes: https://pypi.org/simple, https://us-
python.pkg.dev/colab-wheels/public/simple/
Collecting twilio
Downloading twilio-7.15.1-py2.py3-none-any.whl (1.4 MB)
ent already satisfied: pytz in /usr/local/lib/python3.7/dist-packages (from twilio)
(2022.5)
Collecting PyJWT<3.0.0,>=2.0.0
Downloading PyJWT-2.6.0-py3-none-any.whl (20 kB)
Requirement already satisfied: requests>=2.0.0 in /usr/local/lib/python3.7/dist-
packages (from twilio) (2.23.0) Requirement already satisfied: chardet<4,>=3.0.2 in
/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio) (3.0.4)
Requirement already satisfied: idna<3,>=2.5 in /usr/local/lib/python3.7/dist-packages
(from requests>=2.0.0->twilio)
(2.10)
Requirement already satisfied: certifi>=2017.4.17 in /usr/local/lib/python3.7/dist-
packages (from requests>=2.0.0->twilio) (2022.9.24)
Requirement already satisfied: urllib3!=1.25.0,!1.25.1,<1.26,>=1.21.1 in
```

```

/usr/local/lib/python3.7/dist-packages (from requests>=2.0.0- >twilio) (1.24.3)
Installing collected packages: PyJWT, twilio
Successfully installed PyJWT-2.6.0 twilio-7.15.1
pip install playsound
Looking in indexes: https://pypi.org/simple, https://us-
python.pkg.dev/colab-wheels/public/simple/
Collecting playsound
Downloading playsound-1.3.0.tar.gz (7.7 kB) Building wheels for collected
packages: playsound
Building wheel for playsound (setup.py) ... e=playsound-1.3.0-py3- none-any.whl
size=7035
sha256=e7e96c774a98522e182b59b7b292f0f932097658d8bfce86c922c363f862b0e
2
Stored in directory:
/root/.cache/pip/wheels/ba/f8/bb/ea57c0146b664dca3a0ada4199b0ecb5f9dfc
b7b7e22b65ba2
Successfully built playsound
Installing collected packages: playsound
Successfully installed playsound-1.3.0
#import opencv library
import cv2
#import numpy
import numpy as np
#import image function from keras
from keras.preprocessing import image
#import load_model from keras
from keras.models import load_model
#import client from twilio API
from twilio.rest import Client
#import playsound package
from playsound import playsound
WARNING:playsound:playsound is relying on another python subprocess. Please
use `pip install pygobject` if you want playsound to run more efficiently.
#load the saved model
model=load_model("forest1.h5") #define video video=cv2.VideoCapture(0) #define
the features name=['forest','with fire']

```

## ***Creating An Account In Twilio Service***

```

account_sid='ACfb4e6d0e7b0d25def63044919f1b96e3'
auth_token='f9ae4fc4a617a527da8672e97eefb2d8'
client=Client(account_sid,auth_token)
message=client.messages \
.create(
    body='Forest Fire is detected, stay alert',
    from_='+1 302 248 4366',
    to='+91 99400 12164'
)

```

```
)  
print(message.sid)
```

SM4aa5a4751b7bcec159dc4c695752293d