Assignment-4

Team ID: PNT2022TMID52032

Name: Priya Lakshmi.M

Write Code and connections in wokwi for ultrasonic sensor. whatever distance is less than 100 cm send "Alert" to IBM cloud and display in device recent events.

PROGRAM:

```
//Pins
const int TRIG_PIN = 7;
const int ECHO_PIN = 8;

//Anything over 400 cm (23200 us pulse) is "out of range"
const unsigned int MAX_DIST = 23200;

void setup() {

// The Trigger pin will tell the sensor to range find
Pin Mode(TRIG_PIN, OUTPUT);
digital Write(TRIG_PIN, LOW);

//Set Echo pin as input to measure the duration of
```

```
//pulses coming back from the distance sensor
pinMode(ECHO_PIN, INPUT);
// We'll use the serial monitor to view the sensor output
 Serial.begin(9600);
}
void loop() {
unsigned long t1
unsigned long t2;
 unsigned long pulse_width;
 float cm;
 float inches;
// Hold the trigger pin high for at least 10 us
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
// Wait for pulse on echo pin
while (digitalRead( ECHO_PIN )==0 );
// Measure how long the echo pin was held high (pulse width)
 // Note: the micros() counter will overflow after-70 min
 t1= micros ();
 while (digitalRead(ECHO_PIN) == 1);
  t2 = micros();
  pulse_width = t2-t1;
 // Calculate distance in centimeters and inches. The constants
```

```
//are found in the datasheet, and calculated from the assumed speed
 // of sound in air at sea level (- 340m/s)
 cm=pulse_Width / 58;
 inches = pulse width/148.0;
 // Print out results
 if (pulse_width >MAX _ DIST ){
 Serial.println("Out of range");
 } else {
 Serial.println("*******************************);
 Serial.print("The Measured Distance in cm: ");
 Serial.println(cm);
if( cm < 100){
    //while(true){
    Serial.println("Alert!!");
    //}
 }
 Serial.print("********************************);
 }
 //wait at least 1000ms before next measurement
 Delay(1000);
```

Output:

1. If the distance is less than 100 cm, it alerts.

```
WOKWI B SAVE
 hc-sr04.ino diagram json ● Library Manager ▼
                                                                                                                                                                                              ₫00:00.466 (%58%
           const int TRIG_PIN = 7;
          const int ECHO PIN = 8;
          // Anything over 400 cm (23200 us pulse) is "out of range" const unsigned int MAX_DIST - 23200;
          void setup() {
            // The Trigger pin will tell the sensor to range find
pinMode(TRIG_PIN, OUTPUT);
digitalWrite(TRIG_PIN, LOW);
                                                                                                                                       UNO UNO
            //Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensor
pinMode(ECHO_PIN, INPUT);
             // We'll use the serial monitor to view the sensor output
            Serial.begin(9600);
                                                                                                                                           POWER ANALOG IN
          void loop() {
            unsigned long t1;
unsigned long t2;
unsigned long pulse_width;
float cm;
float inches;
                                                                                                          ***********
                                                                                                          The Measured Distance in cm : 84.14
                                                                                                          Alert!!
                                                                                                                                                                                                    // Hold the trigger pin high for at least 10 us
```

2. If the distance is more than 100 cm, it won't alert

```
WOKWI B SAVE - A SHARE
                                                                                                                                                                                Docs
hc-sr04.ino
                                                                                                   Simulation
               diagram json ● Library Manager ▼
                                                                                                                                                                          Ŏ00:00.599 (%62%
           const int TRIG_PIN = 7;
          const int ECHO_PIN = 8;
          // Anything over 400 cm (23200 us pulse) is "out of range"
          const unsigned int MAX_DIST = 23200;
            // The Trigger pin will tell the sensor to range find
pinMode(TRIG_PIN, OUTPUT);
     11
            digitalWrite(TRIG_PIN, LOW);
                                                                                                                              OO UNO
     14
15
           //Set Echo pin as input to measure the duration of
//pulses coming back from the distance sensor
pinMode(ECHO_PIN, INPUT);
             // We'll use the serial monitor to view the sensor output
     19
20
            Serial.begin(9600);
                                                                                                                             POWER ANALOG IN
    21
22
23
24
          void loop() {
             unsigned long t1;
     25
26
            unsigned long t2;
unsigned long pulse_width;
                                                                                                The Measured Distance in cm : 227.10
                                                                                                *********
            float cm;
float inches;
                                                                                                                                                      Activate Windows
```

3. Simulation and code execution

