### Assignment -4

# Data Publish to IOT

#### Device

Assignment Date	08 november 2022
Project name	IoT Based Safety Gadget for Child Safety Monitoring and Notification
Student Name	K Sanjay
Maximum Marks	2 Marks

## Question-1:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less 100 cms send "alert" to ibm cloud and display in device recent events.

#### **Solution:**

authentication method

```
#include <WiFi.h>//library for wifi

#include <PubSubClient.h>//library for MQtt

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);

//------credentials of IBM Accounts-----

#define ORG "woa350"//IBM ORGANITION ID

#define DEVICE_TYPE "ifthihar "//Device type mentioned in ibm watson IOT Platform

#define DEVICE_ID "ifthihardev "//Device ID mentioned in ibm watson IOT Platform

#define TOKEN " uuc(6Dt-fjW7BD9u)2 " //Token

String data3; float dist;

//------- Customise the above values ------ char server[] = ORG

".messaging.internetofthings.ibmcloud.com";// Server Name

char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format in which data to be send

char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command type AND
```

COMMAND IS TEST OF FORMAT STRING char authMethod[] = "use-token-auth";//

```
char token[] = TOKEN; char clientId[] = "d:" ORG ":" DEVICE_TYPE
":" DEVICE_ID;//client id
//....
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by passing
parameter like server id, portand wificredential
int LED = 4;
int trig = 5;
int echo = 18;
void setup()
{
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo,INPUT);
pinMode(LED, OUTPUT);
delay(10); wificonnect();
mqttconnect();
}
void loop()// Recursive Function
{
digitalWrite(trig,LOW);
digitalWrite(trig,HIGH);
delayMicroseconds(10);
digitalWrite(trig,LOW); float
dur = pulseIn(echo,HIGH); float
dist = (dur * 0.0343)/2;
Serial.print ("Distancein cm");
```

Serial.println(dist);

```
PublishData(dist);
delay(1000); if
(!client.loop()) {
mqttconnect();
}
}
/*.....*/
void PublishData(float dist) {
mqttconnect();//function call for connecting to ibm
/* creating the String in in form JSon to update the data to ibm
cloud
 */ String
object; if
(dist <100)
 {
  digitalWrite(LED,HIGH);
Serial.println("object is near");
object = "Near";
}
 else
 {
  digitalWrite(LED,LOW);
Serial.println("no object found");
object = "No";
}
 String payload = "{\"distance\":";
payload += dist; payload += ","
"\"object\":\""; payload += object;
payload += "\"}";
```

```
Serial.print("Sending payload: ");
Serial.println(payload); if (client.publish(publishTopic,
(char*) payload.c_str())) {
  Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok
in Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
 }
}
void mqttconnect() { if
(!client.connected()) {
  Serial.print("Reconnecting client to ");
Serial.println(server); while (!!!client.connect(clientId,
authMethod, token)) {
                           Serial.print(".");
                                                delay(500);
  }
  initManagedDevice();
  Serial.println();
 }
}
void wificonnect() //function defination for wificonnect
{
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
while (WiFi.status() != WL_CONNECTED) { delay(500);
  Serial.print(".");
 }
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
```

```
}
void initManagedDevice() { if
(client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
 }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic); for (int i =
0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);
(char)payload[i];
 }
data3="";
}
```



