



## Assignment1 : Make a smart home in tinkercad,using2+ sensors,led,buzzer in single code and circuit

Using tinkercad connecting the circuit.



Inserting the code.



Program code:

```
#include <Servo.h>
int output1Value = 0;
int sen1Value = 0;
int sen2Value = 0;
int const gas_sensor = A1;
int const LDR = A0;
int limit = 400;
long readUltrasonicDistance(int triggerPin, int echoPin)
{
    pinMode(triggerPin, OUTPUT); // Clear the trigger
    digitalWrite(triggerPin, LOW);
    delayMicroseconds(2);
    // Sets the trigger pin to HIGH state for 10 microseconds
    digitalWrite(triggerPin, HIGH);
    delayMicroseconds(10);
    digitalWrite(triggerPin, LOW);
    pinMode(echoPin, INPUT);
    // Reads the echo pin, and returns the sound wave travel time in microseconds
    return pulseIn(echoPin, HIGH);
}
Servo servo_7;
void setup()
{
    Serial.begin(9600); //initialize serial communication
    pinMode(A0, INPUT); //LDR
    pinMode(A1, INPUT); //gas sensor
    pinMode(13, OUTPUT); //connected to relay
    servo_7.attach(7, 500, 2500); //servo motor
    pinMode(8, OUTPUT); //signal to piezo buzzer
    pinMode(9, INPUT); //signal to PIR
    pinMode(10, OUTPUT); //signal to npn as switch
    pinMode(4, OUTPUT); //Red LED
    pinMode(3, OUTPUT); //Green LED
}
void loop()
{
    //-----light intensity control-----//
    //-----
    int val1 = analogRead(LDR);
    if (val1 > 500)
    {
        digitalWrite(13, LOW);
        Serial.print("Bulb ON = ");
        Serial.print(val1);
    }
}
```

```

else
{
digitalWrite(13, HIGH);
Serial.print("Bulb OFF = ");
Serial.print(val1);
} //-----
//----- light & fan control -----//
//-----
sen2Value = digitalRead(9);
if (sen2Value == 0)
{
digitalWrite(10, LOW); //npn as switch OFF
digitalWrite(4, HIGH); // Red LED ON, indicating no motion
digitalWrite(3, LOW); //Green LED OFF, since no Motion detected
Serial.print(" || NO Motion Detected " );
}
if (sen2Value == 1)
{
digitalWrite(10, HIGH); //npn as switch ON
delay(3000);
digitalWrite(4, LOW); // RED LED OFF
digitalWrite(3, HIGH); //GREEN LED ON , indicating motion detected
Serial.print(" || Motion Detected! " );
}
delay(300);

//-----
// ----- Gas Sensor -----//
//-----
int val = analogRead(gas_sensor); //read sensor value
Serial.print("|| Gas Sensor Value = ");
Serial.print(val); //Printing in serial monitor
//val = map(val, 300, 750, 0, 100);
if (val > limit)
{
tone(8, 650);
}
delay(300);
noTone(8);
//-----
//----- servo motor -----//
//-----
sen1Value = 0.01723 * readUltrasonicDistance(6, 6);
if (sen1Value < 100)
{
servo_7.write(90);
Serial.print(" || Door Open! ; Distance = ");
Serial.print(sen1Value);
}

```

```

Serial.print("\n");
}
else
{
servo_7.write(0);
Serial.print(" || Door Closed! ; Distance = ");
Serial.print(sen1Value);
Serial.print("\n");
}
delay(10); // Delay a little bit to improve simulation performance
}

```

## OUTPUT:

