Assignment 4

Name	Durairasu S
Team ID	PNT2022TMID47401
Project Name	IoT Based Safety Gadget for Child Safety Monitoring & Notification

1.Write Code and connections in wokwi for ultrasonic sensor. whatever distance is less than 100 cms send "Alert" to ibm cloud aand display in device recent events.


```
#include <WiFi.h>
#include <PubSubClient.h>
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "c4e77h"//IBM ORGANITION ID
#define DEVICE_TYPE "nodemcu"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "6553"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "S3FUWX1R&OpcJZ-ijf" //Token
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribetopic[] = "iot-2/cmd/test/fmt/String";
char authMethod[] = "use-token-auth";
```

```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback ,wifiClient);
const int trigPin = 5;
const int echoPin = 18;
#define SOUND_SPEED 0.034
long duration;
float distance;
void setup() {
 Serial.begin(115200);
  pinMode(trigPin, OUTPUT);
 pinMode(echoPin, INPUT);
 wificonnect();
 mqttconnect();
void loop()
  digitalWrite(trigPin, LOW);
  delayMicroseconds(2);
  digitalWrite(trigPin, HIGH);
  delayMicroseconds(10);
  digitalWrite(trigPin, LOW);
  duration = pulseIn(echoPin, HIGH);
  distance = duration * SOUND_SPEED/2;
  Serial.print("Distance (cm): ");
```

```
Serial.println(distance);
  if(distance<100)</pre>
   Serial.println("ALERT!!");
    delay(1000);
   PublishData(distance);
   delay(1000);
   if (!client.loop()) {
     mqttconnect();
 delay(1000);
void PublishData(float dist) {
 mqttconnect();
 String payload = "{\"Distance\":";
 payload += dist;
 payload += ",\"ALERT!!\":""\"Distance less than 100cms\"";
 payload += "}";
 Serial.print("Sending payload: ");
  Serial.println(payload);
```

```
if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");
  } else {
    Serial.println("Publish failed");
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
     Serial.println();
void wificonnect()
  Serial.println();
  Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);
```

```
while (WiFi.status() != WL_CONNECTED) {
   delay(500);
   Serial.print(".");
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
 } else {
   Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {</pre>
   //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
Serial.println("data: "+ data3);
data3="";
```



Wokwi link: https://wokwi.com/projects/new/esp32

