

Project Development - Delivery Of Sprint-1

Team id	PNT2022TMID46762
Project name	IOT based safety gadget for child safety monitoring and notification
Date	14-11-2022
Maximum marks	4 marks

NOTIFICATION:

This coding will make connection between IoT Device & Parent's application. When the child crosses the geofence, a message will be notified on the parent's application.

Coding:

```
#include<WiFi.h> //library for wifi
#include<PubSubClient.h> //library for MQTT
void callback(char* subscribe topic, byte* payload, unsigned int payload length);
//-----credentials of IBM Account-----
#define ORG "frpi8s" // IBM ORGANIZATION ID
#define DEVICE_TYPE "NodeMCU" //DEVICE TYPE MENTIONED IN IOT WATSON PLATFORM
#define DEVICE_ID "12345" //DEVICE ID MENTIONED IN IOT WATSON PLATFORM
#define TOKEN "12345678" //Token String data3;float dist;
//-----customize the above value-----
char server[] = ORG
".messaging.internetofthings.ibmcloud.com"; //servername
char publish topic[] = "ultrasonic/evt/Data/fmt/json"; /*topic name and type of event perform and format in which data to be send*/
char subscribe topic[] = "ultrasonic/cmd/test/fmt/String"; /*command REPRESENT Command type and COMMAND IS TEST OF FORMAT STRING*/
```

```

char authMethod[]="use-token-auth";//authentication method char
token[]=TOKEN;
char clientid[]="d:" ORG ":" DEVICE_TYPE":" DEVICE_ID;//CLIENT ID
// WiFiClient wifiClient;// creating an instance for wificlient
PubSubClient client(server, 1883 , callback , wifiClient);/*calling the
predefined
client id by passing parameter like server id,portand wificredential*/
int LED =4;
int trig =5; int echo=18; void setup(){
Serial.begin(115200); pinMode(trig,OUTPUT); pinMode(echo,INPUT);
pinMode(LED,OUTPUT); delay(10); Serial.println(); wificonnect();
mqttconnect();
void loop() { digitalWrite(trig,LOW); digitalWrite(trig,HIGH);
delayMicroseconds(10); digitalWrite(trig,LOW);
float dur=pulseIn(echo,HIGH); float dist=(dur * 0.0343)/2;
Serial.print("distance in
cm"); Serial.println(dist); PublishData(dist);
delay(1000);
if (!client.loop()){ mqttconnect();
}}
/*.....retriving to cloud. ....
*/
void PublishData(float dist){ mqttconnect();//function call for connecting
to ibm
/*creating the string in form of JSON to update the data to ibm cloud*/
String
object;
if(dist<100)
{
digitalWrite(LED,HIGH); Serial.println("no object is near");
object="Near";
}
else{
digitalWrite(LED,LOW); Serial.println("no object found"); object="No";
}S
tring payload="{\"distance\":"; payload +=dist;
payload +="," \"object\":\"; payload += object;
payload += "\}";
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishtopic, (char*) payload.c_str())){
Serial.println("Publish ok");/* if its sucessfully upload data on the

```

```

cloud then it will print publish ok in serial monitor or else it will print
publish
failed*/
} else{ Serial.println("Publish failed");
}
}
void mqttconnect(){ if(!client.connected()){
Serial.print("Reconnecting client to "); Serial.println(server);
while(!!!client.connect(clientid,authMethod,
token)){ Serial.print("."); delay(500);
}
initManagedDevice();
Serial.println();
}
}
void wificonnect()//function defenition for wificonnect
{
Serial.println(); Serial.print("Connecting to ");
WiFi.begin("vivo 1816", "taetae95",6);//PASSING THE WIFI
CREDENTIALS TO
ESTABLISH CONNECTION
while (WiFi.status() !=WL_CONNECTED){ delay(500);
Serial.print(".");
}
Serial.println(""); Serial.println("WiFi connected"); Serial.println("IP
address");
Serial.println(WiFi.localIP());
}
void initManagedDevice(){ if(client.subscribe(subscribetopic)){
Serial.println((subscribetopic)); Serial.println("subscribe to cmd OK");
}else{
}
}
Serial.println("subscribe to cmd failed");
void callback(char* subscribetopic,byte*payload,unsigned int
payloadLength)
{
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic); for(int i=0; i< payloadLength; i++){
//Serial.print((char)payload[i]); data3 +=(char)payload[i];
}
//Serial.println("dta: "+ data3);

```

```

//if(data3=="Near")
//{
//Serial.println(data3);
//digitalWrite(LED,HIGH);
//}
//else //{
//Serial.println(data3);
//digitalWrite(LED,LOW);//} data3="";
}

```

Schematic diagram

