```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

#### ▼ READ DATASET AND PRE PROCESSING

```
df = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
df.head()
```

8		v1	v2	Unnamed: 2	Unnamed:	Unnamed: 4
	0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
	1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
	2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
	3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
    # Column Non-Null Count Dtype
--- 0 v1 5572 non-null object
1 v2 5572 non-null object
dtypes: object(2)
memory usage: 87.2+ KB
```

```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

# Create Model and Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
<pre>activation_1 (Activation)</pre>	(None, 1)	0

\_\_\_\_\_

Total params: 96,337 Trainable params: 96,337 Non-trainable params: 0

# Compile the Model

model.compile(loss='binary\_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])

#### ▼ Train and Fit the Model

```
Epoch 1/10
30/30 [============== ] - 12s 286ms/step - loss: 0.3377 - accuracy: 0
Epoch 2/10
Epoch 3/10
30/30 [============= ] - 10s 327ms/step - loss: 0.0395 - accuracy: 0
Epoch 4/10
Epoch 5/10
Epoch 6/10
Epoch 7/10
30/30 [============= ] - 9s 316ms/step - loss: 0.0115 - accuracy: 0.9
Epoch 8/10
Epoch 9/10
30/30 [============= ] - 9s 310ms/step - loss: 0.0065 - accuracy: 0.9
Epoch 10/10
30/30 [============= ] - 10s 346ms/step - loss: 0.0064 - accuracy: 0
<keras.callbacks.History at 0x7f03f70fe810>
```

### Save The Model

```
model.save('sms_classifier.h5')
```

## Preprocessing the Test Dataset

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
```

## Testing the Model

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

Loss: 0.135 Accuracy: 0.982

Test set

Colab paid products - Cancel contracts here