

## Amala Ruban S

```
import pandas as pd
import numpy as np
from keras import utils
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
%matplotlib inline
```

```
from google.colab import drive
drive.mount('/content/drive')
```

Mounted at /content/drive

```
ls
```

[drive/](#) [sample\\_data/](#)

## READ DATASET

```
df = pd.read_csv('/content/drive/MyDrive/IBM_PROJECTS/spam.csv',delimiter=',',encoding='la
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
		crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

## PREPROCESSING

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
```

<class 'pandas.core.frame.DataFrame'>

```

RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
#   Column  Non-Null Count  Dtype
---  -
0    v1      5572 non-null     object
1    v2      5572 non-null     object
dtypes: object(2)
memory usage: 87.2+ KB

```

```

sns.countplot(df.v1)
plt.xlabel('Label')
plt.title('Number of ham and spam messages')

```

```


/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43: FutureWarning: Pas
FutureWarning

```

```

Text(0.5, 1.0, 'Number of ham and spam messages')

```



```

X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)

```

Saved successfully!

```

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)

```

```

max_words = 1000
max_len = 100
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = utils.pad_sequences(sequences,maxlen=max_len)

```

```

sequences_matrix.shape

```

```

(4736, 100)

```

```
sequences_matrix.ndim
```

```
2
```

```
sequences_matrix = np.reshape(sequences_matrix,(4736,100,1))
```

```
sequences_matrix.ndim #3d shape verification to proceed to RNN LSTM
```

```
3
```

```
from keras.models import Sequential
from keras.layers import Dense
from keras.layers import LSTM
from keras.layers import Embedding
```

```
model = Sequential()
model.add(Embedding(max_words,50,input_length=max_len))
```

```
model.add(LSTM(units=64,input_shape = (sequences_matrix.shape[1],1),return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64))
model.add(Dense(units = 256,activation = 'relu'))
model.add(Dense(units = 1,activation = 'sigmoid'))
```

```
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

Model: "sequential"

Layer (type)	Output Shape	Param #
=====		
embedding (Embedding)	(None, 100, 50)	50000
	(None, 100, 64)	29440
	(None, 100, 64)	33024
lstm_2 (LSTM)	(None, 100, 64)	33024
lstm_3 (LSTM)	(None, 64)	33024
dense (Dense)	(None, 256)	16640
dense_1 (Dense)	(None, 1)	257

```
=====
Total params: 195,409
Trainable params: 195,409
Non-trainable params: 0
=====
```

Saved successfully!



## FIT THE MODEL

```
M = model.fit(sequences_matrix,Y_train,batch_size=128,epochs=7,validation_split=0.2)
```

```
Epoch 1/7
30/30 [=====] - 33s 816ms/step - loss: 0.3221 - accuracy: 0
Epoch 2/7
30/30 [=====] - 22s 740ms/step - loss: 0.0905 - accuracy: 0
Epoch 3/7
30/30 [=====] - 22s 738ms/step - loss: 0.0625 - accuracy: 0
Epoch 4/7
30/30 [=====] - 22s 740ms/step - loss: 0.0518 - accuracy: 0
Epoch 5/7
30/30 [=====] - 22s 742ms/step - loss: 0.0381 - accuracy: 0
Epoch 6/7
30/30 [=====] - 24s 819ms/step - loss: 0.0278 - accuracy: 0
Epoch 7/7
30/30 [=====] - 22s 733ms/step - loss: 0.0226 - accuracy: 0
```



## SAVE THE MODEL

```
model.save
```

```
<bound method Model.save of <keras.engine.sequential.Sequential object at
0x7f8604b54290>>
```

## TEST THE MODEL

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = utils.pad_sequences(test_sequences,maxlen=max_len)
```

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 4s 67ms/step - loss: 0.0370 - accuracy: 0.9
```

Saved successfully!


```
l = accr[0]
a =accr[1]
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(l,a))
```

```
Test set
Loss: 0.037
Accuracy: 0.984
```

## ACCURACY AND LOSS GRAPH

```
results = pd.DataFrame({"Train Loss": M.history['loss'], "Validation Loss": M.history['val
fig, ax = plt.subplots(nrows=2, figsize=(16, 9))
results[["Train Loss", "Validation Loss"]].plot(ax=ax[0])
results[["Train Accuracy", "Validation Accuracy"]].plot(ax=ax[1])
```

```
ax[0].set_xlabel("Epoch")  
ax[1].set_xlabel("Epoch")  
plt.show()
```



Saved successfully!



[Colab paid products](#) - [Cancel contracts here](#)

✓ 0s completed at 09:39



Saved successfully!

×