

Ezhilarasi v(110819104006)**

```
import pandas as pd
import numpy as np
from keras import utils
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
%matplotlib inline
```

```
from google.colab import drive
drive.mount('/content/drive')
```

Mounted at /content/drive

```
ls
```

[drive/](#) [sample_data/](#)

READ DATASET

```
df = pd.read_csv('/content/drive/MyDrive/IBM PROJECT/spam.csv',delimiter=',',encoding='lat
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

PREPROCESSING


```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
#   Column  Non-Null Count  Dtype
---  -
0    v1      5572 non-null     object
1    v2      5572 non-null     object
dtypes: object(2)
memory usage: 87.2+ KB
```

```
sns.countplot(df.v1)
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

```
/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43: FutureWarning: Pas
FutureWarning
Text(0.5, 1.0, 'Number of ham and spam messages')
```



```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
max_words = 1000
max_len = 100
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = utils.pad_sequences(sequences,maxlen=max_len)
```

```
sequences_matrix.shape
```

```
(4736, 100)
```

```
sequences_matrix.ndim
```

```
2
```

```
sequences_matrix = np.reshape(sequences_matrix,(4736,100,1))
```

```
sequences_matrix.ndim #3d shape verification to proceed to RNN LSTM
```

```
3
```

```
from keras.models import Sequential
from keras.layers import Dense
from keras.layers import LSTM
from keras.layers import Embedding
```

```
model = Sequential()
model.add(Embedding(max_words,50,input_length=max_len))
```

```
model.add(LSTM(units=64,input_shape = (sequences_matrix.shape[1],1),return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64))
model.add(Dense(units = 256,activation = 'relu'))
model.add(Dense(units = 1,activation = 'sigmoid'))
```

```
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

```
Model: "sequential"
```


Layer (type)	Output Shape	Param #
=====		
embedding (Embedding)	(None, 100, 50)	50000
lstm (LSTM)	(None, 100, 64)	29440
lstm_1 (LSTM)	(None, 100, 64)	33024
lstm_2 (LSTM)	(None, 100, 64)	33024
lstm_3 (LSTM)	(None, 64)	33024
dense (Dense)	(None, 256)	16640
dense_1 (Dense)	(None, 1)	257

```
=====
Total params: 195,409
Trainable params: 195,409
Non-trainable params: 0
```

FIT THE MODEL

```
M = model.fit(sequences_matrix,Y_train,batch_size=128,epochs=7,validation_split=0.2)
```

```
Epoch 1/7
30/30 [=====] - 44s 1s/step - loss: 0.3291 - accuracy: 0.89
Epoch 2/7
30/30 [=====] - 22s 743ms/step - loss: 0.0841 - accuracy: 0
Epoch 3/7
30/30 [=====] - 22s 745ms/step - loss: 0.0546 - accuracy: 0
Epoch 4/7
30/30 [=====] - 22s 749ms/step - loss: 0.0436 - accuracy: 0
Epoch 5/7
30/30 [=====] - 25s 822ms/step - loss: 0.0319 - accuracy: 0
Epoch 6/7
30/30 [=====] - 23s 757ms/step - loss: 0.0278 - accuracy: 0
Epoch 7/7
30/30 [=====] - 23s 754ms/step - loss: 0.0217 - accuracy: 0
```



SAVE THE MODEL

```
model.save
```

```
<bound method Model.save of <keras.engine.sequential.Sequential object at
0x7f5888cf3d50>>
```

TEST THE MODEL

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = utils.pad_sequences(test_sequences,maxlen=max_len)
```

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 4s 66ms/step - loss: 0.0747 - accuracy: 0.9
```




```
l = accr[0]
a =accr[1]
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(l,a))
```

```
Test set
Loss: 0.075
Accuracy: 0.983
```

ACCURACY AND LOSS GRAPH

```
results = pd.DataFrame({"Train Loss": M.history['loss'], "Validation Loss": M.history['val
fig, ax = plt.subplots(nrows=2, figsize=(16, 9))
results[["Train Loss", "Validation Loss"]].plot(ax=ax[0])
results[["Train Accuracy", "Validation Accuracy"]].plot(ax=ax[1])
```

```
ax[0].set_xlabel("Epoch")  
ax[1].set_xlabel("Epoch")  
plt.show()
```



[Colab paid products](#) - [Cancel contracts here](#)

✓ 0s completed at 9:12 AM

