

```

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping

```

## ▼ READ DATASET AND PRE PROCESSING

```

df = pd.read_csv('/content/spam.csv', delimiter=',', encoding='latin-1')
df.head()

```

|   | v1   | v2  | Unnamed: 2 | Unnamed: 3 | Unnamed: 4 |
|---|------|---|------------|------------|------------|
| 0 | ham  | Go until jurong point, crazy.. Available only ... | NaN        | NaN        | NaN        |
| 1 | ham  | Ok lar... Joking wif u oni...                     | NaN        | NaN        | NaN        |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | NaN        | NaN        | NaN        |
| - | .    | U dun sav so early hor... U c already then        | .. ..      | .. ..      | .. ..      |

```

df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'], axis=1, inplace=True)
df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
#   Column  Non-Null Count  Dtype
---  -
0    v1      5572 non-null     object
1    v2      5572 non-null     object
dtypes: object(2)
memory usage: 87.2+ KB

```

```

X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)

```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)

max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

## ▼ Create Model and Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
```

```
model.summary()
```

Model: "model"

| Layer (type)              | Output Shape    | Param # |
|---------------------------|-----------------|---------|
| =====                     |                 |         |
| inputs (InputLayer)       | [(None, 150)]   | 0       |
| embedding (Embedding)     | (None, 150, 50) | 50000   |
| lstm (LSTM)               | (None, 64)      | 29440   |
| FC1 (Dense)               | (None, 256)     | 16640   |
| activation (Activation)   | (None, 256)     | 0       |
| dropout (Dropout)         | (None, 256)     | 0       |
| out_layer (Dense)         | (None, 1)       | 257     |
| activation_1 (Activation) | (None, 1)       | 0       |
| =====                     |                 |         |
| Total params: 96,337      |                 |         |
| Trainable params: 96,337  |                 |         |
| Non-trainable params: 0   |                 |         |


## ▼ Compile the Model

```
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

## ▼ Train and Fit the Model

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
          validation_split=0.2)
```

```
Epoch 1/10
30/30 [=====] - 12s 286ms/step - loss: 0.3377 - accu:
Epoch 2/10
30/30 [=====] - 9s 301ms/step - loss: 0.0934 - accu:
Epoch 3/10
30/30 [=====] - 10s 327ms/step - loss: 0.0395 - accu:
Epoch 4/10
30/30 [=====] - 9s 317ms/step - loss: 0.0311 - accu:
Epoch 5/10
30/30 [=====] - 9s 294ms/step - loss: 0.0213 - accu:
Epoch 6/10
30/30 [=====] - 9s 305ms/step - loss: 0.0167 - accu:
Epoch 7/10
30/30 [=====] - 9s 316ms/step - loss: 0.0115 - accu:
Epoch 8/10
30/30 [=====] - 9s 286ms/step - loss: 0.0081 - accu:
Epoch 9/10
30/30 [=====] - 9s 310ms/step - loss: 0.0065 - accu:
Epoch 10/10
30/30 [=====] - 10s 346ms/step - loss: 0.0064 - accu:
<keras.callbacks.History at 0x7f03f70fe810>
```



## ▼ Save The Model

```
model.save('sms_classifier.h5')
```

## ▼ Preprocessing the Test Dataset

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
```

## ▼ Testing the Model

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 1s 23ms/step - loss: 0.1346 - accuracy: 0.9999
```

```
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(accur[0],accur[1]))
```

```
Test set
```

```
Loss: 0.135
```

```
Accuracy: 0.982
```

[Colab paid products](#) - [Cancel contracts here](#)

✓ 0s completed at 09:37

