

INDUSTRY – SPECIFIC INTELLIGENT FIRE MANAGEMENT SYSTEM

ASSIGNMENT – 4

Write code and connections in wokwi for the ultrasonic sensor.

Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.

SOURCE CODE:

```
#include <WiFi.h>

#include <PubSubClient.h>

#define ORG "486ral"

#define DEVICE_TYPE "IOT"

#define DEVICE_ID "id07"

#define TOKEN "123456789"

#define trigpin 5

#define echopin 18


char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/data/fmt/json";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;


WiFiClient wifiClient;

PubSubClient client(server, 1883, wifiClient);
```

```
long duration;
```

```
float dist;
```

```
void setup()
```

```
{
```

```
  Serial.begin(9900);
```

```
  pinMode(trigpin, OUTPUT);
```

```
  pinMode(echopin, INPUT);
```

```
  wifiConnect();
```

```
  mqttConnect();
```

```
}
```

```
void loop() {
```

```
  publishData();
```

```
  delay(500);
```

```
  if (!client.loop())
```

```
  {
```

```
    mqttConnect();
```

```
  }
```

```
}
```

```
void wifiConnect()
{
  Serial.print("Connecting to ");
  Serial.print("Wifi");
  WiFi.begin("Wokwi-GUEST", "", 6);
  while (WiFi.status() != WL_CONNECTED)
  {
    delay(500);
    Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: ");
  Serial.println(WiFi.localIP());
}
```

```
void mqttConnect()
{
  if (!client.connected())
  {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    while (!client.connect(clientId, authMethod, token))
    {
      Serial.print(".");
      delay(500);
    }

    Serial.println();
  }
}
```

```

void publishData()
{
    digitalWrite(trigpin,LOW);
    digitalWrite(trigpin,HIGH);
    delayMicroseconds(10);
    digitalWrite(trigpin,LOW);
    duration=pulseIn(echopin,HIGH);
    dist=duration*0.034 /2;
    if(dist<100)
    {

        String payload = "{\"Distance\":\"";
        payload += dist;
        payload += ",";
        payload += "\"Status\":\"";
        payload += "\"Alert\"}\"";

        Serial.print("\n");
        Serial.print("Sending payload: ");
        Serial.println(payload);
        if (client.publish(publishTopic, (char*) payload.c_str()))
        {
            Serial.println("Publish OK");
        }

    }
    if(dist>100)

```

```

{

String payload = "{\"Distance\":\"";
payload += dist;
payload += ",";
payload += "\"Status\":\"";
payload += "\"Normal\"}";

Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishTopic, (char*) payload.c_str()))
{
    Serial.println("Publish OK");
}
else
{

    Serial.println("Publish FAILED");
}
}
}

```

diagram.json:

```

{
  "version": 1,
  "author": "Uri Shaked",
  "editor": "wokwi",
  "parts": [
    { "type": "wokwi-esp32-devkit-v1", "id": "esp", "top": 0, "left": 0, "attrs": { } },
    { "type": "wokwi-hc-sr04", "id": "ultrasonic1", "top": -109.38, "left": 180.61, "attrs": { } }
  ]
}

```

```

],
"connections": [
  [ "esp:TX0", "$serialMonitor:RX", "", [] ],
  [ "esp:RX0", "$serialMonitor:TX", "", [] ],
  [ "ultrasonic1:ECHO", "esp:D18", "green", [ "v0" ] ],
  [ "ultrasonic1:TRIG", "esp:D5", "orange", [ "v0" ] ],
  [
    "ultrasonic1:VCC",
    "esp:VIN",
    "red",
    [ "v22.14", "h-48.86", "v-27.94", "h-253.24", "v173.77" ]
  ],
  [ "ultrasonic1:GND", "esp:GND.2", "black", [ "v250.04", "h-311.59", "v3.06" ] ]
]
}

```

OUTPUT:

The screenshot displays the Wokwi IDE interface. On the left, the code for `esp32-blink.ino` is shown, which includes the necessary libraries, defines the IOT device details, and sets up the ultrasonic sensor pins (D5 for TRIG, D18 for ECHO). The code configures a WiFi client and an MQTT publisher to send distance data to the topic `iot-2/evt/data/fat/json`. The `setup` function initializes the serial monitor and pins, while the `loop` function continuously publishes the distance readings.

On the right, the simulation window shows a 3D model of the ESP32 and the HC-SR04 sensor connected by wires. Below the simulation, the serial output shows the sensor's response to the trigger pulses, indicating a distance of 399.92 cm and a "Normal" status.

```

Sending payload: {"Distance":399.92,"Status":"Normal"}
Publish OK

Sending payload: {"Distance":399.92,"Status":"Normal"}
Publish OK

Sending payload: {"Distance":399.92,"Status":"Normal"}

```

WOKWI LINK: <https://wokwi.com/projects/322410731508073042>

IBM CLOUD OUTPUT:

Connection Information

Recent Events

State

Device Information

Metadata

Diagnostics

Connection Logs

Device Actions

Recent Events

The recent events listed show the live stream of data that is coming and going from this device.

Event	Value	Format	Last Received
data	{"Distance":29.99,"Status":"Alert"}	json	a few seconds ago
data	{"Distance":29.99,"Status":"Alert"}	json	a few seconds ago
data	{"Distance":29.99,"Status":"Alert"}	json	a few seconds ago
data	{"Distance":29.99,"Status":"Alert"}	json	a few seconds ago
data	{"Distance":29.99,"Status":"Alert"}	json	a few seconds ago