

Student Name	Keerthika Radhakrishnan
Student Roll Number	2019504538

ASSIGNMENT-4

Problem Statement:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to IBM cloud and display in device recent events.

Source Code:

```
#include <WiFi.h>
#include <PubSubClient.h>
void callback(char* subscribetopic,byte* payload, unsigned int payloadLength);
#define ORG "ejjbdj"
//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "keekee123"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678" //Token
String data3;
char server[]= ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[]="iot-2/evt/distance/fmt/json";
char subscribeTopic[]="iot-2/cmd/test/fmt/String";
char authMethod[]="use-token-auth";
char token[]=TOKEN;
char clientID[]="d:ORG":DEVICE_TYPE":DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server,1883,callback,wifiClient);
#define ECHO_PIN 12
#define TRIG_PIN 13
#define led 2
void setup() {
// put your setup code here, to run once:
Serial.begin(115200);
pinMode(led, OUTPUT);
pinMode(TRIG_PIN, OUTPUT);
pinMode(ECHO_PIN, INPUT);
wificonnect();
mqttconnect();
}
float readDistanceCM() {
digitalWrite(TRIG_PIN, LOW);// Clear the trigger
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);// Sets the trigger pin to HIGH state for 10 microseconds
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration=pulseIn(ECHO_PIN, HIGH);
//Serial.println(duration);
```

```

//duration = pulseIn(ECHO_PIN, HIGH);
return duration*0.017;
//Serial.println(duration);
}
void loop() {
float distance = readDistanceCM();
//Serial.println(distance);
bool isNearby = distance < 100;
digitalWrite(led, isNearby);
Serial.print("Measured distance: ");
Serial.println(distance);
if(distance<100){
PublishData2(distance);
}else{
PublishData1(distance);
}
//PublishData(distance);
delay(1000);
if(!client.loop()){
mqttconnect();
}
//delay(2000);
}
void PublishData1(float dist){
mqttconnect();
String payload= "{\"distance\":\"";
payload += dist;
payload+="}";
Serial.print("Sending payload:");
Serial.println(payload);
if(client.publish(publishTopic,(char*)payload.c_str())){
Serial.println("publish ok");
} else{
Serial.println("publish failed");
}
}
void PublishData2(float dist){
mqttconnect();
String payload= "{\"ALERT\":\"";
payload += dist;
payload+="}";
Serial.print("Sending payload:");
Serial.println(payload);
if(client.publish(publishTopic,(char*)payload.c_str())){
Serial.println("publish ok");
} else{
Serial.println("publish failed");
}
}
void mqttconnect(){
if(!client.connected()){
Serial.print("Reconnecting to ");

```

```

Serial.println(server);
while(!!!client.connect(clientID, authMethod, token)){
Serial.print(".");
delay(500);
}
initManagedDevice();
Serial.println();
}
}
void wificonnect(){
Serial.println();
Serial.print("Connecting to");
WiFi.begin("Wokwi-GUEST","",6);
while(WiFi.status()!=WL_CONNECTED){
delay(500);
Serial.print(".");
}
Serial.println("");
Serial.println("WIFI CONNECTED");
Serial.println("IP address:");
Serial.println(WiFi.localIP());
}
void initManagedDevice(){
if(client.subscribe(subscribeTopic)){
Serial.println((subscribeTopic));
Serial.println("subscribe to cmd ok");
}else{
Serial.println("subscribe to cmd failed");
}
}
void callback(char* subscribeTopic, byte* payload, unsigned int
payloadLength){
Serial.print("callback invoked for topic:");
Serial.println(subscribeTopic);
for(int i=0; i<payloadLength; i++){
data3 += (char)payload[i];
}
Serial.println("data:"+ data3);
if(data3=="lighton"){
Serial.println(data3);
digitalWrite(led,HIGH);
}else{
Serial.println(data3);
digitalWrite(led,LOW);
}
data3="";
}
}

```

Wokwi Link:

<https://wokwi.com/projects/347051211252302418>

Normal and Alert case:

The screenshot displays the Wokwi IDE interface. On the left, the 'sketch.ino' file contains the following C++ code:

```
1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 void callback(char* topic, byte* payload, unsigned int payloadLength);
4 #define ORG "ejjbdj" //IBM ORGANIZATION ID
5 #define DEVICE_TYPE "ESP32" //Device type mentioned in ibm watson IOT Platform
6 #define DEVICE_ID "keekee123" //Device ID mentioned in ibm watson IOT Platform
7 #define TOKEN "12345678" //Token
8 String data3;
9 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
10 char publishTopic[] = "iot-2/evt/distance/fmt/json";
11 char subscribeTopic[] = "iot-2/cmd/test/fmt/String";
12 char authMethod[] = "use-token-auth";
13 char token[] = TOKEN;
14 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
15 WiFiClient wifiClient;
16 PubSubClient client(server, 1883, callback, wifiClient);
17 #define ECHO_PIN 12
18 #define TRIG_PIN 13
19 #define led 2
20 void setup() {
21   // put your setup code here, to run once:
22   Serial.begin(115200);
23   pinMode(led, OUTPUT);
24   pinMode(TRIG_PIN, OUTPUT);
25   pinMode(ECHO_PIN, INPUT);
26   wifiConnect();
27   mqttConnect();
28 }
29 float readDistanceCM() {
30   digitalWrite(TRIG_PIN, LOW); // Clear the trigger
31   delayMicroseconds(2);
32   digitalWrite(TRIG_PIN, HIGH); // Sets the trigger pin to HIGH state for 10 microseconds
33   delayMicroseconds(10);
34   digitalWrite(TRIG_PIN, LOW);
```

The right side of the IDE shows a simulation of the hardware. It includes an HC-SR04 ultrasonic sensor and an ESP32 microcontroller board. The sensor is connected to the ESP32 via a breadboard. The simulation controls (play, pause, stop) and a timer (01:55.685) are visible. The console output shows the following sequence of events:

```
Measured distance: 89.96
Sending payload:{"ALERT":89.96}
publish ok
Measured distance: 89.96
Sending payload:{"ALERT":89.96}
publish ok
Reconnecting to ejjbdj.messaging.internetofthings.ibmcloud.com
```

The bottom of the image shows a Windows taskbar with the system clock at 22:08 on 01-11-2022, and the weather as 25°C Cloudy.

IBM Cloud Storage

[illegible]