Problem statement :
IoT based safety gadget for child safety monitoring and notification.
Domain:
Internet of Things Assignment 4: Distance detection using ultrasonic sensor
ASSIGNMENT 4:
Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cm send "alert" to IBM cloud and display in device recent events.
WOWKI LINK:
hu // h i / //- /- /- /- /- /- /- /-
https://wokwi.com/projects/347922168846221908
BY,
SAMEERA N (623519106030) MYTHILI T (623519106020) YOGESHWARI V (623519106045) SOWMIYA S (623519106038)

```
Solution:
#include<WiFi.h>
#include<WiFiClient.h>#inclu
de<PubSubClient.h>constinttr
igPin = 5; constintechoPin =
18;
//define sound speed in cm/uS
#define SOUND SPEED
0.034#define CM TO INCH
0.393701long duration;
floatdistanceCm;
floatdistanceInch;
void callback(char* subscribetopic, byte* payload,unsignedintpayloadLength); //-----
credentials of IBM Accounts-----
#define ORG "tfltte"//IBM ORGANITION ID
#define DEVICE_TYPE "esp32"//Device type mentioned in ibmwatson IOT Platform
#define DEVICE ID "SAMEERA"//Device ID mentioned in ibmwatson IOT Platform
#define TOKEN "8754774055 "//Token
String data3;
//-----Customise the above values -----char server[] = ORG
".messaging.internetofthings.ibmcloud.com";// Server NamecharpublishTopic[] = "iot-
2/evt/Data/fmt/json";// topic name and type of event perform and format in which data
to be send
charsubscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRINGcharauthMethod[] = "use-token-auth";// authentication
methodchar token[] = TOKEN; charclientId[] = "d:" ORG ":" DEVICE TYPE ":"
DEVICE ID;//client id
WiFiClientwifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient);
voidsetup() {
Serial.begin(115200); // Starts the serial
communicationpinMode(trigPin, OUTPUT); // Sets the trigPin
as an OutputpinMode(echoPin, INPUT); // Sets the echoPin as
an InputSerial.println(); wificonnect(); mqttconnect();
voidloop() { // Clears the
trigPindigitalWrite(trigPin,
LOW);
      delayMicroseconds(2);
// Sets the trigPin on HIGH state for 10 micro
secondsdigitalWrite(trigPin, HIGH);
delayMicroseconds(10); digitalWrite(trigPin, LOW);
```

```
// Reads the echoPin, returns the sound wave travel time in microseconds
                                                                        duration
= pulseIn(echoPin, HIGH);
// Calculate the distance
distanceCm = duration * SOUND_SPEED/2;
// Convert to inchesdistanceInch =
distanceCm * CM_TO_INCH;
// Prints the distance in the Serial Monitor
Serial.print("Distance (cm): ");
Serial.println(distanceCm);
Serial.print("Distance (inch): ");
Serial.println(distanceInch);
PublishData(distanceCm);
delay(1000);
              if
(!client.loop()) {
mqttconnect();
  }
     voidPublishData(float Cm) {
mqttconnect();//function call for connecting to ibm
/*
      creating the String in in form JSon to update the data to ibm
cloud
String payload = "{\"Distance (cm)\":";
payload += Cm; payload += "}";
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it
will print publish ok in Serial monitor or else it will print publish failed
Serial.println("Publish failed");
   } voidmqttconnect() {
if (!client.connected()) {
while(!!!client.connect(clientId, authMethod, token)) {
Serial.print(".");
                      delay(500);
initManagedDevice();
Serial.println();
  } } voidwificonnect() //function defination for
wificonnect {
Serial.println();
Serial.print("Connecting to ");
```

```
WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the
connectionwhile (WiFi.status() != WL_CONNECTED) { delay(500);
Serial.print(".");
 }
Serial.println("");
Serial.println("WiFi connected");
Serial.println("IP address: ");
Serial.println(WiFi.localIP());
}
voidinitManagedDevice() {
if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
Serial.println("subscribe to cmd OK");
 } else
 {
Serial.println("subscribe to cmd FAILED");
 unsignedintpayloadLength) {
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
for (inti = 0; i<payloadLength; i++) {</pre>
//Serial.print((char)payload[i]); data3
+= (char)payload[i];
 }
}
```

Output:

