## **ASSIGNMENT 4**

## Ultrasonic sensor simulation in Wokwi

PROJECT NAME:GAS LEAKAGE MONITERING AND ALERTING SYSTEM

**TEAM LEAD: GOLLA VEENA** 

**TEAM MEMBER 1: NISHWANTH KUMAR.M** 

**TEAM MEMBER 2: DHAYALAN.G** 

**TEAM MEMBER3: MOHAMAD YUSUF.S** 

**Question:** Write a code and connections in wokwi for the ultrasonic sensor. Whenever the distanceis less than 100cms send an "Alert" to IBM cloud and display in the device recent events.

Wokwi simulation link: <a href="https://wokwi.com/projects/347124503089775188">https://wokwi.com/projects/347124503089775188</a>

**WOKWI OUTPUT SCREENSHOT:** 

```
₩OKWÎ 🖹 SAVE 🔻 🧀 SHARE 🛡
                                                                                                                                                                                                       Docs
                                                                                                                                                                                                                    sketch.ino diagram.json Library Manager 🕶
                                                                                                                  Simulation
                                                                                                                                                                                                   Ō00:30.796 (₹)99%
             void setup() {
   Serial.begin(115200);
   pinMode(LED_BUILTIN, OUTPUT);
   pinMode(TRIG_PIN, OUTPUT);
   pinMode(ECHO_PIN, INPUT);
                                                                                                                Editing Ultrasonic Distance Sensor
                                                                                                                Distance:
                                                                                                                                                         -0110
            float readDistanceCM() {
              digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
              delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
                                                                                                               Measured distance: 218.94
                                                                                                                Measured distance: 239.84
                                                                                                                Measured distance: 239.84
            void loop() {
   float distance = readDistanceCM();
                                                                                                                Measured distance: 113.56
                                                                                                                person detected
                                                                                                                person detected
                                                                                                                person detected
            else{
| Serial.print("Measured distance: ");
                                                                                                                                                                                                           <u>⊬</u> II □
```

CODE:

```
#define ECHO_PIN 2
#define TRIG_PIN 3
#define organization = "md8rdq"
#define deviceType = "123"
#define deviceId = "123456"
#define authMethod = "token"
#define authToken = "Titik@2002"

void setup() {
    Serial.begin(115200);
    pinMode(LED_BUILTIN, OUTPUT);
    pinMode(TRIG_PIN, OUTPUT);
    pinMode(ECHO_PIN, INPUT);
}
```

```
float readDistanceCM() {
  digitalWrite(TRIG_PIN, LOW);
  delayMicroseconds(2);
  digitalWrite(TRIG_PIN, HIGH);
  delayMicroseconds(10);
  digitalWrite(TRIG_PIN, LOW);
  int duration = pulseIn(ECHO_PIN, HIGH);
  return duration * 0.034 / 2;
void loop() {
  float distance = readDistanceCM();
if(distance<=100)</pre>
  Serial.println(" person detected");
else{
  Serial.print("Measured distance: ");
  Serial.println(readDistanceCM());
  delay(1000);
```





